The documentation and process conversion measures necessary to comply with this revision shall be completed by 30 September 1997.

INCH POUND

MIL-PRF-19500/313C
30 June 1997
SUPERSEDING
MIL-S-19500/313B
14 June 1982

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW POWER
TYPES 2N2432, 2N2432A, JAN, JANTX, JANTXV, JANS, AND JANHC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for low power, high speed chopper, NPN silicon transistors. Four levels of product assurance are provided for each device type as specified in MIL-PRF-19500. One level of product assurance is provided for die.

1.2 Physical dimensions. See figure 1 (T0-18) and figue 2 (JANHC die).

1.3 Maximum ratings.

Type	P_T T_A = +25°C	P_T T_C = +25°C	V_{CBO}	V_{CEO}	V_{ECO}	I_C	T_{STG}	T_J
	mW	mW	V dc	V dc	V dc	mAdc	°C	°C
2N2432	300 1/	600 2/	30	30	15	100	-65 to +200	-65 to +175
2N2432A	300 1/	600 2/	45	45	18	100	-65 to +200	-65 to +175

1/ Derate linearly 2.0 mW/°C above T_A > +25°C.
2/ Derate linearly 4.0 mW/°C above T_C > +25°C.

1.4 Primary electrical characteristics at T_A = 25°C.

Limits	h_{FE1} V_{CE} = 5 V dc I_C = 10 µA dc	h_{FE2} V_{CE} = 5 V dc I_C = 1 mA dc	$h_{FE(inv)1}$ V_{CE} = 10 mA dc I_E = 200 µA dc		$V_{CE(sat)}$ I_C = 10 mA dc I_B = 500 µA dc	$r_{ec(on)}$ I_e = 100 µA ac(rms) I_B = 1 mAdc I_E = 0, f = 1 kHz		$R_{\Theta JC}$
			2N2432	2N2432A		2N2432	2N2432A	
					V dc	Ohms	Ohms	°C/mW
Min	30	80	2	3				
Max		400			.15	20	15	.25


Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Supply Center Columbus, ATTN: DSCC-VAT, 3990 East Broad St., Columbus, OH 43216-5000, by using the addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5961

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.


Symbol	Dimensions				Note
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.178	.195	4.52	4.95	
CH	.170	.210	4.32	5.33	
HD	.209	.230	5.31	5.84	
LC	.100 TP		2.54 TP		6
LD	.016	.021	0.41	0.53	7,8
LL	.500	.750	12.70	19.05	7,8
LU	.016	.019	0.41	0.48	7,8
L_1		.050		1.27	7
L_2	.250		6.35		7
TL	.028	.048	0.71	1.22	3,4
TW	.036	.046	0.91	1.17	10
P	.100		2.54		
Q		.030		0.76	5
r		.010		0.25	11
α	45° TP		45° TP		6



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Beyond r (radius) maximum, TW shall be held for a minimum length of .011 (.28 mm).
4. Symbol TL is measured from HD maximum.
5. Body contour optional within zone defined by CD, HD, and Q.
6. Leads at gauge plane .054 inch (1.37 mm) +.001 inch (0.03 mm) -.000 inch (0.00 mm) below seating plane shall be within .007 inch (0.18 mm) radius of TP relative to tab. Device may be measured by direct methods or by gauge.
7. Symbol LU applies between L_1 and L_2. Dimension LD applies between L_2 and LL minimum. Lead diameter shall not exceed .042 inch (1.07 mm) within L_1 and beyond LL minimum.
8. All three leads.
9. The collector shall be internally connected to the case.
10. Lead designation shall be: lead 1 = emitter, lead 2 = base, lead 3 = collector
11. Symbol r applied to both inside corners of tab.
12. In accordance with ANSI Y14.5M, diameters are equivalent to ϕx symbology.

FIGURE 1. Physical dimensions (T0-18).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	.013	.017	.330	.430
B	.017	.021	.430	.533
ϕC		.0048		.122
ϕD		.0034		.086

NOTES:
1. Chip thickness: 5 to 7 mils
2. Top metal: Aluminum 10,000 Å min, 12,000 Å nominal
3. Back metal: Gold 2,000 Å min, 4,000 Å nominal
4. Backside: Collector

FIGURE 2. JANHC (A-version) die dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics at T_A = 25° C - continued

Limits	$V_{CE(ofs)1}$ I_B = 200 µA dc I_E = 0		$V_{EC(ofs)2}$ I_B = 1 mA dc I_E = 0		$\lvert h_{fe} \rvert$ V_{CE} = 5 V dc I_C = 1 mA dc f = 20 MHz	C_{obo} V_{CB} = 0 mA dc I_E = 0 100 kHz ≤ f ≤ 1 mHz	C_{ibo} V_{EB} = 0 I_C = 0 100 kHz ≤ f ≤ 1 mHz
	2N2432	2N2432A	2N2432	2N2432A			
	mV dc	mV dc	mV dc	mV dc		pF	pF
Min					2		
Max	0.5	0.4	1.0	0.7	10	12	12

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

MILITARY

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Associated specification. The individual item requirements shall be in accordance with MIL-PRF-19500, and as specified herein.

3.2 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

$V_{(BR)ECO}$ - - - Breakdown voltage, emitter to collector, with base open circuited.
$h_{FE(inv)}$ - - - Forward current transfer ratio except that the collector and emitter shall be interchanged.
I_e - - - - - Emitter current (rms)
$r_{ec(on)}$ - - - Small signal emitter to collector on state resistance.
V_{BC} - - - - Base to collector voltage.
$V_{EC(ofs)}$ - - - Emitter to collector offset voltage, i.e., open circuit voltage between emitter and collector when the base to collector junction is forward biased.
V_{ec} - - - - Emitter to collector voltage (rms).

3.3 Interface requirements and physical dimensions. The Interface requirements and physical dimensions shall be as specified in MIL-PRF-19500, and figure 1 (T0-18) and 2 (die) herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

3.3.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.5 Qualification. Devices furnished under this specification shall be products that are authorized by the qualifying activity for listing on the applicable qualified products list before contract award (see 4.2 and 6.2).

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in paragraph 1.3, 1.4, and table I.

3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in paragraphs 4.4.2 and 4.4.3.

4. VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3)

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.1 JANHC devices. JANHC devices shall be qualified in accordance with MIL-PRF-19500.

4.3 Screening (JANS, JANTX, and JANTXV levels only. Screening shall be in accordance with table IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500)	Measurement	
	JANS level	JANTX and JANTXV levels
9	I_{CBO1} and h_{FE1}	Not applicable
11	I_{CBO1}; h_{FE1}; ΔI_{CBO1} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE1} = 15 percent of initial value.	I_{CBO1} and h_{FE3}
12	See 4.3.1	See 4.3.1
13	Subgroups 2 and 3 of table I herein; ΔI_{CBO1} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE1} = 15 percent of initial value.	Subgroup 2 of table I herein; ΔI_{CBO1} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE1} = 15 percent of initial value.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: T_A = room ambient as defined in the general requirements in 4.5 of MIL-STD-750:

JANS level: 2N2432, 2N2432A - - - V_{CB} = 10 V dc; P_T = 300 mW.
JANTX and JANTXV levels: 2N2432 - - - - - - - V_{CB} = 15 V dc; P_T = 300 mW.
2N2432A - - - - - - - V_{CB} = 25 V dc; P_T = 300 mW.
NOTE: No heat sink or forced air cooling on the devices shall be permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

4.3.2 Screening JANHC. Screening shall be in accordance with MIL-PRF-19500. As a minimum, die shall be 100 percent probed to ensure compliance with group A, subgroup 2.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VIa (JANS) and table VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and as follows. Electrical measurements (end-points) shall be in accordance with the table I, group A, subgroup 2 herein.

4.4.2.1 Group B inspection, table VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Condition
B4	1037	V_{CB} = 10 V dc, P_T = 300 mW, T_A = +25°C ±3°C; t_{on} = t_{off} = 3 minutes minimum for 2,000 cycles. No heat sink or forced air cooling on devices shall be permitted.
B5	1027	V_{CB} = 10 V dc, T_A = +125°C ±25°C for 96 hours; P_T = 300 mW at T_A = +100°C or adjusted as required by the chosen T_A to give an average T_J = +275°C. Marking legibility requirements shall not apply
B6	3131	See 4.5.7.

4.4.2.2 Group B inspection, table VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1027	P_T = 300 mW; V_{CB} = 15 V dc for 2N2432; V_{CB} = 25 V dc for 2N2432A
B5	3131	See 4.5.7.

4.4.4 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500 and as follows. Electrical measurements (end- points) shall be in accordance with table I, group A, subgroup 2 herein.

Subgroup	Method	Condition
C2	2036	Test condition E.
C6	1026	P_T = 300 mW; V_{CB} = 15 V dc for 2N2432, V_{CB} = 25 V dc for 2N2432A.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Emitter to collector cutoff current. Method of test shall be in accordance with method 3041 of MIL-STD-750, condition C, except that all references to the collector and emitter of the transistor under test shall be interchanged.

4.5.3 Emitter to collector breakdown voltage. Method of test shall be in accordance with method 3011 of MIL-STD-750, condition D, except that all references to the collector and emitter of the transistor under test shall be interchanged.

4.5.4 Forward current transfer ratio (inverted connection). Method of test shall be in accordance with method 3076 of MIL-STD-750, except that all references to the collector and emitter of the transistor under test shall be interchanged. Then $h_{FE(inv)} = I_E / I_B$

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

4.5.5 Emitter to collector offset voltage. The transistor shall be tested in the circuit of figure 4. The base current shall be adjusted to the specified value. The voltage between the emitter and collector shall be measured using a voltmeter with an input impedance high enough that halving it does not change the measured value within the required accuracy of the measurement.

4.5.6 Small signal emitter to collector on-state resistance. The transistor shall be tested in the circuit of figure 5. The base current shall be adjusted to the specified value and an ac sinusoidal signal current, I_e , of the specified rms value shall be applied between the emitter and collector. The rms voltage V_{ec} , between the emitter and collector shall be measured using an ac voltmeter with an input impedance high enough that halving it does not change the measured value within the required accuracy of the measurement. The small signal emitter to collector on-state resistance shall then be determined as follows:

$$r_{ec(on)} = V_{ec} / I_E$$

where V_{ec} is the rms voltage between the emitter and collector.

4.5.7 Thermal resistance. Thermal resistance measurements shall be conducted in accordance with method 3131 of MIL-STD-750. The following details shall apply:

a. Collector current magnitude during power application shall be 30 mA dc.
b. Collector emitter voltage magnitude shall be 10 V dc.
c. Reference temperature measuring point shall be the case.
d. Reference point temperature shall be selected with $25^\circ C \leq T_R \leq 75^\circ$ and recorded before the test is started.
e. Mounting arrangement shall be with heat sink to case.
f. Maximum limit for $R_{\Theta JC}$ shall be $0.25^\circ C/mW$.

5. PACKAGING

5.1 Packaging. For aquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these perssonel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points' packaging activity within the Military Department or Defense Agency, or within the Military Departments' System Command. Packaging data retrieval is available from the managing Military Departments' or Defense Agencys' automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

5.2 Marking. Unless otherwise specified (see 6.2), marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Breakdown voltage collector to emitter	3011	Bias condition D; I_C = 10 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$			
2N2432				30		V dc
2N2432A				45		V dc
Breakdown voltage collector to base	3001	Bias condition D; I_C = 100 µA dc;	$V_{(BR)CBO}$			
2N2432				30		V dc
2N2432A				45		V dc
Breakdown voltage emitter to collector	3011	Bias condition D; I_E = 100 µA dc; I_E = 0 (see 4.5.3)	$V_{(BR)ECO1}$			
2N2432				15		V dc
2N2432A				18		V dc
Breakdown voltage emitter to collector	3011	Bias condition D; I_E = 10 mA dc; I_B = 0; pulsed (see 4.5.1 and 4.5.3)	$V_{(BR)EC02}$	10		V dc
Collector to base cutoff current	3036	Bias condition D;	I_{CBO}			
2N2432		V_{CB} = 25 V dc			10	nA dc
2N2432A		V_{CB} = 40 V dc			10	nA dc
Collector to emitter cutoff current	304136	Bias condition C;	I_{CES1}			
2N2432		V_{CB} = 25 V dc			10	nA dc
2N2432A		V_{CB} = 40 V dc			10	nA dc
Emitter to collector cutoff current	3041	Bias condition C; V_{EC} = 15 V dc; V_{BC} = 0; (see 4.5.2)	I_{ECS1}		2	nA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 15 V dc	I_{EBO}		2	nA dc
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 10 µA dc;	h_{FE1}	30		
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 1 mA dc;	h_{FE2}	80	400	

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Forward-current transfer ratio (inverted connection)	3076	V_{CE} = 5 V dc; I_C = 0.2 mA dc; (see 4.5.4)	$h_{FE(inv)1}$			
2N2432				2		
2N2432A				3		
Saturation voltage and resistance	3071	I_C = 10 V dc; I_B = 0.5 mA dc;	$V_{CE(sat)}$		0.15	V dc
Emitter to collector offset voltage	----	I_B = 200 µA dc; I_E = 0 mA dc (see 4.5.5 and figure 4)	$V_{EC(ofs)1}$			
2N2432					0.5	mV dc
2N2432A					0.4	mV dc
Emitter to collector offset voltage	----	I_B = 1 mA dc; I_E = 0 mA dc (see 4.5.5 and figure 4)	$V_{EC(ofs)2}$			
2N2432					1.0	mV dc
2N2432A					0.7	mV dc
Subgroup 3						
High-temperature operation:		T_A = +125° C				
Collector to emitter cutoff current	3041	Bias condition C;	I_{CES2}			
2N2432		V_{CB} = 25 V dc			250	nA dc
2N2432A		V_{CB} = 40 V dc			250	nA dc
Emitter to collector cutoff current	3041	Bias condition C; V_{EC} = 15 V dc; V_{BC} = 0; (see 4.5.2)	I_{ECS2}		200	nA dc
Low-temperature operation:		T_A = -55° C				
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 10 µA dc; pulsed (see 4.5.1)	h_{FE3}	10		
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 1 mA dc; pulsed (see 4.5.1)	h_{FE4}	25		
Forward-current transfer ratio (inverted connection)	3076	V_{CE} = 5 V dc; I_E = 200 µA dc; pulsed (see 4.4.4)	$h_{FE(inv)2}$	1.8		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 4						
Small signal emitter collector on state resistance	----	I_B = 1 mA dc; I_E = 0; I_e = 100 µAac(rms); f = 1 kHz (see 4.5.6 and figure 5)	$r_{ec(on)}$			
2N2432					20	Ohms
2N2432A					15	Ohms
Small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 5 V dc; I_C = 1 mA dc; f = 20 MHz	$\|h_{fe}\|$	2	10	
Open circuit output capacitance	3236	V_{CB} = 0; I_E = 0; 100 kHz ≤ f ≤ 1 MHz	C_{obo}		12.0	pF
Input capacitance	3240	V_{EB} = 0 V dc; I_C = 0; 100 kHz ≤ f ≤ 1 MHz	C_{ibo}		12.0	pF
Subgroups 5, 6, 7						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.




FIGURE 4. Emitter to collector offset voltage test circuit.




FIGURE 5. Small-signal emitter-collector on-state resistance test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1).

b. Lead finish (see 3.3.1).

c. Type designation and product assurance level.

d. Packaging requirements (see 5.1).

6.3 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.4 Suppliers of JANHC die. The qualified JANHC suppliers with the applicable letter version (example, JANHCA2N2432 or JANHCA2N2432A) will be identified on the QPL.

JANC ordering information	
PIN	Manufacturer
	12498
2N2432 2N2432A	JANHCA2N2432 JANHCA2N2432A

6.5 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Products List QPL-19500 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center Columbus, DSCC-VQE, Columbus, OH 43216.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - MI
Navy - AS, CG, MC
Air Force - 19, 85

Preparing activity:
DLA - CC

(Project 5961-1769)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-PRF-19500/313C	**2. DOCUMENT DATE (YYMMDD)** 97/06/30

3. DOCUMENT TITLE SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW POWER TYPES 2N2432, 2N2432A, JAN, JANTX, JANTXV, JANS, AND JANHC

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Alan Barone	b. TELEPHONE (Include Area Code) (1) Commercial 614-692-0510 (2) AUTOVON 850-0510
c. ADDRESS (Include Zip Code) Defense Supply Center Columbus ATTN: DSCC-VAT Columbus, OH 43216-5000	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.