The documentation and process conversion measures necessary to comply with this amendment shall be completed by 5 January 2003.

INCH POUND
MIL-PRF-19500/313F
AMENDMENT 1
5 October 2002

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW POWER
TYPES 2N2432, 2N2432A, 2N2432UB, JAN, JANTX, JANTXV, JANS, JANHC AND JANKC

This amendment forms a part of MIL-PRF-19500/313F, dated 27 February 2002 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title, delete and substitute "SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW POWER TYPES 2N2432, 2N2432A, 2N2432UB, 2N2432AUB, JAN, JANTX, JANTXV, JANS, JANHC AND JANKC".

1.2, delete "(UB package)" and substitute "(AUB and UB packages)".

1.3, delete and substitute:

"

Type	P_T T_A = +25°C	V_{CBO}	V_{CEO}	V_{ECO}	I_C	T_{STG}	T_J	$R_{\theta JA}$
	mW	V dc	V dc	V dc	mA dc	°C	°C	°C/W
2N2432	360 (1)	30	30	15	100	-65 to +200	-65 to +175	485
2N2432A	360 (1)	45	45	18	100	-65 to +200	-65 to +175	485
2N2432UB	360 (1)	30	30	15	100	-65 to +200	-65 to +175	485
2N2432AUB	360 (1)	45	45	18	100	-65 to +200	-65 to +175	485

(1) Derate linearly 2.06 mW/°C for T_A > +25°C."

1.4, $h_{FE(inv)1}$ column, delete "V_{CE} = 10 mA dc" and substitute "V_{CE} = 5 V dc, see table I".

PAGE 5

NOTE 6, bonding pad E, delete and substitute "E = .004 inch diameter (0.102 millimeter).".

PAGE 6

FIGURE 4, title, delete "(UB version)" and substitute "(AUB and UB version)".

PAGE 7

3.5 delete and substitute "Marking. Marking shall be in accordance with MIL-PRF-19500.".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.

PAGE 12

TABLE I, subgroup 2, breakdown voltage collector to emitter, inspection column, add “2N2432AUB”.

TABLE I, subgroup 2, collector to base cutoff current, inspection column, add “2N2432AUB”.

TABLE I, subgroup 2, breakdown voltage emitter to collector, inspection column, add “2N2432AUB”.

TABLE I, subgroup 2, collector to base cutoff current, inspection column, add “2N2432AUB”.

PAGE 13

TABLE I, subgroup 2, collector to emitter cutoff current, inspection column, add “2N2432AUB”.

TABLE I, subgroup 2, forward-current transfer ratio (inverted connection), conditions, add “see 1.4”.

TABLE I, subgroup 2, forward-current transfer ratio (inverted connection), add “2N2432AUB”.

TABLE I, subgroup 2, saturation voltage and resistance, conditions, delete and substitute “I_C 10 mA; I_B = 0.5mA; See 1.4”.

TABLE I, subgroup 2, emitter to collector offset voltage, add “2N2432AUB”.

TABLE I, subgroup 2, emitter to collector offset voltage, add “2N2432AUB”.

TABLE I, subgroup 3, collector to emitter cutoff current, add “2N2432AUB”.

PAGE 14

TABLE I, subgroup 4, small-signal emitter collector on state resistance, add “2N2432AUB”.

TABLE I, footnote 4, delete and substitute “Not applicable for JANS devices.”.

PAGE 16

TABLE III, step 1, inspection column, add “2N2432AUB”.

PAGE 20

DD Form 1426, block 3, add “2N2432AUB”.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - MI
Navy - AS, MC
Air Force - 19

Preparing activity:
DLA - CC

(Project 5961-2646)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:16Z
Check the source to verify that this is the current version before use.