The documentation and process conversion measures necessary to comply with this document shall be completed by 3 November 2022.

INCH-POUND

MIL-PRF-19500/315H
w/AMENDMENT 1
3 August 2022
SUPERSEDING
MIL-PRF-19500/315H
12 April 2017

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, NPN, SILICON, POWER
TYPES 2N2880, 2N3749, JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, power transistors. Four levels of product assurance (JAN, JANTX, JANTXV, and JANS) are provided for each encapsulated device.

1.2 Physical dimensions. Type 2N2880, see figure 1 (TO-59), for type 2N3749, see figure 2 (TO-111).

* 1.3 Maximum ratings.

P_T (1) T_A = 25°C	P_T (2) T_C = 100°C	V_{CBO}	V_{CEO}	V_{EBO}	I_C	I_B	$R_{\theta JC}$	T_{STG} and T_{OP}
W	W	V dc	V dc	V dc	A dc	A dc	°C/W	°C
2	30	110	80	8	5	0.5	3.33	-65 to +200

(1) Derate linearly 11.4 mW/°C for T_A > 25°C.

* (2) Derate linearly 300 mW/°C for T_C > 100°C, see figure 3.

1.4 Primary electrical characteristics at T_C = 25°C.

Limits	h_{FE3} (1) V_{CE} = 5 V dc I_C = 5 A dc	h_{FE2} (1) V_{CE} = 2 V dc I_C = 1 A dc	$\|h_{fe}\|$ V_{CE} = 10 V dc I_C = 1 A dc f = 10 MHz	$V_{BE(sat)}$ (1) I_C = 1 A dc I_B = 100 mA dc	$V_{CE(sat)}$ (1) I_C = 1 A dc I_B = 100 mA dc	C_{obo} V_{CB} = 10 V dc I_E = 0 100 kHz ≤ f ≤ 1 MHz
				V dc	V dc	pF
Min	15	40	3			
Max	---	120	12	1.2	0.25	150

(1) Pulsed (see 4.5.1).

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/.

AMSC N/A
FSC 5961

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: “JAN”, “JANTX”, “JANTXV” and "JANS".

1.5.2 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are as follows: "2880" and "3749".

1.5.3 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* FED-STD-H28/1

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.




FIGURE 1. Physical dimensions of transistor type 2N2880 (TO-59).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

Symbol	Dimension				Notes
	in	in	mm	mm	
	Min	Max	Min	Max	
CH	.320	.468	8.13	11.89	
HT		250		6.35	
CD	.318	.380	8.08	9.65	
CD_1	.380	.437	9.65	11.10	
HF	.423	.438	10.74	11.13	
e	.125	.165	3.18	4.19	5, 8, 9
e_1	.110	.145	2.79	3.68	5, 8
A_1	.090	.150	2.29	3.81	
OAH	.570	.763	14.48	19.38	4
UD	.155	.189	3.94	4.80	
SL	.400	.455	10.16	11.56	
SU		.078	---	1.98	10
ϕT	.040	.065	1.02	1.65	
ϕT_1	.040	.070	1.02	1.78	
SD	0.190- 32UNF-2A				4
PS_1	.090	.110	2.29	2.79	5, 8, 9
PS	.185	.215	4.70	5.46	5, 8, 9

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Collector shall be electrically connected to the case. This terminal may be flattened and pierced only when the 90 degree option is used.
4. SD is the outer diameter of coated threads. (Reference: Screw thread standards for Federal Standard H28/1, (FED-STD-H28/1).
5. The orientation of the terminals in relation to the hex flats is not controlled.
6. All three terminals.
7. The case temperature may be measured anywhere on the seating plane within .125 (3.18 mm) of the stud.
8. Terminal spacing measured at the base seat only.
9. Dimensions e, e_1, PS_1, and PS are measured from the center line of terminals.
10. Maximum unthreaded dimension.
11. This dimension applies to the location of the center line of the terminals.
12. A 90 degree angle lead orientation as shown may be used at the option of the manufacturer. All dimensions of the basic outline except e, e_1, and the 120 degree lead angle apply to this option.
13. Terminal -1, emitter; terminal -2, base; terminal -3, collector.
14. A slight chamfer or undercut on one, or both, ends of the hexagonal is optional.

FIGURE 1. Physical dimensions of transistor type 2N2880 (TO-59) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.




FIGURE 2. Physical dimensions of transistor type 2N3749 (TO-111).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

Symbol	Dimension				Notes
	in	in	mm	mm	
	Min	Max	Min	Max	
CH	.320	.458	8.13	11.63	
HT		.250		6.35	5
* e		.505		12.83	
CD	.318	.380	8.08	9.65	
CD_1	.380	.437	9.65	11.10	5
HF	.423	.438	10.74	11.13	
* e_1	.180	.215	4.57	5.46	7
* PS	.180	.215	4.57	5.46	7
* PS1	.080	.110	2.03	2.79	7
A_1	.090	.150	2.29	3.81	4, 8
OAH	.570	.763	14.48	19.38	
SL	.400	.455	10.16	11.56	
SU		.078		1.98	9
ϕT	.040	.065	1.02	1.65	
* ϕT_1	.040	.070	1.02	1.78	6
UD	.155	.189	3.94	4.80	
SD	0.190- 32UNF-2A				10
Z		.002		0.05	
Z_1		.006		0.15	

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Terminal 1 - emitter; terminal 2 - base; terminal 3 - collector; terminal 4 - case.
4. Chamfer or undercut on one, or both, ends of hexagonal portion is optional.
5. The outline contour, with the exception of the hexagon, is optional within cylinder defined by CD_1 and HT.
6. Terminal 4 can be flattened and pierced or hook type. A visual index is required when the flattened and pierced tab terminal contour (identical to the adjacent terminals) option is used.
7. Angular orientation of terminals with respect to hexagon is optional.
8. A_1 dimension does not include sealing flanges.
9. SU is the length of incomplete or undercut threads.
10. SD is the outer diameter of coated threads. (Reference: Screw thread standards for Federal Standard H28/1 , (FED-STD-H28/1).

FIGURE 2. Physical dimensions of transistor type 2N3749 (TO-111) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500 and figure 1, 2N2880 (TO-59), and figure 2, 2N3749 (TO-111).

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I herein.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4.VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3)

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

4.3 Screening (JANS, JANTX, and JANTXV). Screening shall be in accordance with table E-IVB of MIL-PRF-19500 (JANS, JANTX, and JANTXV), and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for JANS level	Measurements for JANTX and JANTXV levels
(1) 3c	Thermal impedance, method 3131 of MIL-STD-750 (see 4.3.1)	Thermal impedance, method 3131 of MIL-STD-750 (see 4.3.1)
9	I_{CBO1} and h_{FE2}	I_{CBO1}
11	I_{CBO1} and h_{FE2}; ΔI_{CBO1} = 100 percent of initial reading or 50 nA dc, whichever is greater; Δh_{FE2} = +15 percent, -10 percent	I_{CBO1} and h_{FE2} ΔI_{CBO1} = 100 percent of initial reading or 100 nA dc, whichever is greater.
12	See 4.3.2	See 4.3.2
13(a)	Subgroups 2 and 3 of table I herein; ΔI_{CBO1} = 100 percent of initial value or 50 nA dc, whichever is greater; Δh_{FE2} = +15 percent, -10 percent	Subgroup 2 of table I herein ΔI_{CBO1} = 100 percent of initial value or 100 nA dc, whichever is greater; Δh_{FE2} = +20 percent, -10 percent
13(b) (2N3749 only)	Method 1016 of MIL-STD-750, insulation resistance test condition B (short connector, emitter, and base terminals together) R_{ISO} = 10^9 ohms (min)	Method 1016 of MIL-STD-750 insulation resistance test condition B (short connector, emitter, and base terminals together) R_{ISO} = 10^9 ohms (min)

(1) Shall be performed anytime after temperature cycling, screen 3a; TX and TXV levels do not need to be repeated in screening requirements.

* 4.3.1 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, (and V_H where appropriate). Measurement delay time (t_{MD}) = 70 μs max. See table II, group E, subgroup 4 and figure 4 herein.

4.3.2 Power burn-in conditions. Power burn-in conditions (all levels) are as follows:

a. T_J = 187.5 ±12.5°C.

b. $T_A \leq$ 100°C.

c. V_{CE} = 25 ±5 V dc.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIA (JANS) and E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and 4.4.2.1 and 4.4.2.2 herein. Delta measurements shall be in accordance with table III herein.

4.4.2.1 Quality level JANS, table E-VIA of MIL-PRF-19500.

	Subgroup	Method	Condition
	B4	1037	$V_{CE} \geq 5$ V dc; $T_A = 25 \pm 3°C$, 2,000 cycles.
	B5	1027	$V_{CE} \geq 5$ V dc; 96 hours. $P_T = 2$ W at $T_A = 100°C$ or adjusted as required by the chosen T_A to give an average lot $T_J = 275°C$. Marking legibility requirements shall not apply.
	B6	3131	See 4.5.2.
*	B7	3053	Load condition C; 22 devices; c = 0 (unclamped inductive load) (see figure 5). $T_A = 25°C$; duty cycle ≤ 10 percent; $R_S = 0.1\ \Omega$; Test 1, $T_p = 640\ \mu s$, $R_{BB1} = 39\ \Omega$; $V_{BB1} = 20$ V dc; $R_{BB2} = \infty$; $V_{BB2} = 0$; $V_{CC} = 15$ V dc; $I_C = 5$ A dc; L = 1 mH; (0.5 Ω, 5 A dc) (Tower #7870 or equivalent). Test 2, $T_P = 2.88$ ms; $R_{BB1} = 120\ \Omega$; $V_{BB1} = 20$ V dc; $R_{BB2} = \infty$; $V_{BB} = 0$; $V_{CC} = 15$ V dc; $I_C = 1.6$ A dc; L = 10 mH; (0.11 Ω, 12.5 A dc) (Stancor C-2688 or equivalent).
*	B7	3053	See figure 6 and figure 7 (clamped inductive load). $T_A = 25°C$; $I_B = 0.5$ A dc; $I_C = 5$ A dc; $V_{CC} = 55$ V dc.

4.4.2.2 Quality levels JAN, JANTX and JANTXV, table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500.

	Subgroup	Method	Condition
	B3	1027	$T_J = 187.5 \pm 12.5°C$; $T_A \leq 35°C$; $V_{CE} = 25 \pm 5$ V dc.
	B5	3131	See 4.5.2.
*	B7	3053	Load condition C; 22 devices; c = 0 (unclamped inductive load) (see figure 5). $T_A = 25°C$; duty cycle ≤ 10 percent; $R_S = 0.1\ \Omega$. Test 1, $T_p = 640\ \mu s$, $R_{BB1} = 39\ \Omega$; $V_{BB1} = 20$ V dc; $R_{BB2} = \infty$; $V_{BB2} = 0$;
*			$V_{CC} = 15$ V dc; $I_C = 5$ A dc; L = 1 mH; (0.5 Ω, 5 A dc) (Tower #7870 or equivalent). Test 2, $T_P = 2.88$ ms; $R_{BB1} = 120\ \Omega$; $V_{BB1} = 20$ V dc;$R_{BB2} = \infty$; $V_{BB} = 0$; $V_{CC} = 15$ V dc; $I_C = 1.6$ A dc; L = 10 mH; (0.11 Ω, 12.5 A dc) (Stancor C-2688 or equivalent).
*	B7	3053	See figure 6 and figure 7, (clamped inductive load). $T_A = 25°C$; $I_B = 0.5$ A dc; $I_C = 5$ A dc; $V_{CC} = 55$ V dc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows. Delta measurements shall be in accordance with table III herein.

Subgroup	Method	Condition
C2	2036	Test condition A; weight= 10 pounds; time = 15 s.
C2	2036	Thermal strength (terminal torque). Test condition D1; torque = 6 inch-ounces; t = 15 s; (tubulated leads only).
C2	2036	Terminal strength (stud torque). Test condition D2; torque = 15 inch-pound; application time = 15 s.
C2	2036	Terminal strength (tension). Test condition A; weight = 7 pounds ±5 ounces; application time = 15 s (tubulated leads only).
C6	1026	T_J = 187.5 ±12.5°C; $T_A \leq$ 35°C; V_{CE} = 25 ±5 V dc.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table E-IX of MIL-PRF-19500 and as specified in table II herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurements shall be as specified in MIL-STD-750.

4.5.2 Thermal resistance. Thermal resistance measurements shall be conducted in accordance with method 3131 of MIL-STD-750. The following details shall apply:

a. Collector current magnitude during power applications shall be selected with 0.8 A dc $\leq I_C \leq$ 1.2 A dc and recorded before test is started.

b. Collector to emitter voltage magnitude shall be 20 V dc.

c. Reference temperature measuring point shall be the case.

d. Reference point temperature shall be selected with 25°C $\leq t_R$ 75°C and recorded before the test is started.

e. Mounting arrangement shall be with heat sink to case.

f. Maximum limit of $R_{\theta JC}$ shall be 3.33°C/W.

4.5.3 Inspection conditions. Unless otherwise specified herein, all inspections shall be conducted at a case temperature (T_C) of 25°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.1	$Z_{\theta JX}$			°C/W
Breakdown voltage, collector to base	3001	Bias condition D; I_C = 10 μA dc	$V_{(BR)CBO}$	110		V dc
Breakdown voltage, collector to emitter	3011	Bias condition D; I_C = 100 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	80		V dc
Breakdown to voltage, emitter to base	3026	Bias condition D; I_E = 10 μA dc	$V_{(BR)EBO}$	8		V dc
Collector to base cutoff current	3036	Bias condition D; V_{CB} = 80 V dc	I_{CBO1}		0.2	μA dc
Collector to emitter cutoff current	3041	Bias condition A; V_{CE} = 110 V dc; V_{BE} = -0.5 V dc	I_{CEX1}		1.0	μA dc
Collector to emitter cutoff current	3041	Bias condition D; V_{CE} = 60 V dc	I_{CEO}		20	μA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 6 V dc	I_{EBO}		0.2	μA dc
Forward current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 50 mA dc	h_{FE1}	40	120	
Forward current transfer ratio	3076	V_{CE} = 2 V dc; I_C = 1 A dc pulsed (see 4.5.1)	h_{FE2}	40	120	
Forward current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 5 A dc pulsed (see 4.5.1)	h_{FE3}	15		
Collector to emitter voltage (saturated)	3071	I_C = 1.0 A dc; I_B = 0.1 A dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$		0.25	V dc
Collector to emitter voltage (saturated)	3071	Test condition A; I_C = 5.0 A dc; I_B = 0.5 A dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		1.5	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued 2/						
Base to emitter voltage (non-saturated)	3066	Test condition B; V_{CE} = 2 V dc; I_C = 1 A dc; pulsed (see 4.5.1)	V_{BE}		1.2	V dc
Base to emitter voltage (saturated)	3066	Test condition A; I_C = 1 A dc; I_B = 0.1 A dc; pulsed (see 4.5.1)	$V_{BE(sat)}$		1.2	V dc
Subgroup 3						
High-temperature operation:		T_A = 150°C				
Collector to emitter cutoff current	3041	Bias condition A; V_{CE} = 80 V dc; V_{BE} = 0.5 V dc	I_{CEX2}		50	µA dc
Collector to base cutoff current	3036	Bias condition D; V_{CB} = 60 V dc	I_{CBO2}		10	µA dc
Low-temperature operation:		T_A = -55°C				
Forward-current cutoff current	3076	V_{CE} = 5 V dc; I_C = 1 A dc	h_{FE4}	15		
Subgroup 4						
Small-signal short- circuit forward-current transfer ratio	3206	V_{CE} = 5 V dc; I_C = 50 mA dc; f = 1 kHz	h_{fe}	40	140	
Multitude of small-signal short- circuit forward current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 1 A dc; f = 10 MHz	$\|h_{fe}\|$	3	12	
Open circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0; 100 kHz ≤ f ≤ 1 MHz	C_{obo}		150	pF
Switching parameters:		See figure 8.				
Pulse delay time			t_d		60	ns
Pulse rise time			t_r		300	ns
Pulse storage time			t_s		1.7	µs
Pulse fall time			t_f		300	ns

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 5						
Safe operating area (dc)	3051	T_C = +100°C; powers application time = 10 s (see figure 9)				
Test 1		V_{CE} = 80 V dc , I_C = 80 mA dc				
Test 2		V_{CE} = 20 V dc, I_C = 1.5 A dc				
* Safe operating area (clamped switching)		See figure 6 and figure 7 (clamped inductive load) T_A = +25°C; I_B = 0.5 A dc; I_C = 5 A dc; V_{CC} = 15 V dc				
Endpoint electrical measurements		See table I, subgroup 2 herein.				
Subgroups 6 and 7						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 3, 4, and 5 (JANS).
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) - for qualification and re-qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling	1051	500 cycles, condition D.	
Hermetic seal	1071		
Fine leak Gross leak			
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 2			45 devices c = 0
Blocking life	1048	1,000 hours minimum, T_A = 150°C, V_{CB} = 80 percent of rated.	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 4			
Thermal impedance curves		See table E-IX of MIL-PRF-19500, group E, subgroup 4.	
Subgroup 6			11 devices
ESD	1020		
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

TABLE III. Groups B, C, and E delta measurements. 1/ 2/ 3/

Step	Inspection 4/	MIL-STD-750		Symbol	Limits	Limits
		Method	Conditions		Min	Max
1.	Collector to base cutoff current	3036	Bias condition D; V_{CB} = 80 V dc	ΔI_{CBO1} 5/		100 percent of initial value or 100 nA dc, whichever is greater.
2.	Forward current transfer ratio	3076	V_{CE} = 2 V dc; I_C = 1 A dc; pulsed (see 4.5.1)	Δh_{FE2} 5/		+20 percent, -10 percent change from initial reading.
3.	Collector to emitter voltage (saturated)	3071	I_C = 1.0 A dc; I_B = 0.1 A dc; pulsed (see 4.5.1)	$\Delta V_{CE(sat)1}$ 5/		50 mV dc change from previously measured value.

1/ The delta measurements for table E-VIA (JANS) of MIL-PRF-19500 are as follows:
   a. Subgroup 4, see table III herein, steps 1, 2, and 3.
   b. Subgroup 5, see table III herein, steps 1, 2, and 3.
2/ The delta measurements for table E-VIB (JANTX and JANTXV) of MIL-PRF-19500 are as follows:
   a. Subgroup 3, see table III herein, step 2.
   b. Subgroup 6, see table III herein, steps 1 and 2.
3/ The delta measurements for table E-VII of MIL-PRF-19500 are as follows: Subgroup 6, see table III herein, steps 1 and 2 (JANS) and step 2 (JAN, JANTX, and JANTXV).
4/ See MIL-PRF-19500 for sampling plan.
5/ Devices which exceed the group A limits for this test shall not be accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.



* FIGURE 3. Temperature-power derating for 2N2880 and 2N3749 (TO-59 and TO-111 packages)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.




FIGURE 4. Thermal impedance graph ($R_{\theta JC}$) for 2N2880 and 2N3749 (similar to TO-59 and TO-111).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.





FIGURE 5. Safe operating area for switching between saturation and cutoff - unclamped inductive load.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.



Procedure:

1. With switch S1 closed, set the specified test conditions.
2. Open S1. Device fails if clamp voltage is not reached.
3. Perform specified end-point tests.

FIGURE 6. Clamped inductive sweep test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.






FIGURE 7. Safe operating areas for switching between saturation and cutoff - clamped inductive load.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.





NOTES:
1. The input waveform is supplied by a pulse generator with the following characteristics: $t_r \leq 15$ ns, $t_f \leq 15$ ns, $Z_{OUT} = 50\ \Omega$, PW = 2 μs, duty cycle ≤ 2 percent.
2. Output waveforms are monitored on an oscilloscope with the following characteristics: $t_r \leq 15$ ns, $R_{in} \geq 10\ m\Omega$, $C_{in} \leq 11.5$ pF.
3. Resistors shall be non-inductive types.
4. The dc power supplies may require additional by-passing in order to minimize ringing.

FIGURE 8. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.




FIGURE 9. Maximum safe operating area graph (dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).


c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QPDSIS-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at http://quicksearch.dla.mil/.

6.4 PIN construction example.

6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.

6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level	PINs for devices of the "S" quality level
JAN2N2880	JANTX2N2880	JANTXV2N2880	JANS2N2880
JAN2N3749	JANTX2N3749	JANTXV2N3749	JANS2N3749

6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil or by facsimile (614) 693-6939 or DSN 850-6939.

* 6.7 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
* Navy - SH
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Army - AR, MI, SM
* Air Force - 19
Navy - AS, MC, OS, SH

Preparing activity:
DLA - CC

(Project 5961-2022-043)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:17Z
Check the source to verify that this is the current version before use.