MILITARY SPECIFICATION
SEMICONDUCTOR DEVICE
TRANSISTOR, PNP, GERMANIUM

TYPE 2N2834

This amendment forms a part of Military Specification MIL-S-19500/310(NAVY), dated 11 February 1965, and is approved by the Naval Electronic Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

* Inactive for new design after the date of this amendment.

PAGE 1

* FSC number: Delete "FSC 5960" and substitute "FSC 5961".

PAGE 2

3.4, Delete and substitute:

"3.4 Marking. Marking shall be in accordance with MIL-S-19500, except that the country of origin may be omitted."

* 4.1, Delete and substitute:

"4.1 Qualification inspection. Qualification inspection shall not be required."

* 4.4, Delete and substitute:

"4.4 Group A inspection. Group A inspection shall consist of the examinations and tests specified in table I on a 100 percent basis."

4.6, Delete and substitute:

"4.6 Group C inspection. Group C inspection shall consist of the tests shown in table III. Devices shall be subjected to the tests initially and at least once every 6 months. In lieu of the operating life test in group B, subgroup 6, the operating life test in group C, subgroup 1 shall be performed."

PAGE 3

* 6.1: Delete in its entirety.

PAGES 4 AND 5

* TABLE I, LTPD column: Delete in their entirety.

PAGE 7

TABLE II, subgroup 6, Steady state operation life test, Specific conditions column: Add "(See 4.6)".

PAGE 8

TABLE III, subgroup 1, Steady state operation life test, Specific conditions column: Add "(See 4.6)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:15Z
Check the source to verify that this is the current version before use.

TABLE III, subgroup 2: Delete and substitute:

Examination or test	Conditions		LTPD	Symbol	Limits		Unit
	MIL-STD-750 method	Specific conditions			Min	Max	
Subgroup 2			15				
Barometric pressure, reduced	1001	15 mmHg					
Measurement during test:							
Collector to base cutoff current	3036 Condition D	V_{CB} = -160 V dc		I_{CBO}	---	-10	mA dc
Thermal resistance	3151			O_{J-C}	---	1.0	°C/W

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Navy - EC

Review activity:
Navy - SH

User activities:
Navy - CG, MC

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5961-N857-7)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:15Z
Check the source to verify that this is the current version before use.