MIL-C-63989A(AR
AMENDMENT 1
4 MARCH 1985

MILITARY SPECIFICATION

CARTRIDGE, 5.56MM, BALL, M855

This amendment forms a part of Military Specification MIL-C-63989A(AR) dated 5 October 1984, and is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 11

4.5.6.1: Delete in its entirety and substitute include in page 11.

PAGE 13

Add 4.5.6.3A as included page 13A.

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection

MIL-C-63989A(AR)
AMENDMENT 1

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
6.1	Jacket				9349657/9392529
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	9349678/9392530
					PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None Defined				
MAJOR:	(Individual AQL's)				
1.	Diameter		1.50%	3.2	SMTE
2.	Base thickness		1.50%	3.2	SMTE
3.	Base thickness variation		1.50%	3.2	SMTE
4.	Wall thickness at chamfer		1.50%	3.2	SMTE
5.	Improper weight		1.50%	3.2	Balance
MINOR:					
1.	Evidence of poor workmanship		2.5%	3.18	Visual

DA (D) [illegible] 160, 1 Aug 83 replaces edition of 1 Jul 77 which [illegible]

Source: http://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63989A(AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.5.6.3A	Bullet, Ball, 5.56MM (Alternative)				9392531
					NEXT HIGHER ASSEMBLY
					9342868
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None Defined				
MAJOR:	(Individual AQL's)				
101.	Diameter of bourrelet		1.50%	3.2	SMTE
102.	Concentricity of boat-tail to bourrelet diameter		1.50%	3.2	SMTE
103.	Length of boat-tail		1.50%	3.2	SMTE
104.	Angle of boat-tail		1.50%	3.2	SMTE
105.	Length of bullet		1.50%	3.2	SMTE
106.	Distance from bullet tip to cannelure		1.50%	3.2	SMTE
107.	Concentricity of bullet tip to bourrelet diameter		1.50%	3.2	SMTE
108.	OMITTED"				
109.	Diameter of knurl		1.50%	3.2	SMTE
110.	Ogive radius		1.50%	3.2	SMTE
111.	Bullet tip, width		1.50%	3.2	SMTE
112.	Improper weight		1.50%	3.2	Balance
113.	Improper contact of slug to surface "X"		1.50%	3.2	Visual
114.	Damaged cannelure		1.50%	3.2	Visual
115.	Lead above bullet base		1.50%	3.2	Visual
MINOR:					
201.	Evidence of poor workmanship		2.50%	3.18	Visual

Notes:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:08Z
Check the source to verify that this is the current version before use.