INCH-POUND

MIL-M-63320A(AR)
AMENDMENT 4
25 APRIL 1990
SUPERSEDING
AMENDMENT 3
27 March 1989

MILITARY SPECIFICATION

Microcircuit, DIGITAL, CMOS (INITIAL LOGIC)

This amendment forms a part of Military Specification MIL-M-63320A(AR) dated 8 April 1981, and is approved for use within the US Army Armament Munitions and chemical Command and is available for use by all the Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1 Drawings, delete “9292962” and substitute “12927055 and 9292962”,

PAGE 3

3.4 line 1: Delete “Environmental tests” and substitute “Mechanical tests”.

"C" Mechanical shock, Conditions: Delete ‘D” and substitute

Delete "Method 2015.1” and substitute "Method 2015".

(This change reinstates original provision of specification.)

3.5.4., (a) and (b): Delete (-45°C to +85°C) and substitute (-40°C to +70°C).

PAGE 6

* 3,6,2, delete ‘9292962X.. ., as applicable and substitute "12927055X or 9292962X where “X” denotes the drawing revision letter, as applicable”.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:38Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.1 Submission: Delete last sentence and substitute “The first article sample, after screening, shall consist of the quantities needed for double samplings stipulated in Table III."

PAGE 8

4.3.4: Add "e. A lapse in production for a period exceeding 90 days or as stipulated in the contract” .

PAGE 9

TABLE 111, Drawing number, delete “9292962” and substitute “12927055 and 9292962”.

Table III, Subgroups a, b, c, d: Delete “25” and substitute "8/"

Subgroup b, Mechanical shock: Delete condition “D” and substitute condition “C".

Subgroup C, Delete ‘Method 2015.1" and substitute “Method 2015”.

(This change reinstates original provision of specification.)

TABLE III, Subgroup g: Delete ’25” and substitute ‘9/".

NOTES : Delete present content of note 1 and substitute ‘Devices which fail to any test criteria in the screening sequence shall be removed from the first article sample. The contractor should choose a first article sample that will provide, after screening, the quantities stipulated in notes 8 and 9“.

PAGE 11

TABLE III: Add the following notes:

‘8/ A double sampling plan shall be used as follows: 25-0-2, 38-1-2. For group b replace fallouts from subgroup a.

9/ A double sampling plan shall be used as follows: 45-0-2, 77-1-2. ”

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

PAGE 13

* 4.4.2.1, Drawing number, delete "9292962" and substitute “12927055 and 9292962”.

PAGE 14

4.4.2.2, Drawing number, delete “9292962” and substitute “12927055 and 9292962”.

4.4.2.2, AQL or 100% Column: Delete “All LTPD’s" and substitute “LTPD’s of 10%, 10%, 10% and 10%”.

PAGE 15

4.4.2.3, Subgroup 2: Delete “Method 2015.1” and substitute “Method 2015”.

(This change reinstates original provision of specification..)

Delete ‘Bona strengtn (bond pulls 1/), ---, LTPD 15%”. Substitute ‘Bond strength (bond pulls 1 /), 5, 1-2”.

Delete Notes “1/” in its entirety and substitute: 1/ Pull all bond wires on each device - reject for two (2) or more bond failures.”

* 4.4.2.3, Drawing number, delete “9292962” and substitute "12927055 and 9292962”.

PAGE 16

* 4.4.2.4, Drawing number, delete “9292962” and substitute "12927055 and 9292962".

4.4.2.4, Subgroup 2, Mechanical shock: Change Condition "D" to Condition "C"

PAGE 20

4.5.17, Burn-in screen, line 6: Delete "7.5 volts dc" and substitute "8.0 volts dc."

4.5.18, Steady state life, line 3: Delete:

"Test duration shall be 100 hours minimum at 1250C + 50C"

And substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

"Test duration shall be 1000 hours minimum at 125°C ± 50C or equivalent per Method 1005 of MIL-STD-883B. Temperature in excess of 1350C + 8°C and Test duration less than 496 hours shall not be allowed.".

PAGE 21

6.3 and 6.5: Delete "QAA" and substitute "QAT".

PAGE 23


FIGURE 1: Delete present and substitute revised FIGURE 1 included to this amendment.

PAGE 38

FIGURE 15: Delete present and substitute revised FIGURE 15 includes to this amendment.

FIGURE 15: Delete "7.5 ±0,1 V dc, ± 7.5 ±0,1 V (Square Wave) and substitute '±8.0 ±-0.5 V dc, ± 8.0 ±0.5 V (Square Wave)" .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.



	NOMINAL	TOLERANCE	STYLE	TYPE	TCC
C1	0.01 uf	± 1.0%	Ceramic	NPO	± 25 ppm
R1	2.0 M ohms	± 5.0%	Composition		
R2	470 K ohms	± 1.0%	Metal Film		± 50 ppm

FIGURE 1. Test Circuit for Leakage Current (Oscillator) and Oscillator Function tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.




FIGURE 15. Burn-in and Steady State Life-Test Circuit.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:38Z
Check the source to verify that this is the current version before use.

MIL-M-63320A(AR)
AMENDMENT 4

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project: 1345-A577)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.