MILITARY SPECIFICATION

PROJECTILE, 175MM: HE, M437
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-P-60622B (AR) dated 14 September 1977.

PAGE 9

Paragraph 4.4.1: Delete in its entirety and substitute:

"4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition heat treatment lots shall contain body forgings from not more than one heat of steel that has been heat treated in the same heat treatment equipment, at the same temperature, in one unchanged process. The heat treatment lot thus constituted shall be the basis for selecting the samples for the tension test."

PAGE 26

Paragraph 4.5.7.2 Delete in its entirety and substitute:

"4.5.7.2 Service pressure. The metal parts assemblies supplied in accordance with Tables II and III will be inert loaded and dummy fuzed and fired using Charge III, unless otherwise specified. The projectile assemblies will be fired alternately with projectile assemblies from a reference lot for comparison. The projectile shall be fired in a gun for which the round is standard, the tube of which shall have a minimum remaining service life of 50 percent based on current gun tube condemnation criteria. Photographic equipment will be set up near the gun muzzle to record the flight of the projectile. Range, velocity and chamber pressure for each round fired will be recorded."

Custodian:
Army - AR

Preparing activity:
Army - AR

Project No.: 1320-A506

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:50Z
Check the source to verify that this is the current version before use.