MIL-T-55335(EL)
Amendment 2
26 November 1974
SUPERSEDING
Amendment 1
30 March 1972

MILITARY SPECIFICATION

TEST FACILITIES KIT, MK-1191( )/AR
(UNITS OF)

This amendment forms a part of Military Specification MIL-T-55335(EL), 30 August 1971 and is approved for use by all departments and agencies of the Department of Defense.

Page 1

2.1 under SPECIFICATIONS, MILITARY, delete: "MIL-T-5422 Testing, Environmental, Aircraft Electronic Equipment".

Page 6

3.12.1.1: Delete "+100°F" and substitute "+131°F".

Page 7

3.12.2: Delete "procedure prescribed in MIL-T-5422" and substitute "Procedure I, Method 507 of MIL-STD-810".

3.12.6, delete and substitute:

"3.12.6 Vibration (See 4.8.6). - The test set shall meet the vibration requirements of Test Method 514.1-7 (Curve AY) of MIL-STD-810."

3.12.7, delete and substitute:

"3.12.7 Shock (See 4.8.7). - The equipment shall not suffer damage or fail to operate after subjection to basic design and bench-handling shock tests conducted in accordance with Method 516.1 of MIL-STD-810. Transit Drop Test shall not be performed."

Delete: "Table I" and "Note A" entirely.

Page 19

4.5.3: Delete "Subgroup II" of "Table IV" and substitute:

"SUBGROUP II

Spray Tight Protection	3.12.4	4.8.4
Shock Tests	3.12.7	4.8.7"

FSC-6625

Source: https://assist.dla.mil -- Downloaded: 202640-22T23:03Z
Check the source to verify that this is the current version before use.

Page 21

4.8.2: Delete "Specification MIL-T-5422" and substitute "Procedure I, Method 507 of MIL-STD-810".

Page 22

4.8.6: Delete "514-1" and substitute "514.1".

4.8.7, Delete and substitute:

"4.8.7 Shock. - The test set shall be subjected to shock tests in accordance with Procedures I and V, Method 516.1 of MIL-STD-810. At the conclusion of the shock tests, without adjustment or repair, the test set shall be inspected and tested for compliance with the electrical tests and inspections specified in 4.8."

4.8.7.1, Delete and substitute:

"4.8.7.1 Shock, basic design (See 3.12.7). - The test set shall be subjected to shock test in accordance with Procedure I of Method 516.1, MIL-STD-810. Figure 516.1-2 shall apply using shock parameters (a) & (c)."

4.8.7.2, Delete and substitute:

"4.8.7.2 Shock, bench-handling. - The test set shall be subjected to bench-handling shock test conducted in accordance with Procedure V, Steps 1 and 2 of Method 516.1, MIL-STD-810."

Page 36

5.2.1 End of last sentence, delete "class B" and substitute "finish A".

Page 37

6.2c Delete in its entirety and substitute "When rough handling test is required".

CUSTODIAN:
ARMY-EL

Preparing Activity:
ARMY-EL
Project No. 6625-A648

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:03Z
Check the source to verify that this is the current version before use.