MIL-A-5034B
2 November 1979
SUPERSEDING
MIL-A-5034A
29 December 1950

MILITARY SPECIFICATION

ADAPTER, BOMB RACK, 30-INCH, AERO 1A

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for the manufacture and inspection of a bomb rack adapter. The adapter gives a 355.6 millimeter (14 inch) suspension bomb rack a 762 millimeter (30 inch) suspension capability allowing the bomb rack to carry and release stores weighing from 45 to 1,814 kilograms (100 to 4,000 pounds). The test limits in this specification define minimum acceptable capabilites.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-7743	-Testing, Store Suspension and Release Equipment; General Specification for
MIL-H-85042	-Hooks, Bomb Rack, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Engineering Specifications and Standards Department (Code 93) Naval Air Engineering Center, Lakehurst, N.J, 08733 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1095

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-100	-Engineering Drawing Practices
MIL-STD-129	-Marking for Shipment and Storage
MIL-STD-130	-Identification Marking of U.S. Military Property
MIL-STD-143	-Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-794	-Parts and Equipment, Procedures for Packaging and Packing of
MIL-STD-831	-Test Reports, Preparation of

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Order of precedence of specifications and standards. Should a conflict exist between any requirement in this specification and any requirement in the applicable documents referenced herein, the requirements of this specification shall take precedence over the referenced (applicable} document.

3. REQUIREMENTS

3.1 First article. The adapters furnished under this specification shall be a product which has been inspected and passed the first article inspection herein (see 4.3).

3.2 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Interchangeability. All parts having the same part number shall be directly and completely interchangeable with each other with respect to installation and performance.

3.4 Identification of parts. All parts shall be marked as specified on the drawings listed in the data list for the adapter being procured, or in accordance with MIL-STD-130, if not specified on the drawings. The item identification and part number requirements of MIL-STD-100 shall govern the part number and changes thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

3.5 Adapter.

3.5.1 Construction. The construction of the adapter shall be in accordance with the drawings listed in the data list for the adapter being procured and as specified herein (see 6.2.lf).

3.5.2 Performance. The adapters shall satisfy all performance requirements when subjected to the following inspections in the order specifiec in Tables I and II.

a. Adapter Inspection (see 4.6.1)

b. Lag Time (see 4.6.2a)

c. Vibration (see 4.6.2b)

d. High-g Release (see 4.6.2c)

e. Life (see 4.6.2d)

f. Shock (see 4.6.2e)

g. Static (see 4.6.2f)

h. Salt Spray (see 4.6.2g)

3.6 Adapter hooks. The construction and inspection of the adapter hooks shall be in accordance with MIL-H-85042.

3.7 Workmanship. The workmanship displayed in fabrication and assembly of the adapter shall be such as to assure, within design limitations, the ability of the adapter to meet performance requirements under all applicable environmental conditions specified herein. Unauthorized repair, welding, heavy burrs, or parts assembled by introduction of high stresses not prescribed in the drawings, are typical signs of inferior workmanship and shall be cause for rejection. The standards of workmanship exhibited in the approved first article sample, subject to any qualification stated in the government's notice of approval, shall be determinative of the requirements of the contract relative to workmanship.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the government. The government

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

reserves the right to perform any of the inspections set forth in the specification, where such inspections are deemed necessary to assure that the supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection of the adapters shall be classified as follows:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4)

4.3 First article inspection. First article inspection shall consist of all of the inspections listed in Table I. First article inspection report format shall be in accordance with MIL-STD-831 (see 6.3).

4.3.1 Sampling for first article inspection. First article adapter samples shall consist of the first three adapters manufactured on contract. The adapters shall be permanently labeled A, B and C for ease of identification. Failure of the adapters to pass any of the first article inspections shall be cause for rejection (see 6.3).

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the following inspections:

a. Individual Inspections (see 4.4.1)

b. Sampling Inspections (see 4.4.2)

Quality conformance inspection report format shall be in accordance with MIL-STD-831 (see 6.3).

4.4.1 Individual inspections. Individual inspections are those inspections conducted on each adapter. Individual inspections for the adapters are shown in Table II, Group 1. Failure to pass any of these inspections shall be cause for rejection of the adapter.

4.4.2 Sampling inspections. A random sampling of the adapters shall be selected by the procuring activity from each production lot in accordance with Table III and shall be subjected to the inspections listed in Table II, Group 1 and Group 2. Group 1 inspections shall be conducted prior to Group 2 inspections. Failure to pass any of these inspections shall be cause for rejection of the entire lot (see 6.3).

4.5 Inspection conditions. Unless otherwise specified, all inspections shall be performed under the following conditions:

a. Room temperature. Room ambient of 25±10°C (77±18°F) indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

b. Test temperature. All parts of the test item shall be stabilized at the specified temperature ±2.8°C (±5°F) indicated prior to conducting any tests. Unless otherwise specified, temperature stabilization will have been attained when the indicated temperature of the surface of the largest mass of the test item does not change by more than ±2.8°C (±5°F) in a period of 1 hour.

c. Test fixture. The adapter shall be tested utilizing an Aero 65 series bomb rack (or equivalent bomb rack such as BRU-14/A or BRU-15/A) as the parent rack and other suitable fixtures that symmetrically apply a swaybrace load of no more than 8896 Newtons (2,000 pounds) 2224 Newtons (500 pounds) per swaybrace pad) in the vertically downward direction. The adapters shall be mounted to the parent rack with bolts and lock nuts. After installation onto the parent bomb rack, the link assemblies of the adapters shall be free to move under their own weight in the vertically downward direction. The adapters shall be swaybraced prior to any tests specified herein that require the release of a store.

d. Test stores. The stores, as referenced herein by weight, shall conform to the following parameters.

1. The 45 kilogram (100 pound) store shall utilize the suspension lugs designated for 1,361 to 2,268 kilogram (3,000 to 5,000 pound) weight class and shall be spaced 762 millimeters (30 inches) apart. The center of gravity of the store shall be midway between the suspension lugs and 203 millimeters (8 inches) below the hook bearing surface of the suspension lugs.

2. The 453 kilogram (1,000 pound) store shall utilize applicable suspension lugs, spaced 762 millimeters (30 inches) apart. Its center of gravity shall be based on the MK 83 L.D.G.P. bomb.

3. The 1,622 kilogram (3,575 pound) store shall utilize applicable suspension lugs spaced 762 millimeters (30 inches) apart. Its center of gravity shall be midway between the suspension lugs and 203 millimeters (8 inches) below the hook bearing surface of each suspension lug.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

4.6 Inspection.

4.61 Adapter inspection. Each adapter shall be inspected to ensure that it has been properly assembled and adjusted, and that the workmanship is as specified herein (see 3.7).

4.6.1.1 Qualification by analysis, inspection, and demonstration. All requirements for the adapter not qualified by testing shall be qualifiec by analysis, inspection or demonstrations approved by the procuring activity.

4.6.1.2 Packaging inspection. Each adapter shall be examined to ensure that the preparation for delivery conforms to this specification (see section 5).

4.6.2 Additional tests. The adapter shall pass the following tests of MIL-T-7743 as specified, except as modified herein.

a. Lag Time (see 4.6.2.1)

b. Vibration Test (see 4.6.2.2)

c. High-g Release (see 4.6.2.3)

d. Life Test (see 4.6.2.4)

e. Shock Test (see 4.6.2.5)

f. Static Test (see 4.6.2.6)

g. Salt Spray (see 4.6.2.7)

4.6.2.1 Lag time. Rated voltage shall be applied to the parent bomb rack and the time interval between voltage application and the last contact of the bomb lugs from the adapter hooks shall be measured. The lag time for the adapters shall not exceed 0.100 second. The lag time of the adapters shall be determined by first measuring the lag time of the parent bomb rack using a 453 kilogram (1,000 pound) store and subtracting this average value from the combined lag time of the adapters and parent bomb rack when used together. The lag time of the adapters shall be determined under the conditions listed in Table IV.

4.6.2.2 Vibration. The adapters and parent bomb rack shall be subjected to the following vibration tests. The procedures of MIL-T-7743 shall be applicable.

a. Resonance vibration, search unloaded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

b. Destructive vibration - unlatched and loaded tests.

1. A 453 kilogram (1,000 pound) store shall be utilized during the loaded portion of this test.

4.6.2.3 High-g release. Perform 25 electrical releases by applying rated voltage (28 VDC) to the parent bomb rack. The adapter hooks shall sustain a total vertically downward load of 10,676 Newtons (2,400 pounds) (including store weight) during all releases. all releases shall be conducted with the bomb rack and adapter in a horizontal attitude. The adapters shall release satisfactorily each time and without deformation to any component of the adapter.

4.6.2.4 Life. Perform 500 releases by applying rated voltage (28 VDC) to the parent bomb rack, using a store weight of 1,622 kilograms (3,575 pounds). Lag time shall be measured on the 1st to 10th and the 491st to 500th releases. The lag time, as defined in 4.6.2.1 shall not exceed 0.100 second.

4.6.2.5 Shock. The adapters and parent bomb rack shall be subjected to the following shock tests. The procedures of MIL-T-7743 shall be applicable.

4.6.2.5.1 No load. The adapters and parent bomb rack shall be tested once in each direction.

4.6.2.5.2 Yield load. A 1,622 kilogram (3,575 pound) store shall be mounted on the adapters and the test of 4.6.2.5.1 shall be repeated for each condition shown in Table V.

4.6.2.6 Static load. The adapters and parent bomb rack, utilizing a rigid simulated store of negligible weight (91 kilograms, 200 pounds maximum) shall be subjected to the loads specified in Table VI. The loads shall be applied about the center of gravity of the store. The center of gravity shall be midway between the suspension lugs and 203 millimeters (8 inches) below the hook bearing surface of the suspension lugs. upon completion of the tests shown in Table VI, the adapters are to be tested to the ultimate load of 300,255 Newtons (67,500 pounds), applied vertically downward.

4.6.2.7 Salt spray. The adapters shall be placed in a salt spray chamber with the link assemblies in the free position. Upon completion of the exposure period, the adapters shall be installed on a parent bomb rack and a 45 kilogram (100 pound) store shall be latched into the adapter. The adapters shall then be allowed to dry for a minimum of 48 hours. The store shall be electrically released by applying rated voltage to the parent bomb rack. The lag time, as defined in 4.6.2.1, shall not exceed 0.100 second.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

4.7 Qualification cross reference. Table VII identifies each requirement in Section 3 and correlates the Section 4 paragraphs that qualify it.

5. PACKAGING

5.1 Adapter preservation and packaging. Preservation and packaging shall be in accordance with Level A, B or C as specified in MIL-STD-794, as specified in the contract, without the use of preservation compound,

5.2 Packing. Shipping containers shall contain one each package adapter. The container shall be suitable for Level A, B or C as specified in MIL-STD-794.

5.3 Unitized loading. Unitized loading for the adapters is authorized as specified in MIL-STD-794.

5.4 Marking. All shipping containers shall be marked in accordance with the requirements of MIL-STD-129 with the following information:

ADAPTER, BOMB RACK, 30-INCH, AERO 1A
MILITARY SPECIFICATION NO. MIL-A-5034
PRESERVED (DATE)
DOMESTIC OR EXPORT PACKED (AS APPLICABLE)
GOVERNMENT ORDER NO. (OR CONTRACT NO. IF ORDER NO. IS NOT ASSIGNED)
NAME OF SUPPLIER (AND NAME OF MANUFACTURER IF NOT THE SAME)
MANUFACTURER'S CODE IDENTIFICATION NUMBER

6. NOTES

6.1 Intended use. The adapters covered by this specification are intended for use in level bombing, dive bombing, and other types of bombing and shall provide for mounting externally as on an airplane wing or fuselage.

6.2 Ordering data. Procurement documents shall specify the following.

6.2.1 Procurement requirements.

a. Title, number and date of this specification.

b. Selection of applicable levels of preservation, packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

c. Samples subjected to sampling inspection shall not be considered or accepted as part of the contract (see 4.4.2).

d. Sampling inspection selection (see 4.4.2).

e. Number of samples and inspection sequence for production lots in excess of 300 units (see Table III).

f. Applicable drawing package (see 3.5.1).

g. Name and location of government representative responsible for random selection of inspection samples (see 4.4.2).

h. Items of data required (see 6.3).

i. Name and location of government approved test laboratory.

6.2.2 Contract provision. Contracts shall specify the following provision for first article inspection.

6.2.2.1 First article. When a first article is required for inspection and approval (see 3.1, 4.3, 6.2 and 6.3), the contract shall specify the following provision for first article inspection. When a contractor is in continuous production of adapters from contract to contract, consideration should be given to waive the first article inspections. If inspection is required, indicate:

a. If first article inspections are conducted at the contractor's plant or a government approved laboratory, an inspection report shall be forwarded to the procuring activity for verification.

b. That the approval of first article samples or the waiving of the first article inspection shall not relieve the contractor of his obligation to fulfill all other requirements of the specification and contract.

6.3 Contract data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of 7-104.9(n) of the Armed Services Procurement Regulations, the data requirements identified below will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of ASPR-7-104.9(n) are not invoked, the data specified below will be delivered by the

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

contractor in accordance with the contract requirements. Deliverable data required by this specification is cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
4.3	First Article Inspection Report	DI-T-5329 - Inspection Test Reports
4.4	Quality Conformance Inspection Reports	DI-T-5329 - Inspection Test Reports

(Copies of data item descriptions required by the contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

6.4 Quality assurance definitions. Definitions for quality assurance terms are in accordance with MIL-L-STD-109.

Review Activities:
NAVY - AS
ARMY-AV
AIR FORCE - 18

Preparing Activity:
NAVY - AS
DOD Proj. No. 1095-0115

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

TABLE 1. First article inspections - schedule and sequency 1/

Tests	Test paragraph	Sample		
		A	B	C
Adapter inspection	4.6.1	1	1	1
Lag time	4.6.2a	X	2	X
Vibration	4.6.2b	2	X	X
High-g release	4.6.2c	3	3	X
Life	4.6.2d	X	4	2
Shock	4.6.2e	X	X	3
Static	4.6.2f	4	X	X
Salt spray	4.6.2g	X	X	4

1/ Inspection sequence is denoted by the numbers in the sample columns. An X denotes inspection not required.

TABLE II. Quality conformance inspections - schedule and sequence - 1/

Tests	Test paragraph	Sample			
Group 1		All Samples			
Adapter inspection	4.6.1	1			
Group 2		A	B	C	D
Lag time	4.6.2a	X	1	1	X
Shock	4.6.2e	1	X	X	1
Vibration	4.6.2b	2	X	X	2
High-g release	4.6.2c	X	2	2	X
Life	4.6.2d	X	3	3	X
Static	4.6.2f	3	X	X	X
Salt spray	4.6.2g	4	X	X	3

1/ Inspection sequence is denoted by the numbers in the sample columns. An X denotes inspection not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

TABLE III. Sampling test items

Item	Production lot size	Number of samples
Adapters	100 or less 101 - 200 201 - 300 301 or More	2 3 4 1/

1/ The procuring activity shall specify the number of samples, and the sequence of inspections each unit shall be subjected to for lots in excess of 300 units (see 6.21e).

TABLE IV. Lag determination.

Attitude (from horizontal)	Store weight	Number of releases
Horizontal	45 kilograms (100 pounds)	2
Horizontal	1,622 kilograms (3,575 pounds)	2
Dive and climb 15°, 30°, 45°	45 kilograms (100 pounds)	2 at each attitude
Dive and climb 15°, 30°, 45°	1,622 kilograms (3,575 pounds)	2 at each attitude

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

TABLE V. Applied yield loads.

Direction	Applied load(g's)
Vertical up	3.3
Vertical down	6.1
Transverse port	2.2
Transverse starboard	2.2
Longitudinal forward	7.7
Longitudinal aft	7.7

TABLE VI. Applied static loads.

Direction	Load
Vertical down	222,411 Newtons (50,000 pounds)
Vertical up	124,550 Newtons (28,000 pounds)
Longitudinal (forward and aft)	97,861 Newtons (22,000 pounds)
Transverse (port and starboard)	13,345 Newtons (3,000 pounds)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

TABLE VII. Qualification cross reference.

Paragraph title	Requirement paragraph	Test paragraph
First article	3.1	4.3
Selection of spec's & std's	3.2	4.6.1.1
Interchangeability	3.3	4.6.1.1
Identification of parts	3.4	4.6.1.1
Construction	3.5.1	4.6.1.1
Adapter inspection	3.5.2a	4.6.1
Lag time	3.5.2b	4.6.2a
Vibration	3.5.2c	4.6.2b
High-g release	3.5.2d	4.6.2c
Life test	3.5.2e	4.6.2d
Shock	3.5.2f	4.6.2e
Static	3.5.2g	4.6.2f
Salt spray	3.5.2h	4.6.2g
Adapter hooks	3.6	4.6.1.1
Workmanship	3.7	4.6.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-A-5034B ADAPTER, BOMB RACK, 30-INCH, AERO 1A

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Lakehurst, NJ 08733

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DOD 316



Engineering Specifications and Standards Department (Code 93)
Naval Air Engineering Center
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.

NOTICE OF VALIDATION

MIL-A-5034B
NOTICE 1
2 March 1987

MILITARY SPECIFICATION

ADAPTER, BOMB RACK, 30 INCH, AERO 1A

MIL-A-5034B, dated 2 November 1979, has been reviewed and determined to be still current.

Custodians:
Army - AV
Navy - AS
Air Force - 18

Preparing activity:
Navy - AS

AMSC N/A

FSC 1095

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2022-10-17T04:08Z
Check the source to verify that this is the current version before use.

INCH-POUND

MIL-A-51487A(EA)
11 May 1990
SUPERSEDING
MIL-A-51487(EA)
1.4 April 1987

MILITARY SPECIFICATION

ARMING/FIRING UNIT

This specijica[ion is approved for use by the U.S. Army Chemical Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Departmen t of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of arming/firing unit (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-PET-S, Aberdeen Proving Ground, MD 21010-5423 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1040

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:08Z
Check the source to verify that this is the current version before use.