NOT MEASUREMENT SENSITIVE

MIL-L-11484/67D
14 January 1994
SUPERSEDING
MIL-L-11484/67C
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, LENGTH OF SERVICE (10, 20, 30, and 40 YEARS), MARINE CORPS CIVILIAN

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

PIERCED

DASH NO.
-1: 10 Years
-2: 20 Years
-3: 30 Years
-4: 40 Years

MATERIAL: Red Brass

FINISH: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
HEIGHT (Overall): 21/32 inch (1.67 cm) (REF)
WIDTH (Overall): 5/8 inch (1.59 cm) (REF)
THICKNESS (At Thickest Point): 0.150 inch ± 0.005 inch (0.381 ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T16:27Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The numbers indicating years of service are included in the government furnished hubs or dies.

3. The design of Dash No. -1, -2, -3 and -4 are identical except for the number of the year shown. Dash No. -3 is shown as illustrative only.

4. Pierced areas shall be as indicated.

5. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button 1/8 inch (0.32 cm) above the horizontal center line.

Custodians:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0743)

Source: https://assist.dla.mil -- Downloaded: 202640-17T16:27Z
Check the source to verify that this is the currentversion before use.