NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/71E
27 September 1996
SUPERSEDING
MIL-L-11484/71D
14 January 1994

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, JOINT CHIEFS OF STAFF IDENTIFICATION BADGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL:
BASE (Wreath): Red brass
DEVICE: Gilding metal

FINISH:
BASE: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.
DEVICE: Hard Enameled, Gold Plated, Rose Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 19.

DIMENSIONS:
HEIGHT (Overall):
BASE: 9/16 inch (1.43 cm) (REF)
DEVICE: 15/32 inch (1.19 cm) (REF)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:28Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
BASE: 1/2 inch (1.43 cm) (REF)
DEVICE: 15/32 inch (1.19 cm) (REF)
THICKNESS (At thickest point):
BASE: 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)
DEVICE: 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)
ASSEMBLED: 0.100 inch ± 0.010 inch (0.254 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The base has a platform to support the device. This platform will require the base to be pierced in four areas - above, below and to the sides of the platform. Pierced areas are indicated on the Government furnished hub.

3. Enameled areas shall be as indicated. The colors shall conform to the TIOH color chip numbers listed below or the standard sample.

COLOR	CHIP NO.
Red	1
Blue	18
White	28

4. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

5. The device shall be soft soldered to the base in the location shown.

6. Lapel button shall be lacquered.

7. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

8. The full size identification badge shall conform to MIL-B-41809/2.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0858)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:28Z
Check the source to verify that this is the current version before use.