MILITARY SPECIFICATION

ENTRANCE, PROTECTIVE, PRESSURIZED, MISSILE VAN,

COLLAPSIBIE, M7

1. SCOPE

1.1 This specification covers one type of pressurized protective entrance.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of intitation for bids or request for proposal, form a part of this specification to the extent specified herein-

SPECIFICATIONS

FEDERAL

UU-P-271	-	Paper, Wrapping, Waterproofed Kraft
MMM-A-260	-	Adhesive, Water-Resistant (For Sealing Waterproofed Paper)
PPP-c-650	-	Crates, Wood, Open and Covered.
PPP-T-60	-	Tape; Pressure-Sensitive Adhesive, Waterproof for Packaging.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-117	-	Bags and Sleeves, Interior Packaging.
MIL-T-704	-	Treatment and Painting of Material.

STANDARDS

FEDERAL

Fed. Test Method Std. No. 601 - Rubber Sampling and Testing (Test Methods).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

DL5-19-3046 - Entrance, Protective, Pressurized, Missile Van, Collapsible, M7
D150-2-1 - Marking Diagram for Shipping Containers.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.? Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of incitation for bids *or* request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules, and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-19-3046 or on subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the item shall conform to the specifications and drawings listed on Drawing DL5-19-3046 and subsidiary drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

3.2 Manufacture and assembly. The protective entrance shall be assembled as specified on Drawing D5-19-3046.

3.2.1 Sewed seams. All sewed seams shall be straight and regular lines. AU ends shall be back stitched at least 2 inches. No loose threads shall dangle.

3.2.2 Lap joined cemented seams, All lap joined cemented seams of the protective entrance shall be capable of withstanding a pull of 5 pounds per inch when tested as specified in 4.3.2.2.

3.3 Preproduction. Prior to the start of regular production, a preproduction sample of protective entrance and lap joined cemeted seams shall be produced in accordance with this specification for examination and test (see 4.3).

3.4 Workmanship. The protective entrance shall be free from foreign matter (dirt, grease, oil, or viscous material) and damage (punctures, tears, dents, scratches, or abrasions) and any *sharp* edges or burrs.

4. QULAITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Suppliers responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order: the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government The Government reserves the right to perform *any* of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of one protective entrance and five lap joined seams (6 inches by 6 inches with seam going through the center) shall be made using the same methods, materials, and equipment as will be used in regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination and nondestructive tests. Each preproduction sample shall be examined for all the requirements of the applicable drawings and this specification.

4.3.2.2 For destructive test. Each of the five lap joined cemented seams in the preproduction sample shall be tested as specified in method 8311 of Federal Test Method Standard No. 601.

4.3.3 Acceptance/rejection criteria. Each lap joined seam and the protective entrance in the preproduction sample shall comply with the requirements of this specification when examined and tested as specified in 4.3.2 to be acceptable.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the protective entrances produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions. However, no more than one lot of cement from one manufacturer and one lot of cloth shall be represented in any one lot of finished entrances.

4.4.2 Sampling. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure.

4.4.3.1 For examination and nondestructive tests. Sample entrances and the level A preparation for delivery shall be examined in accordance with the classification of defects and MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

4.4.3.2 Classification of defects.

(a) Entrance protective, pressurized, missle van, collapisible, M7 (Dwg D5-19-3046).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing
102	Component incorrectly assembled
103	Stitching and back stitching not as specified (3.2.1)
104	Lap joined cemented seams not Joined securely
105	Location of button or socket incorrect
106	Workmanship (3.4)
107	Failure of fasteners to close properly

(b) Reparation for delivery section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Damaged portions of painted areas not treated or repainted as specified
102	Metal container hinges not oiled as specified
103	Internal bracing and blocking missing or insufficient to make a tight package
104	Corners of container not cushioned as specified
105	Metal container not closed as specified
106	Waterproof wrap missing or not closed and sealed as specified
107	Crate incorrect
108	Crate closure incorrect
109	Metal container incorrectly packed within crate
110	Metal container, crate, or waterproof wrap damage (punctured, torn, broken, or wracked)
111	Strapping incorrect, loose, or missing
112	Marking incorrect, missing, or illegible

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

5. PREPARATION ON FOR DELIVERY

5,1 Preservation and packaging. levels shall be as specified (see 6.2).

5.1.1 Level A. All packages shall be of the- minimum cube required to contain the items.

5.1.1.1 Repairing. Metal surfaces on which paint is damaged or chipped shall be treated and repainted in conformance with type A of MIL-T-704.

5.1.1.2 Cap screws and washers. These items shall be packaged in a heat sealable interior packaging bag conforming to type III, class B of MIL-B-117.

5.1.1.3 Technical publications. One copy of technical publications shall be packaged in accordance with method IC-3 of MIL-P-116.

5.1.1.4 Protective entrance. The protective entrance shall be folded and placed inside of the container (Drawing E5-19-1791, which is listed on Drawing DL5-19-1791) provided. Internal bracing and blocking shall be added as required to prevent movement of the item. The hinges on the protective entrance container door shall be oiled with type P-9 preservative oil, conforming to MIL-P-116. Excessive preservative oil shall be wiped off. Items packaged as specified in 5.1.1.2 and 5.1.1,3 shall be secured to the inside of the container door with pressure sensitive tap conforming to class 1 of PPP-T-60. The items so secured shall not interfere with the door. The container doors shall then be closed and secured by the catch provided. The corners of the container shall be cushioned, as required, to prevent rupturing the waterproofing barrier material wrap. The container shall then be enclosed within a waterproof wrap fabricated from case liner or crate liner waterproofed kraft wrapping paper conforming to W-P-271. All folds, laps, and seams of the waterproof wrap shall be sealed with waterproof adhesive conforming to MMM-A-260.

5.1.2 Level C. The protective entrance shall be folded and placed inside the container (Drawing E5-19-1791) provided and the necessary internal cushioning and blocking added to prevent movement of the item. Items packaged as specified in 5.1.1.2 and 5.1.1.3 shall be secured to the door of the-container in the manner specified in 5.1.1.4. The container shall then be closed and secured by the catch provided.

5.2 Packing. Levels shall be as specified (see 6,2).

5.2.1 Level A. The protective entrance, preserved and packaged as specified in 5.1.1 shall be packed in a type II, style A, open wood crate,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

conforming to PPP-C-650. The metal protective entrance container shall be placed on its side when packed in the above cited crate. Anchoring of crate contents, crate closure, and strapping shall be in accordance with the appendix of the crate specification. All strapping shall be galvanized.

5.2.2 Level B. The protective entrance, preserved and packaged as Specified in 5.5.1, shall be packed as specified in 5.2.1, except that all strapping used in the closure shall be coated-finish.

5.2.3 Level C. The protective entrance, preserved and packaged as specified in 5.1.2, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall be in compliance with Uniform Freight Classification rules Or the regulations of other common carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and intermediate packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with Drawing D150-2-1.

5.4 Repair part. When this item is procured for storage and issue as a repair part, preservation, packaging, packing and marking shall be as specified on the repair part packaging data sheet which is identified by the Federal stock number for the repair part.

6. NOTES

6.1 Intended use. This protective entrance is intended for use as a component of the Collective Protection Equipment, CBR, Battery Control Central, Hawk, M10.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packaging and packing required.
(c) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:53Z
Check the source to verify that this is the current version before use.

6.3 Supersession data. This specification supersedes Chemical Corps Purchase Description No. 197-54-788A, dated 12 April 1962.

Custodian:

Army- MU

Preparing activity:

Army - MU(EA)

Project No. 4240 -A219

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968 -341-510/A-541

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.