MILITARY SPECIFICATION

CORN, YELLOW, DEHYDRATED, COMPRESSED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers uncooked, yellow, dehydrated, compressed corn for use by the Department of Defense as an item of general issue.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-29	-	Canned Subsistence Items, Packaging and Packing of
PPP-C-96	-	Cans, Metal, 28 Gage and Lighter

MILITARY

MIL-L-1497	-	Labeling of Metal Cans for Subsistence Items
MIL-L-35078	-	Loads, Unit; Preparation of Nonperishable Subsistence Items; General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8915

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Regulations Governing Inspection and Certification of Processed Fruits and Vegetables, Processed Products Thereof, and Certain Other Processed Food Products

United States Standards for Grades of Frozen Whole Kernel (or Whole Grain) Corn

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

United States Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

Source: https://assist.dla.mil -- Downloaded: 20260-22T00:01Z
Check the source to verify that this is the current version before use.

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN DRY MILK INSTITUTE, INC.

Standards for Grades of Dry Milks, Including Methods of Analysis: Bulletin 916

(Application for copies should be addressed to the American Dry Milk Institute, Inc., 130 North Franklin Street, Chicago, IL 60606.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 No. 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Suite 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.4, 6.1 and 6.4).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome and shall be as specified herein or in referenced documents.

3.2.1 Corn. The yellow sweet corn shall have a tender pericarp. Varieties such as Style Pack, Jubilee, Dividend, Mellogold or equivalent shall be used. The corn shall be harvested at a stage of maturity when milky fluid spurts from the kernel when it is punctured by a thumbnail. Frozen corn conforming to U.S. Grade A (Fancy) of the U.S. Standards for Grades of Frozen Whole Kernel (or Whole Grain) Corn of the latest harvest which meets the above requirements may be used provided sulfiting is accomplished subsequent to complete thawing.

3.2.2 Sodium sulfite or sodium acid sulfite. The sulfite(s) used shall meet the requirements of the Food Chemicals Codex (F.C.C.).

3.2.3 Water. Water used for formulation and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.3 Preparation and processing.

3.3.1 Corn kernel cutting. The corn shall be cut from the cob with a minimum of tearing and crushing of the kernels. The kernels shall be cut to exclude the base tip of the kernel.

3.3.2 Blanching. Fresh corn shall be blanched in live steam or hot water until peroxidase has been inactivated when tested as specified in 4.5.2.2.

3.3.3 Sulfiting. The fresh and frozen (after thawing) corn shall receive a sulfite treatment by such methods as will insure a reasonably uniform distribution throughout the product and a residual sulfur dioxide content in the dehydrated product within the limitation specified in 3.4.1. The sulfite used shall conform to the Food Chemicals Codex. Contact of the wet corn with iron, subsequent to the sulfiting operation, shall be strictly avoided.

3.3.4 Freezing. The blanched and sulfited corn shall be quick frozen as expeditiously as possible after sulfiting and held in the frozen state until dehydrated.

3.3.5 Dehydration. The frozen product shall be freeze-dehydrated at absolute pressure not exceeding 1.0 millimeter of mercury. At no time shall there be evidence of thawing in the product. After dehydration has been completed, the pressure in the freeze-drying chamber shall be equalized to

Source: https://assist.dla.mil -- Downloaded: 20260-22T00:01Z
Check the source to verify that this is the current version before use.

atmospheric pressure with nitrogen and the product shall be preserved immediately as specified in 5.1, or shall be held under an atmosphere of nitrogen (not more than 2.0 percent oxygen) not more than 16 hours until packaging can be effected.

3.3.5.1 Particle size. The dehydrated corn particle shall be of such size that not more than 1.0 percent passes through a U.S. No. 8 sieve when tested as specified in 4.5.2.3.

3.3.6 Conditioning. The dehydrated corn kernels shall be conditioned by adding water sufficient to make them pliable so that they will not be crushed or ground under high pressure. (Note: Satisfactory compressed corn has been produced by spraying with moisture to increase the dry weight by 12 to 16 percent and placing the sprayed corn in a closed cnntainer and then heating approximately 10 minutes at 150°F in order to equilibrate the moisture in the corn.)

3.3.7 Mechanical pressing. The moistened corn shall be placed in a 3-3/4 ± 1/8 inch diameter mold and compressed into discs by applying 1000 to 1500 pounds per square inch pressure for a dwell time of approximately 10 to 30 seconds, depending upon the variety and maturity of the corn.

3.3.8 Redrying. The compressed corn shall be redried within a minimum of time so that the finished product complies with 3.4.

3.4 Finished product requirements.

3.4.1 Compressed product. The compressed dehydrated product shall be free from hay-like, scorched, rancid, musty, or other objectionable odors; shall not exceed 3.0 percent by weight of moisture; and shall contain a sulfite level, calculated as sulfur dioxide, of 500 ± 250 ppm.

3.4.2 Rehydrated product. The rehydrated product shall meet the requirements for U.S. Grade A (Fancy) of the U.S. Standards for Grades of Frozen Whole Kernel (or Whole Grain) Corn.

3.4.3 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.5 Plant qualification. The product shall be prepared, processed, and packaged under sanitary conditions in accordance with good manufacturing practice. The product shall be processed in establishments meeting the sanitary requirements of the applicable Government inspection agency.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this document. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient examination. Conformance of ingredients to identity and condition requirements shall be determined by examination of pertinent labels, markings, US Grade certificates, invoices, certificates of analysis, or other valid documents. In addition, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient lot or of any involved product.

4.5.1.2 Can tin coating weight testing. The cans shall be tested in accordance with PPP-C-96 for conformance to the tin coating weight requirement in 5.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

4.5.2 In-process inspection.

4.5.2.1 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or other valid documents shall be cause for rejection of the involved product.

4.5.2.2 In-process testing for peroxidase. As each production run is initiated, a sample of the blanched corn, prior to dehydration, shall be tested in accordance with 4.6.3. A test indicating active peroxidase enzymes shall be cause for rejection of that portion of the production from the time of previous negative result until such time as a negative test result is again attained.

4.5.2.3 In-process testing for particle size. Each batch of dehydrated corn prior to compressing shall be tested for particle size. A representative 100-gram sample of corn shall be selected from the batch and placed on a U.S. No. 8 sieve with attached collecting pan and cover. The sample shall be sieved with a Rotap or equivalent shaking device for 3 minutes. If the weight of the sieved particles in the collecting pan exceeds 1.0 percent of the weight of the original sample, the batch shall be rejected.

4.5.3 Net weight examination. The cans of product shall be examined for net weight. Any individual sample having a net weight of less than 15.0 ounces shall be scored as a minor defect. The lot size shall be expressed in units of cans. The sample unit shall be one can of product. The inspection level shall be S-2 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. In addition, the lot shall be rejected if the sample average net weight is less than 16.0 ounces.

4.5.4 Product examination. The finished product shall be examined for the defects listed in table I. The lot size shall be expressed in cans. The sample unit shall be 10 avoirdupois ounces of rehydrated product, representative of one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

TABLE I. Product defects 1/ 2/

Category	Defect
Major	Dehydrated product
151	Presence of hay-like, scorched, rancid, oxidized, musty or other objectionable odors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

TABLE I. Product defects 1/ 2/ (cont'd)

Category	Defect
Major	
	Rehydrated product 3/
152	Product does not conform to the classifications of Grade A (Fancy) of the U.S. Standards for Grades of Frozen Whole Kernel (or Whole Grain) Corn

1/ The presence of any foreign material (e.g. glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale, etc.) or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an AMS agent).

3/ Two or more intact discs of compressed corn randomly selected shall be rehydrated on the basis of 4 fluid ounces of boiling water to each avoirdupois ounce of compressed corn. While bringing the water back to a boil, separate the discs by stirring, remove from heat, cover allow to stand for 5 minutes and drain.

4.5.5 Moisture and sulfur dioxide content testing. The finished product shal be tested as specified in 4.6.1 and 4.6.2 for conformance to the moisture and sulfur dioxide requirements in 3.4.1. The sample for testing shall be a 1-pound composite, derived from the number of cans indicated by inspection level S-2. The lot size shall be expressed in cans. Results for moisture shall be reported to the nearest 0.1 percent, and for sulfur dioxide to the nearest 10 ppm. A test failure for either moisture or sulfur dioxide content shall be cause for rejection of the lot.

4.5.6 Leakage examination. Examination for leakage shall be in accordance with the examination criteria of PPP-C-29 (see 5.1.1).

4.5.7 Can condition examination. Examination of filled and sealed cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

4.5.8 Oxygen in headspace testing. The filled and sealed cans shall be tested as specified in 4.6.4 for conformance to the oxygen in headspace requirement in 5.1.1. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.5.9 Shipping container examination. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in construction, closure and reinforcement shall be in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified aa follows:

Major:	National stock number, item description, contract number or date of pack markings missing, incorrect or illegible. Arrangement or number of cans not as specified.
Minor:	Other required markings, missing, incorrect, or illegible. Reinforcement with nonmetallic strapping or tape is not used. Tiered cans not separated as specified.

Level C shipping cnntainers shall be examined for the marking, arrangement, and number of can defects specified above and for the closure method specified in 5.2.3.

4.5.10 Unit load inspection. Inspection of unit loads shall be in accordance with quality aasurance provisions of MIL-L-35078.

4.6 Methods of inspection.

4.6.1 Moisture content test. Prepare a clean, dry Waring blender or similar mill by grinding a sample and discarding it. Grind approximately 100 grams of a well mixed sample in the prepared blender. Sieve the ground material through a U.S. Standard No. 20 sieve and collect that portion which passes through in a clean, dry, tightly closed container. Weigh two samples, approximately 2.0 grams each of the sieved material, into tared, dry, aluminum weighing dishes (approximately 2 or 2-1/2 inches in diameter and 3/4 inch in depth) with tight-fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 6 hours at 70°C under a pressure of not more than 100 mm mercury. During drying, admit to the oven a slow current of air (approximately two bubbles per second) dried by passing through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the percent of moisture in the original samples.

4.6.2 Sulfur dioxide content test. Sulfur dioxide of the ground sample shall be determined in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, chapter: Food Additives: Direct section: Chemical Preservatives, method: Total Sulfurous Acid, Modified Monier-Williams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

4.6.3 Peroxidase activity. The test to show adequate blanching shall be made in accordance with the following methods:

a. Reagents (use Food Chemicals Codex)

Distilled water
0.5 percent guaiacol in 50.0 percent ethyl alcohol solution
0.08 percent hydrogen peroxide (2.8 mL of 30.0 percent hydrogen peroxide per liter). Keep in refrigerator in dark bottle and renew solution each week.
Clean sand.

b. Apparatus:

Test tubes, 3/4 or 7/8 inch in diameter
3 or 4-inch diameter funnels
6 or 7-inch cotton milk filters
Waring blender or similar mixer or porcelain mortar (4 to 6 inch diameter) and pestle
50.0 mL graduated cylinder
1.0 and 2.0 mL pipettes
Timer or watch with second hand
Test tube rack
Balance which will weigh 10.0 gram samples to $\pm$ 0.1 gram (A triple beam type balance is recommended)
If blender is used, a larger sample will permit use of less sensitive balance

c. Procedure, using blender:

1. Weigh out representative 100 to 200-gram sample.
2. Place in blender with 3.0 mL water to each gram of vegetable.
3. Grind for 1 minute at moderate or high apeed.
4. Filter through cotton milk filter.
5. Add 2.0 mL of filtrate to 20.0 mL of distilled water in test tube.
6. Prepare a blank by adding 2.0 mL of filtrate to 22.0 mL of distilled water in a second test tube, mix and use as a color comparison tube. (Do not add any guaiacol or peroxide to this tube.)
7. Add 1.0 mL of 0.5 percent guaiacol solution to first test tube without mixing.
8. Add 1.0 mL of 0.08 percent hydrogen peroxide to the same tube without mixing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

c. Procedure, using blender; (cont'd)

9. Mix cnntents thoroughly by inverting and watch for development of any color differing from the blank, regardless of hue, but of sufficient intensity to show an obvious contrast. Development of color is a positive test and indicates inadequate blanching. If no color contrast develops in 3-1/2 minutes, consider the test negative and the product adequately blanched. If color develops after 3-1/2 minutes, it is to be disregarded and the test still considered negative (for further information see full report, Masure, M.P. and Campbell, H., "Rapid Estimation of Peroxidase in Vegetable Extracts - An Index of Blanching Adequacy for Frozen Vegetables." Fruit Prod. Jour. and American Food Mfr. 23:369-375,383, Aug. 1944.)

d. Procedure, using mnrtar:

1. Weigh representative 10.0-gram sample.
2. Place 30.0 mL distilled water in graduated cylinder.
3. Place sample in mortar with a little clean sand, add minimum amnunt of water from graduated cylinder to give best consistency for thorough maceration, and grind for 3 minutes. Add remainder of water from cylinder and mix.
4. Proceed as under c. above, 4 through 9 inclusive.

NOTE: Because of the limits of mortar grinding when using mortar with 10.0 gram samples, special attention should be given to assuring representative samples. Sample size can be increased to 20.0 or 30.0 grams with additional time given to grinding, or the number of units represented can be increased by halving or quartering, if the sample is uniform.

4.6.4 Oxygen content test. Oxygen content of headspace gas shall be determined in accordance with the Determination of Oxygen method in Bulletin 916 of the American Dry Milk Institute, Inc. The result of each determination shall be reported to the nearest 0.1 percent.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.1).

5.1.1 Level A. A net weight of 16.0 ounces of compressed product shall be unit packed in a size 401 by 411 can. A minus tolerance of 1.0 ounce will be permitted in any individual can provided that the average net weight of cans examined in accordance with 4.5.3 is not less than 16.0 ounces. The can shall be an open top style, round, metal can with soldered or welded side seam and

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:01Z
Check the source to verify that this is the currenversion before use.

compound-lined, double-seamed ends. The can shall be made throughout from not less than commercial 0.25-pound per base box electrolytic tin plate (see 4.5.1.2). The cans shall have a sufficient base plate weight and temper to protect the product during shipment and storage. The can shall be coated overall on the outside with a coating conforming to type I or when specified type III of TT-C-495. The can shall be hermetically sealed under an atmosphere of nitrogen, so the oxygen content of the gases in the filled and sealed can shall not exceed 2.0 percent, when tested in accordance with 4.5.8. The can shall not leak when tested in accordance with 4.5.6.

5.1.2 Level C. The compressed discs of the product shall be preserved in accordance with 5.1.1 except that cans with or without commercial exterior coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tin plate with an exterior commercial coating.

5.2 Packing. Twenty-four cans of product arranged 4 in length, 3 in width, and 2 in depth, shall be packed on end in a snug-fitting shipping container in accordance with level A, B or C, as specified (see 6.1).

5.2.1 Level A packing. The shipping container shall be a fiberboard box, constructed, closed in accordance with style RSC, V2s of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636.

5.2.2 Level B packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V3c, V3s, or V4s of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive filament reinforced type in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing. The shipping container shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable, except fiberboard containers shall be closed in accordance with Method II as specified in the appendix of PPP-B-636. The tiered cans shall be separated with a full length and width pad.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and claas of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling and marking.

5.4.1 Cans. Cans shall be labeled in accordance with MIL-L-1497. Labeling shall include the following information:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

CORN, YELLOW, DEHYDRATED, COMPRESSED
Net Weight
Name and Address of Supplier
Date Packaged
Preserved with Sulfur Dioxide
Gas packed (if applicable)

DIRECTIONS FOR USE

Yellow corn, dehydrated, compressed	16 oz.(1 No 2-1/2 can)
Water, boiling	2 quarts
Butter or margarine, melted	3 oz.
Salt	1-1/2 teaspoon
Pepper	1/4 teaspoon

Add corn to boiling salted water. Stir to separate. Bring to boil; remove from heat, Cover and let stand 5 minutes. Drain and reserve 1/2 cup liquid. Combine liquid, butter and pepper. Pour over corn.

Yield: 16 (1/2) cup servings.

5.4.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. When a first article is required (see 3.1, 4.4 and 6.4).
c. Provisions for approved preproduction samples (see 3.4.3 and 6.4).
d. Levels of preservation and packing required (see 5.1 and 5.2).
e. Type and class of unit load when unit loading is specified (see 5.3).
f. When type III exterior coating of cans is desired (see 5.1.1).

6.2 Appropriate level of pack. Based on conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

6.3 Level C packing. Packing specified in 5.2.3 is intended for direct shipment from the supply source to the first consuming activity within CONUS for immediate consumption.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.5 Supersession data. This document supersedes LP/P DES 14-74 - Corn, Yellow, Dehydrated, Compressed, 28 June 1974.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8915-0772

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 20261O-22T00:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-44118	Corn, Yellow, Dehydrated, Compressed

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 APR 83

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:01Z
Check the source to verify that this is the current version before use.