MIL-P-44120A
10 March 1988
SUPERSEDING
MIL-P-44120
22 March 1984

MILITARY SPECIFICATION

PIE FILLING, MIX, APPLE, DEHYDRATED, COMPRESSED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers compressed, dehydrated, apple pie filling mix.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specifications For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR PARTS 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Grades of Dehydrated (Low-Moisture) Apples

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service (AMS), U.S. Department of Agriculture, P.O Box 96456, Washington, DC 20090-6456.)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, P.O. Box 96456, Washington, DC 20090-6456.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists Inc., 3340 Pilot Knob Road, St. Paul, MN 55121.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCE

Food Chemicals Codex

(Application for copies should be addressed to the Office of Director, National Academy Press, National Research Council, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

NATIONAL MOTOR FREIGHT ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Suite 1120, 222 South Riverside Plaza, Chicago, IL 60606.)

AMERICAN OIL CHEMISTS SOCIETY

Official and Tentative Methods of the American Oil Chemists Society

(Application for copies should be addressed to the American Oil Chemists Society, 508 South Sixth Street, Champaign, IL 61820.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Bid sample approval. Unless otherwise specified, (see 6.1), six hermetically sealed 401 x 411 cans, each containing not less than 1 pound, 8 ounces of the dehydrated pie filling mix representative of the product which the bidder proposes to furnish under contract, shall be submitted to the contracting officer prior to the bid opening date. The apple slices in each can shall weigh not less than 9.5 ounces. One or more of the samples will be used to determine whether the product has the desired color, flavor, odor, and texture quality characteristics specified 3.4. The remaining samples submitted by the bidder shall be used as standards for compliance with the procured item. Approval of the bid sample does not relieve the bidder from complying with all other requirements of this document.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent and insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Apple slices. The dehydrated apple slices used shall meet the requirements of the U.S. Standards for Grades of Dehydrated (Low-Moisture) Apples, Grade A pie pieces, except that the sulfur dioxide content shall be not less than 200 parts per million (ppm) nor greater than 1,000 ppm.

3.2.2 Sugar. Sugar shall be white refined, sucrose, granulated cane or beet, or a combination thereof.

3.2.3 Starch modified. The starch shall be white, free flowing, odorless, and finely pulverized. The starch shall be a modified waxy maize starch requiring cooking to gelatinize. The starch shall demonstrate initial viscosity development in the temperature range of 140° to 170°F. The starch shall resist breakdown at low pH, under shear stress, and under conditions of cold storage. Fruit fillings and sauce prepared with this thickener shall have good clarity and a smooth stable texture and body.

3.2.4 Salt. Salt shall be white refined sodium chloride with or without anti-caking agent. Iodized salt shall not be used.

3.2.5 Citric acid. Citric acid shall meet the requirements of the Food Chemicals Codex.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

3.2.6 Cinnamon, ground. Ground cinnamon shall be prepared from the dried bark of Cinnamomum burmanii Blume, commonly known as "Korintze Cinnamon". The cinnamon shall contain not less than 1.5 mL of volatile oil per 100 grams of ground cinnamon and shall be of such size that not less than 95 percent shall pass through a U.S. Standard No. 60 sieve.

3.2.7 Nutmeg, ground. Ground nutmeg shall be derived from dried kernel of Myristica fragrans Houtt. The nutmeg shall have a dull brown color. The ground nutmeg shall contain not less than 7.5 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 20 sieve.

* 3.2.8 Oil, vegetable, high stability. The hydrogenated vegetable oil shall be properly processed cottonseed, peanut or soybean oil, or any combination thereof. The oil shall be free from rancid, sour, or other objectionable flavors or odors after testing and shall have a stability of not less than 60 hours as determined by the Active Oxygen Method (AOM) in Method Cd 12-57 of the Official and Tentative Methods of the American Oil Chemists Society, when the oil is cottonseed or peanut oil or any combination thereof. When the oil is derived from soybeans singly or in combination with the other domestic oils specified, it shall have at least 100 hours AOM stability. FDA approved levels of antioxidants may be used to achieve this stability requirement.

3.2.9 Lecithin. Lecithin, if used (see 3.3.3) shall meet the requirements of the Food Chemicals Codex.

3.3 Preparation and processing.

3.3.1 Formula. The product shall be prepared according to the following formula:

Ingredients	Percent of ingredients	Weight per can
Apple slices, dehydrated		9.5 ounces
Dry mixture (blend):		14.5 ounces
Sugar	89.4	
Starch (modified)	7.0	
Salt	1.2 1/	
Citric acid	0.3	
Nutmeg, ground	0.4	
Cinnamon, ground	0.7	
Oil, vegetable, high stability	1.0	

1/ Proportions of starch and sugar may be varied to give a satisfactory finished pie consistency.

3.3.2 Blending. The ingredients with the exception of the apple shall be thoroughly blended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

3.3.3 Apple slice compression. The dehydrated apple slices shall be conditioned by applying sufficient dry heat to make them pliable and to preclude their being broken, crushed, or ground under high pressure. Application of the dry heat shall not overheat the apple slices or cause an undesirable change in their color. Conditioning of the dehydrated apple slices can be effected by heating at 225°F for 5 minutes or until they are pliable and then immediately spraying them with a very light coating of lecithin. Three to 4 ounces of the conditioned apple slices shall be placed into a 3-3/4 ± 1/8 inch diameter mold and compressed into a disc. (A satisfactory disc has been prepared by applying 1,000 pounds per square inch pressure for 10 to 20 seconds.)

3.4 Finished product.

3.4.1 Dehdyrated product. The finished product shall not exceed 3.0 percent moisture, by weight, when tested in accordance with 4.4.2.

3.4.2 Prepared product. The finished product when prepared according to direction (see 5.4.1) shall not boil out excessively and when cooled to room temperature (70° to 75°F) shall be of a syrupy, semi-solid consistency which when cut will not spread more than 1/2 inch from the cut edge. The filling shall be translucent without ungelatinized starch pockets and uncooked or raw ingredients. The filling shall have a characteristic spicy cooked apple flavor without undesirable off-flavor or off-odor. The apples shall retain their slice characteristic and be fully rehydrated and tender and not rubbery, mushy, or sauce-like in texture.

* 3.5 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods", and the plant sanitation requirements of the appropriate Government inspection agency.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

* 4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1, the components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or other applicable purchase document.

* 4.3.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.3.1.2 Unfilled can inspection. Conformance of unfilled cans to the requirements specified in 5.1.1 shall be determined by examination of certificates of conformance or of other valid documents. Any nonconformance shall be cause for rejection of the can lot or of any involved product.

4.3.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or other valid documents shall be cause for rejection of the involved product.

4.3.3 Weight examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in cans. The sample unit shall be one filled can. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for minor defects.

TABLE I. Weight defects 1/

Category		Defect
Major	Minor	
201		Net weight less than 23.0 ounces. 2/

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

TABLE I. Weight defects 1/ (cont'd)

Category		Defect
Major	Minor	
101		Weight of apples less than 9.0 ounces. 3/

1/ After determining net weight, use a 12-inch U.S. Standard No. 12 sieve to separate the apples from the other ingredients so that the weight of the apples alone may be determined. The can contents shall be separated by sieving portions at a time.

2/ The lot shall be rejected if the sample average net weight is less than 24 ounces.

3/ The lot shall be rejected if the sample average weight of the apples per can is less than 9.5 ounces.

4.3.4 Prepared filling examination. The prepared filling, after baking, shall be examined for the defects listed in table II. The lot size shall be expressed in cans. The sample unit shall be one filled can. The pie filling shall be prepared in accordance with 5.4.1 using a proportionate quantity of ingredients to prepare one 9-inch pie from each sample unit. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 4.0 for minor defects.

TABLE II. Prepared filling defects 1/ 2/

Category		Defect
Major	Minor	
151		Filling spreads more than 1/2 inch from cut edge when a segment of pie is removed.
152		Ungelatinized starch pockets, uncooked or raw ingredients
* 153		Exhibits excessive boil out
154		Not a syrupy, semi-solid consistency 3/
	201	Not translucent
155		Not a spicy, cooked apple flavor 3/

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

TABLE II. Prepared filling defects 1/ 2/ (cont'd)

Category		Defect
Major	Minor	
156		Appearance and texture of applesauce 3/
157		Apple pieces not fully rehydrated or not tender
158		Apple pieces texture rubbery or mushy

1/ Examinations shall be made in a temperature range of 70° to 75°F.

2/ Presence of foreign material (e.g. glass, dirt, insect parts, hair, wood, metal), undesirable off-flavor or odor, or foreign color shall be cause for rejection of the lot.

* 4.4 Product testing.

* 4.4.1 Leakage testing. The cans of pie filling shall be tested for leakage as specified in 4.5.1. The lot size shall be expressed in cans. The sample unit shall be one can. The inspection level shall be S-3. Any test failure is a major defect and shall be cause for rejection of the lot.

* 4.4.2 Moisture content testing. The finished product shall be tested for moisture content as specified in 4.5.2. The lot size shall be expressed in cans. The sample for testing shall be a 1-pound composite (6-1/3 ounces of dehydrated apples plus 9-2/3 ounces of dry mixture blend) extracted from the number of cans indicated by inspection level S-2. If the test result does not conform to the requirement in 3.4.1, it is a major defect and the lot shall be rejected.

4.4.3 Can condition examination. Examination of filled and sealed cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497.

4.4.4 Shipping container examination. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in construction, closure, and reinforcement shall be in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible
Reinforced with other than nonmetallic strapping or tape

Minor: Other required markings missing, incorrect, or illegible
Interior packing with tier separator pads not as specified
Arrangement or number of cans not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

Level C shipping containers shall be examined for the closure method specified in 5.2.3 and for the defects specified above, except for the reinforcement defect.

4.4.5 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

4.5 Methods of inspection.

4.5.1 Leakage test. The seams of the filled and sealed cans shall be examined as follows: Submerge can in water contained in a vacuum desiccator, Mead tester, or equivalent device, and draw a vacuum of 10 inches for 30 seconds and observe for leakage. A leak consists of a steady progression of bubbles and shall be considered a test failure. Isolated bubbles that can be caused by the release of air entrapped in the double seam are not considered as signs of leaks. Any leak shall be considered a test failure.

4.5.2 Moisture test. Under low humidity conditions, a relative humidity of 20 percent or less, extract and grind a proportionate amount of the dehydrated compressed apples and the dry mix. Two 3- to 4-gram samples shall be weighed in aluminum weighing dishes (approximately 2 to 2-1/2 inches in diameter and 3/4 inch in depth) with tight fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 6 hours at 70°C under a pressure of not more than 100 milliliters of mercury. During drying, the oven shall be purged by a slow current of air (approximately two bubbles per second) which has been dried by passage through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the loss as percent moisture and report to the nearest 0.1 percent.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.1).

5.1.1 Level A. A net weight of 24 ounces (not less than 9.5 ounces of apples shall be filled into a 401 x 411, open top style, round metal can with welded or soldered side seam and compound-lined, double-seamed ends. A net weight tolerance of minus 1 ounce (0.5 ounce for apple component) is permitted, provided the average net weight of cans in any lot is not less than 24.0 ounces and the average net weight for the apple component is not less than 9.5 ounces. The can shall be made throughout from commercial electrolytic tinplate of not less than 0.25-pound per base box and shall be coated outside with a coating conforming to type I or, when specified (see 6.1), type III of TT-C-495. The can shall have a sufficient base plate weight and temper to protect the product during shipment and storage. The can shall be hermetically sealed and shall not show seam leakage when tested as specified in 4.5.1

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with or without commercial exterior coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tinplate, provided the cans have an exterior commercial coating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Twenty-four cans of product shall be packed on end, four in length, three in width, and two in depth in a snug-fitting fiberboard shipping container conforming to style RSC, grade V25 of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad, made of the same material as the box. Each fiberboard box shall be closed and reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping of unit loads shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Twenty-four cans of product shall be packed on end, four in length, three in width, and two in depth in a snug-fitting fiberboard shipping container conforming to style RSC, grade V3c, V3s, V4s of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad, made of the same material as the box. Each fiberboard box shall be closed and reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing. Twenty-four cans of product shall be packed on end, four in length, three in width, and two in depth in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The container shall be in accordance with National Motor Freight Classification or Uniform Freight Classification, as applicable. The tiered cans shall be separated with a full length and width pad. Fiberboard boxes shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.3 Unit loads. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling and marking.

5.4.1 Cans. Cans shall be labeled in accordance with MIL-L-1497 and in addition, shall contain the following information:

DIRECTION FOR USE

1. Pour 1-3/4 quarts of water into a pan and bring to a boil
2. Stir in contents of this can.
3. Cover, bring back to boil and simmer gently for 10 minutes.
4. Allow product to cool to room temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

5. Measure about 3 cups of filling into each unbaked pie shell. Distribute Apples and liquid equally into the pie shells.
6. Cover with the top crust and seal the edges.
7. Bake in a hot oven at 425°F for 30 to 35 minutes or until lightly browned.

Yield: 2-1/4 quarts of apple pie filling. Makes 3 (9 inch) pies.

5.4.2 Shipping containers. The shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

* 6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When other than six cans are required for bid sample approval (see 3.1).
c. Level of preservation and packing required (see 5.1 and 5.2).
d. When type III exterior coating is required (see 5.1.1).
e. Type and class of unit load required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 Subject term (key word) listing.

Apples
Dessert
Pies

6.4 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, TS
Navy - MC
DP - SS

Preparing activity:

Army - GL

Project No. 8940-0617

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-44120A	Pie Filling, Mix, Apple, Dehydrated, Compressed

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE. NATICK/OP-1 Feb 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.