INCH-POUND

MIL-S-44095A(GL)
19 April 1989
SUPERSEDING
MIL-S-44095(GL)
28 December 1982

MILITARY SPECIFICATION

SURVIVAL KIT, INDIVIDUAL, VEST TYPE

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a survival kit consisting of a vest and a number of survival aids.

1.2 Classification. The vest shall be of the following sizes (see 6.2).

Small
Large

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-K-818 - Knife, Pocket, General Purpose
MIL-W-1053 - Whistle, Ball, Plastic
MIL-B-8571 - Bag, Storage, Drinking Water
MIL-C-10436 - Compass, Magnetic, Unmounted: Lensatic, Luminous, 5 Degree and 20-MIL
MIL-M-18371 - Mirrors, Emergency Signaling, Mark 3
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-T-36045 - Tourniquet, Nonpneumatic, Camouflaged, 1-1/2 by 42 Inches
MIL-S-36609 - Survival Kit, Individual, Tropical, Tactical Air Crew
MIL-B-36964 - Blanket, Combat, Casualty Lightweight, Waterproof, Aluminized Plastic
MIL-L-38217 - Light, Marker, Distress

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

11-1-1783	- Survival Kit, Individual; Vest Assembly
11-1-2898	- Vest, Survival Kit, Individual, Vest Type
11-1-2899	- Left Side Body Pattern Small Size
11-1-2900	- Right Side Body Pattern Small Size
11-1-2901	- Right Side Body Pattern Large Size
11-1-2902	- Left Side Body Pattern Large Size
11-1-2903	- Pocket Patterns
11-1-2904	- Pocket and Lace Loop Patterns
11-1-3173	- Pocket-PRC-90 Radio
11-1-3174	- Survival Kit and General Purpose Pocket

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

3.2 Materials. Materials and components shall conform to the requirements specified herein and in the subsidiary documents applicable thereto. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Color. The color of the materials and components of the vest shall be as specified on the applicable drawing (see 6.4).

3.4 Design. The kit shall consist of a vest with pockets or compartments and the survival aids specified on Drawing 11-1-1783.

3.5 Vest construction. The vest shall be cut in accordance with the patterns specified herein and shall be constructed as specified on Drawing 11-1-2898.

3.5.1 Stitches, seams, and stitchings. Stitches, seams and stitchings used in the construction of the vest shall conform to FED-STD-751.

3.5.2 Patterns. The manufacturer's working patterns shall be identical in size and shape to the appropriate patterns referenced on Drawings 11-1-2899 thru 11-1-2904, 11-1-3173, and 11-1-3174 which provide for seam allowance, size, shape, placement of pockets, directional lines for cutting, and notches for proper assembly of all parts. Unless otherwise specified, the patterns provide an allowance of 3/8 inch for single needle seams.

3.6 Workmanship. The finished vest shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to the requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:52Z
Check the source to verify that this is the current version before use.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted the Government reserves the right to inspect such items to determine the vaidity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.2 Component and material certification. The contractor shall furnish a certificate of compliance as evidence that the fire starter supplied is the same as or equivalent to the fire starter referenced in note 9 of Drawing 11-1-1783 when the fire starter is not government furnished.

4.4.2 In-process inspection. Inspection shall be made of the following operations to establish conformance to specified requirements. Wherever nonconformance is noted, correction shall be made to the items affected, the lot in progress, and to the operation. Parts that do not match and cannot be corrected shall be removed from production.

a. Visual and dimensional examination of the working patterns to determine that they conform to the government patterns in all respects (see 3.5).

b. Visual and dimensional examination of the cut parts to determine that they are properly cut with respect to size and material directional requirements (warp and filling), that location marks and notches on the parts are located correctly, and that parts containing material defects and damages have been removed.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:52Z
Check the source to verify that this is the currentversion before use.

c. Inspection shall be performed for seams and stitching operations and for any other operations or assemblies which cannot be inspected after the end item is completed.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of survival kits. The sample unit shall be one survival kit. The inspection level shall be II and the acceptable quality level (AQL's), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects.

Examine	Defect	Classification Major	Minor
Materials	Mesh net containing any cut, tear, burn or smash	101	
	Mesh net containing any abrasion, broken, or missing yarns resulting in a broken mesh opening	102	
	Mesh net containing any abrasion, broken, or missing yarns but not resulting in a broken mesh opening		201
	Mesh net containing any mend, darn, patch or splice	103	
	Nylon cloth containing any hole except drill holes 1/16 inch or less, cut, tear, smash, multiple floats, missing yarns, or open places	104	
	Exposed drill holes 1/16 inch in diamater or less in nylon cloth		202
	Tape or webbing containing any cut, hole, or tear	105	
	Tape or webbing not firmly or tightly woven or edges of tape or webbing frayed or scalloped		203
	Color of mesh net, tape, webbing, slide fastener tapes, or hook or pile fastener tapes not as specified		204
	Any cut, damage, kink, or knot in nylon cords, seriously affecting service-ability	106	
	End of nylon cords not seared		205
	Nylon cords contain core ends projecting through the core sleeve		206

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects. (cont'd)

Examine	Defect	Classification Major	Minor
Hardware	Hardware not type specified	107	
	Any required component improperly set or reversed, failing to serve intended purpose	108	
	Hardware broken, damaged, or malformed or containing corroded areas, burrs, or sharp edges	109	
	Any snap fastener omitted or not closing or opening freely	110	
	Any snap fastener nor properly clinched, i.e., components of stud or socket separating when snap fasteners are snapped or unsnapped, or clinched excessively, cutting surrounding material	111	
	Any lift-a-dot fastener not positioned as specified	112	
Seams and stitching	Open seam more than 1/2 inch but not more than 1 inch 1/		207
	Open seam more than 1 inch 1/	113	
	Raw edges (except where required) more than 1/4 inch but not more than 1 inch but securely caught in stitching 1/		208
	Raw edges (except where required) more than 1 inch but securely caught in stitching 1/	114	
	Any raw edge including inside of pockets not seared or overedge stitched	115	
	Not specified seam or stitch type	116	
	Loose stitch tension resulting in loosely exposed bobbin or top thread		209
	Tight stitch tension resulting in tightness of puckering of fabric		210
	One stitch per inch less than minimum specified		211
	Two or more stitches per inch less than minimum specified	117	
	One or more stitches in excess of maximum stitches per inch specified		212
	Stitching margins not as specified		213
	Stitching ends backstitched less than 1/2 inch unless held down by other stitching or turned under in a hem		214

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects. (cont'd)

Examine	Defect	Classification Major	Minor
Seams and stitching (cont'd)	Thread breaks overstitched less than 1 inch for stitch type 301 1/		215
	Any required row of straight stitching omitted	118	
	Seam twisted or pleated		216
	Binding loosely or improperly applied, badly pleated, or ends not finished as specified or not securely caught in stitching		217
	Needle chews resulting in damage to fabric	119	
Construction details	Center joining seam or shoulder seams not reinforced by tape	120	
	Any pocket not constructed or positioned on vest as specified	121	
	Any slide fasteners not attached to pocket as specified, i.e., distorted, failing to effect a smooth closure, or direction of pull not as specified on drawings	122	
	Pile portion of fastener tape attached to pocket flap		218
	Hook portion of fastener tape attached to pocket		219
	Fastener tape not specified size		220
	Fastener tape misplaced, not serving intended purpose	123	
	Nylon cords not secured in pocket stitching as specified	124	
	Ends of loop adjustment tapes not properly turned under, resulting in loop end not securely caught in stitching	125	
	Loop tape cord not laced through loop tapes as specified and tied in square knot		221
	Loops not securely anchored to the tapes by stitching along edge of tape, catching tape and loops		222
	Any required component omitted or any required operation omitted or not as specified (unless otherwise classified herein)	126	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects. (cont'd)

Examine	Defect	Classification Major	Minor
Slide fasteners and assemblies	Slide fastener not specified type or size	127	
	Slider of slide fastener jamming or failing to interlock chain scoops	128	
	Thong omitted from slide fastener	129	
	Ends of thongs not seared		223
	Slide fastener tapes improperly stitched to vest fronts, preventing slider from operating freely	130	
	Bottom corners of vest uneven more than 1/4 inch but not more than 1/2 inch when slide fastener is engaged		224
	Bottom corners of vest uneven more than 1/2 inch	131	
Survival aids	Any aid missing from kit	132	
Label	Information on label incomplete, incorrect, or illegible	133	
	Stitching omitted on one or more edges of contractor's label		225
	Label missing	134	
General	Spots or stains not removable, or thread ends not trimmed throughout vest		226

1/ A seam shall be classified as open if one or more stitches joining the seam are broken or if two or more continuous skipped stitches or runoffs occur. Thread breaks that are not overstitched and raw edges that are not securely caught in stitching shall be classified as open seam.

4.4.4 End item fit examination. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of survival kits. The sample unit shall be one survival kit. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:52Z
Check the source to verify that this is the current version before use.

TABLE II. End item fit defects

Examine	Defect
Fit of survival aids into pockets	Pockets too small or large. Survival aids fail to fit properly within the pocket.
	Pocket flaps too small or large. Fail to close properly after survival aid is inserted into pocket.
NOTE:	The survival kit fit examination shall be performed with the survival aids furnished by the contracting activity (see 6.4.2). The survival aids shall be inserted into their designated pockets and the pocket flaps closed to ensure a proper fit.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A.

5.1.1.1 Unit packing.

5.1.1.1.1 Vests. Each vest, with slide fasteners, hook and pile fasteners and snap fasteners closed, shall be neatly folded to measure approximately 12 by 9 inches. Each folded vest shall be unit packed in a close-fitting flat or square style, clear polyethylene film bag of 0.00125 inch thickness (± 25 percent tolerance). The bag may be fabricated from polyethylene film tubing or sheeting. The bag shall be formed with heat sealed seams that are straight and continuous. The final closure of the bag shall be heat sealed with the seal made as close as possible to the open end. A 1/4-inch diameter hole shall be made at one corner of the bag to allow excess air to escape. Alternatively, the final closure of the bag may be affected by means of a tuck or reverse flap.

5.1.1.1.2 Fire starter (magnesium). One magnesium fire starter, complete with instructions, shall be unit packed in a clear polyethylene film bag of 0.003 inch thickness. The bag shall be formed with heat sealed seams that are straight, continuous and parallel with each other to form the edges of the bag.

5.1.1.1.3 Other components. Other components shall be unit packed in accordance with table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

TABLE III. Unit packing of kit contents

Nomenclature	Applicable specification	Preservation	Quantity
Bag, storage, drinking water, size B	MIL-B-8571	Level A	1
Blanket, combat casualty, type III	MIL-B-36964	Level A	1
Compass, lensatic	MIL-C-10436	Level A	1
Knife, pocket	MIL-K-818	Level A	1
Lighter, marker, distress type I, class 1	MIL-L-38217	Level A	1
Mirror, emergency, signaling, mark 3, type I	MIL-M-18371	Level A	1
Survival kit, individual	MIL-S-36609	Level A	1
Tourniquet, non-pneumatic	MIL-T-36045	Level A	1
Whistle, ball, plastic	MIL-W-1053	Level A	1

5.1.1.2 Intermediate packing. One complete survival vest assembly, unit packed as specified, shall be packed in a snug-fitting intermediate fiberboard box conforming to style RSC, grade W6c of PPP-B-636. The components of each assembly shall be neatly and compactly arranged within the box. The instruction sheet shall be placed on top with the printed matter facing up. Voids within the box shall be fitted with cellulosic material to immobilize the contents while the box is in transit. Each fiberboard box shall be closed in accordance with method IV as specified in the appendix of PPP-B-636.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Complete survival kit. Six complete survival kits of one size, preserved as specified in 5.1.1.2, shall be packed in a snug-fitting shipping container conforming to style RSC, grade V2s of PPP-B-636. The shipping containers shall be completely filled with no voids and of a size that can be palletized in accordance with MIL-STD-147. Each fiberboard shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:52Z
Check the source to verify that this is the current version before use.

Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to non-metallic strapping, except for type II, class F loads.

5.2.1.2 Vest, when procured separately (see 6.2). Twenty vests of one size only, preserved as specified in 5.1.1.1.1, shall be packed in a snug-fitting fiber-board shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. The inside dimensions of the shipping container shall approximate 24 inches in length, 18 inches in width, and 12 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed and strapped in accordance with the appendix of the box specification. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the size and type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.1.3 Fire starter (magnesium) when procured separately (see 6.2). Four hundred eight fire starters, preserved as specified in 5.1.1.1.2 shall be packed in a snug-fitting shipping container conforming to RSC, grade V2s, of PPP-B-636. The approximate dimensions of the shipping container shall be 16 inches in length, 8 inches in width, and 7 inches in depth. Each shipping container shall be closed and reinforced in accordance with the container specification. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to non-metallic strapping except for type II, class F loads.

5.2.2 Level B packing.

5.2.2.1 Complete survival kit. Six complete survival kits of one size, preserved as specified in 5.1.1.2, shall be packed in a snug-fitting fiber-board shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The shipping container shall be completely filled with no voids, and of a size that can be palletized in accordance with MIL-STD-147. Each fiberboard shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.2 Vest, when procured separately (see 6.2). Twenty vests of one size only, preserved as specified in 5.1.1.1.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW), of SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. The inside dimensions of the shipping container shall be approximately 24 inches in length, 18 inches in width, and 12 inches in depth. Approximate dimensions are furnished as a guide only. Each fiberboard shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

5.2.2.3 Fire starter (magnesium) when procured separately (see 6.2). Four hundred and eight fire starters, preserved and unit packed as specified in 5.1.1.1.2 shall be packed in a snug-fitting shipping container conforming to RSC, type CF (variety SW), or SF, class domestic, grade 275 of PPP-B-636. The approximate dimensions of the shipping container shall be 16 inches in length, 8 inches in width, and 7 inches in depth. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.4 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.3 Commercial packing. Survival kits or vests or fire starters when procured separately (see 6.2), preserved as specified in 5.1 shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), survival vests or components packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V of MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L, or film bonding means O or P. Pallet pattern for the complete vest assembly shall be in accordance with the appendix of MIL-STD-147. Pallet pattern shall be number 6 for the vest when procured separately, and number 27 for the magnesium firestarter. Interlocking of loads shall be affected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, intermediate packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Polyethylene bagged unit packs. Polyethylene bagged unit packs shall have the required identification information legibly printed or stamped in black directly on the bag across the center face, or on a white label inserted within the bag so as to permit ready identification.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The survival kit is intended for use by Army aviators to aid survival in emergency situations in remote areas.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:52Z
Check the source to verify that this is the current version before use.

packet sleeping bags are intended for use in

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Size of vest required.
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Components to be Government furnished (see 11-1-1783).
f. Levels of preservation and packing (see 5.1 and 5.2).
g. Type and class of unit load required (see 5.2.1).
h. When vest of fire starter only is required (see 5.2.1.2, 5.2.1.3, 5.2.2.2, 5.2.2.3 and 5.2.3)
i. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.4).
j. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Samples.

6.4.1 Color samples. Samples of the color shades may be obtained from the contracting activity or as directed by the contracting officer.

6.4.2 Survival aid samples. For access to samples of the survival aids required for the fit examination in 4.4.4, address the contracting activity issuing the invitation for bids.

6.5 Subject term (key word) listing.

Army aviators
Emergency

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - GL

Review activities:
Army - AV, MD

Preparing activity:
Army - GL

(Project 8465-A969)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-44095A(GL)	Survival Kit, Individual, Vest Type

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:52Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:52Z
Check the source to verify that this is the current version before use.