MIL-B-50653(MU)
AMENDMENT 1
13 September 1974

MILITARY SPECIFICATION

BOARD, COMPONENT: 10548362

This amendment forms a part of Military Specification MIL-B-50653(MU) dated 15 April 1971 and is approved for use by all Departments and Agencies of the Department of Defense.

Table I, Characteristics, Main trigger output, Pulse width: Delete "1.1 ± 0.2 μs" and substitute "1.25 ± 0.35 μs".

Delayed trigger output, Pulse width: Delete "1.4 ± 0.2 μs" and substitute "1.5 ± 0.3 μs".

Delay: Delete "22 ± 2 μs" and substitute "22 ± 4 μs".

Paragraph 4.6.3.2, *Width: Delete "1.1 ± 0.2 μs" and substitute "1.25 ± 0.35 μs".

Paragraph 4.6.3.3, *Width: Delete "1.4 ± 0.2 μs" and substitute "1.5 ± 0.3 μs".

Delete note in its entirety and substitute new note "*For pulse widths of 4.6.3.2 and 4.6.3.3 select resistors R22 and R33 for minimum pulse width at -40°C. For resistor values refer to parts list, P/L 10548362."

Paragraph 4.6.3.4: Delete "24 ± 2 μs" and substitute"22 ± 4 μs".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1285-A393

FSC 1285

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.