MIL-C-50652/14(MU)
AMENDMENT 2
8 May 1974
SUPERSEDING
AMENDMENT 1
25 October 1972

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY: 10548359

(CONVERTER, RANGE D/A, 4A16)

This amendment forms a part of Military Specification MIL-C-50652/14(MU) dated 15 April 1971, and is approved for use by all Department and Agencies of the Department of Defense.

Table I, Characteristic column, add:

"-10.0 ± 0.1 Vdc
-10.0 volt return"

Terminals column, add:

"P1-12
P1-13"

* Table II: Delete in its entirety and substitute new Table II as shown on page 2 of this amendment.

* Table III: Delete in its entirety and substitute new Table III as shown on page 3 of this amendment.

* Table IV: Delete in its entirety and substitute new Table IV as shown on page 4 of this amendment.

Paragraph 4.6.1: Change "MIL-C-59652" to "MIL-C-50652".

*The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1285-A385

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

TABLE II - RANGE VOLTAGES INCREMENTAL LIMITS

STEP	EQUIVALENT RANGE (M)	INPUT LOGIC LEVELS - TERMINALS P1 19	11	18	17	2	4	15	5	6	33	OUTPUT VOLTAGE P1-41 NOT LESS THAN	NOT MORE THAN
1	5000	0	0	0	1	1	1	1	1	1	1	+19.950	+20.050
2	2560	0	0	0	0	1	0	0	0	0	1	+10.140	+10.340
3	1280	0	0	0	0	1	0	0	0	1	0	+ 5.070	+ 5.170
4	640	0	0	0	0	1	0	0	1	0	0	+ 2.520	+ 2.600
5	320	0	0	0	0	1	0	1	0	0	0	+ 1.240	+ 1.320
6	160	0	0	0	0	1	1	0	0	0	0	+ 0.600	+ 0.680
7	80	0	0	0	0	0	1	0	0	0	0	+ 0.280	+ 0.360
8	40	0	0	0	1	1	0	0	0	0	0	+ 0.120	+ 0.200
9	20	0	0	1	0	1	0	0	0	0	0	+ 0.040	+ 0.120
10	10	0	1	0	0	1	0	0	0	0	0	+ 0.020	+ 0.080
11	5	1	0	0	0	1	0	0	0	0	0	+ 0.000	+ 0.060
12	0	0	0	0	0	1	0	0	0	0	0	- 0.030	+ 0.020

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

TABLE III - RANGE VOLTAGES CUMULATIVE LIMITS

STEP	EQUIVALENT RANGE (M)	INPUT LOGIC LEVELS TERMINALS P1- 9	11	18	17	2	4	15	5	6	33	OUTPUT VOLTAGE P1-41 NOT LESS THAN	NOT MORE THAN
1	5035	1	1	1	1	1	1	1	1	1	1	+19.935	+20.340
2	2555	1	1	1	1	0	0	0	0	0	1	+10.118	+10.322
3	1275	1	1	1	1	0	0	0	0	1	0	+ 5.049	+ 5.151
4	635	1	1	1	1	0	0	0	1	0	0	+ 2.500	+ 2.580
5	315	1	1	1	1	0	0	1	0	0	0	+ 1.220	+ 1.300
6	155	1	1	1	1	0	1	0	0	0	0	+ 0.580	+ 0.660
7	75	1	1	1	1	1	0	0	0	0	0	+ 0.260	+ 0.340
8	35	1	1	1	0	1	0	0	0	0	0	+ 0.100	+ 0.180
9	15	1	1	0	0	1	0	0	0	0	0	- 0.020	+ 0.100

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.

TABLE IV - RANGE RATIO LIMITS

STEP	EQUIVALENT RANGE (M)	9	11	18	17	2	4	15	5	6	33	OUTPUT RATIO VOLTAGES ± 1%
1	5000	0	0	0	1	1	1	1	1	1	1	1.0000
2	2560	0	0	0	0	1	0	0	0	0	1	.5120
3	1280	0	0	0	0	1	0	0	0	1	0	.2560
4	640	0	0	0	0	1	0	0	1	0	0	.1280
5	320	0	0	0	0	1	0	1	0	0	0	.0640
6	160	0	0	0	0	1	1	0	0	0	0	.0320
7	80	0	0	0	0	0	1	0	0	0	0	.0160
8	40	0	0	0	1	1	0	0	0	0	0	.0080
9	20	0	0	1	0	1	0	0	0	0	0	.0040
10	10	0	1	0	0	1	0	0	0	0	0	.0020
11	5	1	0	0	0	1	0	0	0	0	0	.0010
12	0	0	0	0	0	1	0	0	0	0	0	.0000

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:32Z
Check the source to verify that this is the current version before use.