MIL-C-50652/5 (AR)
AMENDMENT 2
31 March 1982
SUPERSEDING
AMENDMENT 1
7 February 1975

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY: 10548016
(GENERATOR, RCFD)

This amendment forms part of Military Specification MIL-C-50652/5 (MU), dated 15 April 1971, and is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

TABLE I, INPUT AND OUTPUT CHARACTERISTICS, under characteristics, for output signal:

Delete "amplitude between 2 to 4 Vdc." and substitute " "0" state: 0.0 ± 0.5V; "1" state: 3.5 ± 1.0V."

PAGE 4

TABLE II, SIGNAL DELAY LIMITS, under DELAY LIMITS-NMT, for Step 5:

Delete "28.0" and substitute "38.0".

PAGE 7

* Figure 1, TEST FIXTURE SETUP, Under J1,

for TP1: Delete "11" and substitute "41"

for TP2: Delete "41 and substitute "11"

FSC: 1285

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:31Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity
Army - AR

(Project 1285-A537)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:31Z
Check the source to verify that this is the current version before use.