MIL-B-28599B(YD)
16 April 1984
SUPERSEDING
MIL-B-28599A(YD)
16 October 1979

MILITARY SPECIFICATION

BAG, LINEMAN'S GLOVE

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for a lineman's glove bag.

1.2 Classification. The bag shall be of the following compositions and styles (see 6.2).

Composition

A - Cotton duck.
B - 50 percent cotton - 50 percent nylon.
C - Vinyl-coated nylon.

Style 1 - Straight gusset (4 inch).
Style 2 - Tapered gusset.

1.2.1 Part number. The military specification part number for items described in this specification will be identified as follows:

	M28599	X	X
Military specification part number			
Composition			
Style			

Composition
A - Cotton duck.
B - 50 percent cotton - 50 percent nylon.
C - Vinyl-coated nylon.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:22Z
Check the source to verify that this is the current version before use.

Style
1 - Straight gusset, 4 inch.
2 - Tapered gusset.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-276 - Thread, Cotton.
V-T-285 - Thread, Polyester.
V-T-295 - Thread, Nylon.
CCC-C-419 - Cloth, Duck, Cotton, Unbleached, Plied Yarns, Army and Numbered.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-C-12369 - Cloth, Ballistic, Nylon.
MIL-G-16491 - Grommet, Metallic.
MIL-C-41836 - Cloth, Duck, Cotton and Nylon.

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams and Stitching.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as Department of Defense (DoD) adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:22Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D3951 - Commercial Packaging, Standard Practice For

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish a bag of the required composition and style for first article inspection and approval (see 4.2.1 and 6.4).

3.2 Standard commercial product. Each bag shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product shall be included in the bags being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs or brochures, and represents the latest production model.

3.3 System of measurement. The dimensions used in this specification are not intended to preclude the use of the metric system of measurement in the fabrication and production of the material, individual parts, and the finished product, provided form, fit, and function requirements are satisfied.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.4.1 Composition A, cotton duck. The cloth used in fabrication shall be made from natural, unbleached cotton duck cloth, conforming to CCC-C-419, type I, No. 8, hard texture.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:22Z
Check the source to verify that this is the current version before use.

3.4.2 Composition B, cotton-nylon. The cloth shall conform to MIL-C-41836.

3.4.3 Composition C, vinyl coated nylon. The cloth shall conform to MIL-C-12369.

3.4.4 Thread. Thread used in sewing shall conform to V-T-276, type IIIA or V-T-285, style I, or V-T-295, type I, and shall have a minimum breaking strength of 14 pounds.

3.4.5 Grommets. Grommets shall be provided in bottom or bottom gusset. The grommets and washers shall conform to MIL-G-16491, type III, class 8.

3.5 Design. The glove bag shall consist of a body with a gusset bottom and sides, equipped with a rust-resistant snap hook and dee ring for attachment to a lineman's belt.

3.5.1 Dimensions. The minimum dimensions of the bag shall be 15 inches long and 8 inches wide with a 4-inch gusset on each side (style 1). The bag may also have a tapered gusset at each side (style 2) (see 6.2). A tolerance of $\pm$ 1/4 inch shall be permitted.

3.5.2 Stitching. All stitching shall conform to type 301, FED-STD-751, 6 to 8 stitches per inch. Thread breaks in stitching shall be overstitched not less than 1 inch at each break. Stitching shall be backstitched not less than 1 inch at the ends except where ends are turned under in a hem or held down by over-stitching. Thread tension shall be maintained to prevent loose stitching. All thread ends shall be trimmed.

3.5.3 Seams. Seam allowance shall be maintained with seams properly sewn so that no runoffs, twists, pleats, puckers, or open seams shall result.

3.5.4 Setting of grommets. Holes, punched to receive the grommets, shall be smaller than the outside diameter of the grommet barrel, making it necessary to force the barrel through the hole. Grommets shall be securely clinched to avoid cutting of the material.

3.6 Special marking. Each bag shall be stenciled in a clear, legible manner with the words "ALWAYS WEAR YOUR GLOVES".

3.7 Workmanship. The quality of workmanship shall be such as to produce a glove bag that is in accordance with the requirements of the specification and is free of defects which would interfere with the use of the bag in the application for which it is intended.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:22Z
Check the source to verify that this is the currentversion before use.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one complete bag when a first article is required (see 3.1, 6.2, and 6.4). This inspection shall include the examination of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4 and the packaging inspection of 4.5. This inspection shall be performed on the samples selected in accordance with 4.3.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. All bags of the same composition and style offered for delivery at one time shall be considered a lot for the purpose of inspection. The inspection level shall be level II and the Acceptable Quality Level shall be 4.0 percent defective. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

4.4 Examination. Each sample bag selected shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements shall constitute a defect.

4.5 Packaging inspection. The preservation, packing, and marking of the item shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, B, or commercial as specified (see 6.2).

5.1.1 Level A. Each bag shall be preserved and packaged method IC in accordance with MIL-P-116. The applicable submethod shall be at the contractor's option.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:22Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Each bag shall be preserved and packaged method III in accordance with with MIL-P-116.

5.1.3 Commercial. Bags shall be preserved and packaged in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A or commercial as specified (see 6.2).

5.2.1 Levels A and B. Packing shall be accordance with MIL-STD-794. Containers shall be selected from table I for the appropriate level. Only closed containers shall be used.

5.2.2 Commercial. Bags shall be packed in accordance with ASTM D3951.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The glove bag is intended for use as a means of protecting lineman's rubber gloves when not in actual use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Composition of material (see 1.2).
c. Style of bag (see 1.2)
d. Applicable issue of the DoDISS (see 2.1.1)
e. If any specification, standard, or handbook is to be of an issue other than the issue listed in the DoDISS issue specified in the solicitation (see 2.1.1).
f. When first article is required for inspection and approval (see 3.1, 4.2.1, and 6.4).
g. When tapered gusset is required (see 3.5.1).
h. Level of preservation and level of packing required (see 5.1 and 5.2).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item or a standard production item from the contractors current inventory as specified in 4.2.1. The first article should consist of one complete bag. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, testing, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 20260-20T13:22Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing Activity:
Navy - YD

(Project 4240-N797)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:22Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:22Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-28599B(YD)	BAG, LINEMAN'S GLOVE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:22Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commander
Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:22Z
Check the source to verify that this is the current version before use.