MIL-R-28567B(YD)
24 December 1981
SUPERSEDING
MIL-R-28567A(YD)
23 April 1974

MILITARY SPECIFICATION

ROLLER, MOTORIZED, VIBRATING DRUM, ARTICULATED, PNEUMATIC TIRE

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a motorized roller, equipped with a vibrating steel drum and two pneumatic tires, mounted on an articulated frame, and powered by a diesel engine through a hydrostatic transmission.

1.2 Classification. The roller shall be of the following types, as specified (see 6.2):

Type I - Shall have vibration rate of 1600 ±100 vibrations per minute (vpm). Tires shall be non-directional traction type. Drum shall be tamping foot with option of smooth type.

Type II - Shall have vibration rate of 2100 ±200 vpm. Tires shall be smooth tread and roller shall be smooth drum only. Sprinkler system required.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-R-3075 - Rollers, Motorized, Road, Diesel- or Gasoline-Engine-Driven, Packaging of.
MIL-H-13531 - Hose, Rubber and Hose Assembly, Rubber (Hydraulic, Flexible).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3895

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

STANDARD

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.

T&RA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Description. The roller shall have a vibrating steel drum and two pneumatic tires, mounted on an articulated frame, driven by a diesel engine through a hydrostatic transmission and shall be type I (soil compaction) and type II (asphalt compaction).

3.2 First article. When specified (see 6.2), the contractor shall furnish a roller of the type specified for first article inspection and approval (see 4.3 and 6.4).

3.3 Standard commercial product. The roller shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product shall be included in the roller being furnished. A standard commercial product is a product which has been sold or is currently being offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.5 Identical items. All rollers of the same classification furnished under a specific contract shall be physically and mechanically identical. Parts, accessories, assemblies, and components are included in this requirement. Written approval for deviations must be obtained in advance from the contracting officer.

3.6 Maintainability. The roller shall be designed so that components are readily accessible for repair or replacement, with minimum removal or disturbance of adjacent parts or components, using general-purpose tools. Operating parts, accessories, and drain outlets shall be readily accessible for regular maintenance service.

3.7 Safety. All rotating or reciprocating parts, and all parts subject to high operational temperatures, that are of such nature or are so located as to be or become a hazard to the operating or attending personnel, shall be substantially guarded or insulated to the extent necessary to eliminate the hazard. An open canopy roll over protective structure is required. Handrails or holds shall be provided for operators mounting and dismounting. Automatic devices that will prevent the engine from starting when the transmission control lever is in any position but neutral shall be provided.

3.8 Performance, weight, and dimensions. The roller shall withstand the load and strain imposed without permanent deformation or damage while traveling at the speeds specified herein on rough terrain. Equipped with the either smooth or tamping foot type drum and without ballast, the roller shall weigh not less than 20,000 pounds. The roller shall conform to the dimensions as specified in table 1.

TABLE 1. Roller dimensions.

Item	Dimensions	
	Minimum	Maximum
Overall dimensions:		
Length (inches)	198	219
Width (inches)	95	106
Drum dimensions:		
Length (inches)	80	84
Head thickness (inches)	3/4	-
Wheel base (inches)	102	112
Turning radius (inches)	-	309
Curb clearance (inches)	15	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

3.9 Engine. The roller shall be powered by a rear-mounted diesel engine having horsepower, torque, and speed characteristics to meet satisfactorily all vehicular performance requirements specified herein. The diesel engine shall achieve self-sustained combustion at the manufacturer's rated idle speed in less than 5 minutes in ambient temperatures from -20° Fahrenheit (F) to +120°F. The engine shall be ready for full load operation in less than 15 minutes. When an ether priming system is furnished it shall be of the measured shot type with storage capacity of not less than 12 fluid ounces. The engine shall be furnished complete with at least the following accessories:

a. An instrument and control panel located at the operator's station; fitted with, but not necessarily limited to, the following:

   1. Liquid quantity fuel indicator.
   2. Lubricating oil pressure indicator.
   3. Cooling liquid temperature indicator.
   4. Tachometer.
   5. Hour meter, totalizing mechanism of not less than 9,999 hours.
   6. Battery charging indicator.
   7. Manual speed control.
   8. Emergency shutdown device.
   9. Normal shutdown device.

b. A 12-volt electrical cranking system with battery. The battery shall be 12-volt potential, lead acid, negative ground, and have a capacity of not less than 100 ampere-hours at the 20-hour rate. Battery shall be shipped charged, dry, and sealed to prevent absorption of atmospheric moisture. Electrolyte shall not be furnished.
c. A battery box painted with acid-resistant paint.
d. A battery charging alternator or generator with a rating of not less than 35 amperes.
e. A two-stage, dry type, intake, air cleaner with service indicator.
f. Safety control devices of the visual or audible type for high coolant temperature and low lubricating oil pressure.
g. Engine housing.
h. Fuel tank of sufficient capacity for 8 hours of normal operation.
i. Automatic switch or device to preclude accidental starts when transmission or drive system is in any mode except neutral.

3.10 Frame. The frame shall be constructed of structural steel sections or steel plates with members joined using one of the arc welding processes. Frame shall be reinforced to prevent distortion by utilizing cross braces, gussets, or a combination of both. Frame shall be hinged to facilitate steering. Hinge shall be located at or near the center of the roller and on the longitudinal axis of the frame. Hinge shall allow the vibrating drum to oscillate not less than 10° above and 10° below the drum's longitudinal axis. Frame shall be mounted on two drive wheels on rear and a single front drive vibrating drum (see 3.13). Manufacturer shall provide lockout device to preclude frame from articulating during servicing or carrier loaded for transport.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

3.11 Brakes. The service braking system, emergency stopping system, and parking system shall conform to the performance requirements of SAE J1136.

3.12 Rims, tires, and tubes. Tire and rim sizes shall conform to the Tire and Rim Association's recommendations for the type and size of the tires furnished. Tires for type I roller shall be superhard, wide base type, with hard rock lug treads. Tires for type II shall be of the smooth type for use when compacting asphalt. Tires shall be of not less than 100 level quality and of a rated capacity at least equal to the load imposed measured at each wheel at the ground. If tube type tires are furnished, tubes shall be heavy-duty type and of mating size with the tires. Tires shall be equipped with air-water valves.

3.13 Traction drive. Unless otherwise specified (see 6.2), power from the engine shall be transmitted to the drive wheels and the front drum by a hydrostatic drive, a selective gear transmission having not less than two-speeds forward and one-speed reverse, and a nonslip type differential. When specified (see 6.2), drum drive for type II roller shall not be furnished. Equipped with the smooth drum, the roller shall operate at any speed from 0.5 miles per hour (mph) up to not less than 6.5 mph while traveling on a level paved surface.

3.14 Drums. Unless otherwise specified (see 6.2), type I rollers shall be equipped with tamping foot type drums conforming to 3.14.2. When specified (see 6.2), type I rollers shall be equipped with smooth drums conforming to 3.14.1. The tamping foot drum shall be interchangeable with the smooth drum for type I rollers. Type II roller shall be equipped with a smooth drum conforming to 3.14.1.

3.14.1 Smooth drum. The length of the drum shall be as specified in table 1. The shell and heads of the drum shall be constructed of steel plates. The heads of the drum shall have a minimum thickness as specified in table 1. A drum equipped with an internal vibrating mechanism shall have a shell thickness of not less than 3/4 inch and an outside diameter of not less than 54 inches. A drum equipped with an external vibrating mechanism shall have a shell thickness of not less than 1/2 inch, shall be internally reinforced at mid-span, and shall have an outside diameter of not less than 48 inches. The outer surface of the shell shall be machined smooth. Joints between shell and heads shall be welded and the heads shall not incorporate provisions for ballasting. The drum shall be furnished with an axle assembly. Axle shall be mounted on antifriction type bearings.

3.14.2 Tamping foot drum. The tamping foot drum shall be furnished with an independent axle assembly mounted on antifriction type bearings. The minimum head and shell steel plate thicknesses for the tamping foot drum shall be as specified in 3.14.1. The quantity and type of tamping feet provided on the drum shall be the manufacturer's standard.

3.15 Drum cleaner(s). Replaceable and adjustable cleaner(s) shall be provided for the drum. The cleaner(s) shall extend over the full length of the drum for smooth drums and between feet for the tamping foot drums. Drum cleaner(s) shall prevent accumulation of material on the drum when the roller is propelled in either the forward or reverse direction.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

3.16 Vibrating mechanism. A variable frequency vibrating mechanism shall be provided. The vibrating mechanism shall have a minimum frequency of not less than 1600 ±100 vpm for type I and 2100 ±200 vpm for type II, with a range of frequency adjustment of not less than 350 vpm. Operating at the manufacturer's recommended maximum continuous frequency, the centrifugal force (cf) generated by the vibrating mechanism shall be not less than 23,000 pounds for the type I. Type II shall also have an adjustable amplitude capability that provides a range of centrifugal force from 6,400 pounds at minimum vpm to 40,500 pounds at maximum vpm and reversing eccentrics. The following formula shall be used to compute the minimum cf requirement specified herein:

$$CF = 0.000028416\ wrn^2$$

Where w = weight of eccentric revolving body in pounds
r = mean radius in inches
n = number of revolutions per minute

All rotating shafts shall be mounted on heavy-duty bronze or antifriction type bearings. The vibrating mechanism shall be driven by the roller's engine through a hydrostatic drive. Controls, located at the operator's station, shall control the engagement, disengagement, and frequency of the vibrating mechanism.

3.17 Hydraulic system. The hydraulic system shall be complete with all operating accessories, including pumps, reservoir, hydraulic cylinders, valves, pressure relief valves, filters, hoses, piping, and fittings. A wiper shall be provided on all cylinders adjacent to the piston rod seal to prevent dirt and abrasives from damaging the seal or entering the cylinders. The hydraulic system shall be equipped with a full flow, 10 micron (nominal) oil filter accessible for cleaning. Vents shall be equipped with filter elements to prevent dirt from entering the reservoir with the air. Suction line shall be above the reservoir bottom. Return line shall terminate below the minimum oil level of the reservoir. Drain plug shall be located at the lowest point in the tank and shall be of the magnetic type. All high pressure hydraulic hoses and fittings shall be capable of withstanding a bursting test pressure of four times the working pressure, and a maximum operating pressure of at least two times the working pressure. High pressure hydraulic hoses shall have physical qualities equal to or conforming to MIL-H-13531, type I or II, as applicable. Hydraulic oil shall be of the noncorrosive type, with the characteristics to withstand a temperature range from 10°F to 325°F.

3.18 Sprinkler system. Type II rollers shall be equipped with a sprinkler system for wetting the drum and rear tires. The sprinkler system shall include all piping, fittings, controls, and water tank(s) necessary to supply water to wet the full length of the drum and full width of the tires. Piping and fittings shall be nonferrous type, with the characteristics necessary to withstand vibration transmitted from the roller under all operating conditions. Separate controls shall be provided for the drum and the two tires. Water tank(s) shall have a total capacity of not less than 150 gallons. Tank(s) shall be equipped with vent and drain plug(s) that shall allow complete drainage of water.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

3.19 Lighting system. A complete 12-volt lighting system shall be provided. Lighting system shall include two forward and two rearward directed sealed beam floodlights. Lamp housings shall be provided with adjustable mounting brackets, and shall be positioned so the lights do not shine in the operator's eyes when in his normal operating position. All wiring shall be protected against wearing and weathering, and shall be so secured that no section exceeding 3 feet is unsupported. Grommets shall be used where wiring passes through structural steel sections and sheet metal to prevent chafing of the cable. Lamp housings shall be guarded adequately to prevent damage.

3.20 Operator's station. Roller shall be provided with an operator's station. Station shall be furnished with controls, an instrument panel, and an operator's seat. All controls necessary to operate the roller shall be located at the station. In addition to those instruments specified in 3.9 and 3.17, the instrument panel shall contain a frequency meter indicating vpm of the vibrating mechanism. Instruments shall be visible and controls shall be easily accessible to the operator in his normal sitting position. All controls and instruments shall be clearly identified for their intended operation and function with permanently affixed identification plates made of corrosion-resistant material. The operator's seat shall be adjustable, and shall be covered with a durable, waterproof covering. Steps or ladder rungs and handholds shall be furnished for easy access to the station by the operator. The station's deck and steps shall be provided with an antiskid surface. Station shall be isolated from vibrations generated by the vibrating mechanism.

3.21 Toolbox. The roller shall be equipped with a metal toolbox normally furnished on commercial model rollers. The toolbox shall have a hinged lid with a hasp for padlock. The toolbox shall be securely fastened to the roller in a readily accessible and a protected position.

3.22 Lifting and tie down attachments. The roller shall be equipped with lifting and tying down attachments. Lifting and tie down attachments shall conform to type II or type III of MIL-STD-209 "Slinging Eyes and Attachments for Lifting and Tie Down Military Equipment". Tying down attachments may be identified by stenciling or other suitable marking. Tie down marking shall clearly indicate that the attachments are intended for tying down the roller on the carrier when shipped.

3.23 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. Color of the finish coat shall be as specified (see 6.2).

3.23.1 Cleaning. Metal surfaces to be painted shall be cleaned to insure that they are free from all oil, grease, welding slag and spatter, mill scale which can be removed by power wire brushing, products of corrosion, dirt, or foreign substances.

3.23.2 Treatment. As soon as practicable after cleaning, and before any evidence of rust or other contamination can result, metal surfaces shall be treated with a primer pretreatment coating to increase the adhesion of the coating system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

3.23.3 Painting. For metal surfaces, painting shall consist of at least one coat of rust-inhibiting primer and one coat of finish enamel. The rust-inhibiting primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes except that the total dry film thickness shall be not less than 2.5 mils. The paint shall be free from runs, sags, orange peel, or other defects.

3.24 Identification, instruction, and transportation plates. Identification, instruction, and transportation plates shall be affixed to the roller in a conspicuous place. The instruction plate shall describe any special or important procedure to be followed in operating and servicing the roller. A diagram showing the lifting attachments and lifting sling shall be inscribed on the transportation plate, with the lifting capacity of each attachment and the required length and size of each sling cable marked thereon. A silhouette of the roller showing the center of gravity shall be provided. When specified (see 6.2), the identification plate shall be furnished by the contracting officer. The contractor shall stamp the required information in the appropriate blanks.

3.25 Lubrication. Lubrication shall be in accordance with the equipment manufacturer's recommendations. Pressure lubrication shall not damage seals or other parts. All parts requiring lubrication shall be lubricated prior to delivery and tagged to show the type and temperature rating of the lubricant used.

3.26 Workmanship.

3.26.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.26.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.26.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.26.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

3.26.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the casting ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Examination. Each roller shall be examined for compliance with the requirements specified in Section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.3 First article inspection. First article inspection shall be performed on one roller when a first article sample is required (see 3.2). This inspection shall include the examination of 4.2 and the tests of 4.4. The first article may be a standard production item from the supplier's current inventory provided the roller meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining rollers to be furnished under the contract.

4.4 First article tests. The first article shall be subjected to the tests specified in 4.4.1, 4.4.2, 4.4.3, and 4.4.5. In addition, type II roller shall be tested in accordance with 4.4.4. Failure to pass any phase of applicable tests shall be cause for rejection.

4.4.1 Maneuverability. Test course shall have a relatively level grade with a rough surface. Degree of roughness shall be sufficient to demonstrate the drum's ability to oscillate to its maximum limit. Course length shall be not less than 200 feet. Width shall be sufficient to allow roller to turn around without reversing the traction drive. The operator shall maintain the highest possible travel speed as dictated by the roughness of the course and without jeopardizing good safety practices. Roller shall perform the following maneuvers for not less than 20 minutes each. Vibrating mechanism shall operate at a frequency of not less than that specified, for the applicable type of roller being tested, in accordance with 3.16.

a. Figure-eight turns using the shortest possible turning radius and with the vibrating mechanism operating.
b. Travel back and forth in forward gear with vibrating mechanism operating.
c. Travel back and forth in reverse gear with vibrating mechanism operating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

Throughout the test, the roller shall be observed to verify compliance with the requirements as specified in 3.8, 3.10, 3.13, 3.15, and 3.16.

4.4.2 Brake system test. The brake system shall be tested to determine functionability and conformance to the requirements specified in 3.11 or the contractor shall furnish a certificate of compliance that the roller meets SAE J1136.

4.4.3 Tamping foot drum test. The type I roller, equipped with the tamping foot drum, shall be subjected to the maneuverability test as specified in 4.4.1.

4.4.4 Sprinkler test. Type II rollers shall be tested to determine conformance to the requirements specified in 3.18. Water tank(s) shall be filled to capacity. Roller shall be driven on a bituminous or asphalt paved surface throughout test. Sprinkler system shall be operated for not less than 30 minutes while roller is traveling at not less than 5 mph. Controls shall be operated as many times as necessary to determine ease of operation, effectiveness, and responsiveness. Upon completion of test, surplus water shall be drained from the tank(s).

4.4.5 Lifting and tying down attachments test. The roller shall be tested to verify that the attachments conform to the requirements specified in 3.22.

4.4.6 Production sample. Upon acceptance of the first article, the first article shall remain at the manufacturing facility as a production sample, and shall be the last roller delivered on the contract. The first article shall be reconditioned, including replacement of abnormally worn parts and paint touch-up or repainting, prior to delivery to enable it to be accepted as a contract item. The contractor shall maintain the first article in a serviceable condition for the duration of the contract.

4.5 Production operational tests. Each production roller shall be operated for 1 hour at speeds between 1 mph and top speed and at applicable vibrating frequency for the type roller being tested. All controls shall be operated as many times as necessary to determine ease of operation, effectiveness, responsiveness, and that the mechanisms actuated by the controls operate promptly, fully and without restriction, malfunction, or excessive vibration. The hydraulic system, including hoses, fittings, and seals shall be examined for evidence of leakage or failure. Gear cases, bearings, shafts, and other moving parts shall be tactually examined for excessive heating or abnormal operation insofar as is practicable. Failure to pass any phase of this test shall be cause for rejection.

4.6 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of Section 4 of MIL-R-3075. The inspection shall consist of the quality conformance inspection; and, when specified (see 6.2), a preproduction pack shall be furnished for examination and test within the time frame required (see 6.2).

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of ℄ with the level of preservation and the level of packing as specified (see 6.2). The following requirements shall also apply:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

5.1.1 Flywheel and starter drives. For level A, flywheel ring gears and starter drive mechanisms shall be preserved as specified in MIL-R-3075.

5.1.2 Clutch. For level A, the clutch shall be disassembled and preserved as specified in MIL-R-3075.

5.1.3 Brakes. For level A, brake components enclosed within brake drums and the braking surfaces of brake drums shall be preserved as specified in MIL-R-3085.

5.1.4 Depreservation guides. The depreservation guide may be in the contractor's standard format.

6. NOTES

6.1 Intended use. The type I roller is intended for use in compacting aggregate and earth. The type II roller is intended primarily for use in compacting hot and cold layed bituminous materials.

6.2 Ordering data. Acquisition documents should specify:

a. Title, number, and date of this specification.
b. Type of roller required (see 1.2).
c. When specifications and standards shall be other than as specified (see 2.1.1).
d. When a first article is required for inspection and approval (see 3.2, 4.3, and 6.4).
e. When a smooth type drum for type I, is also required (see 3.14).
f. When drum drive for type II roller is not required (see 3.13).
g. Color of finish coat required (see 3.23).
h. When identification plate shall be furnished by the contracting officer (see 3.24).
i. When a preproduction pack shall be furnished for inspection and time frame required for submission (see 4.6).
j. Level of preservation and packaging and level of packing required (see 5.1 and 5.2).

6.3 Contract data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article is required, it shall be tested and approved under the appropriate provisions of paragraph 7-104.55 of the DAR. The first article should be a first production item consisting of one complete roller unit or it may be a standard production item from the contractor's current inventory as specified in 4.3. The contracting officer should include specific instructions in all acquisition instruments regarding arrangement for examinations, tests, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Navy - YD

Review activity:

DLA - CS

Preparing activity:

Navy - YD

Project No. 3895-N194

Source: https://assist.dla.mil - Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE* if mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:14Z
Check the source to verify that this is the current version before use.