MILITARY SPECIFICATION

PROJECTILE, 64 MM, RIOT CONTROL, KE M743

This amendment forms a part of MIL-P-51474A(EA), dated 25 April 1984, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Delete paragraph 3.3.1 in its entirety and substitute the following:

"3.3.1 Wrap assembly. The wrap assembly shall have a maximum tensile strength of 81.0 pounds when tested in accordance with 4.4.4.1."

PAGE 7

Delete paragraph 4.4.4.1 in its entirety and substitute the following:

"4.4.4.1 Wrap assembly.

(a) Fixture. Use a test fixture consisting of two 1/4-inch-diameter pins which are parallel to each other and are oriented normal to the pull axis of the tensile tester. The pins must be free to rotate in their supports and have a free span pin length of 0.75 ± 0.01 inch.

(b) Procedure.

(1) Precondition the assembled projectile for 24 hours at 130° ± 5°F.

(2) Cool the projectile to room temperature in a low humidity environment such as a desiccator.

(3) Cut a 0.50 ± 0.01 inch wide test band from the breakband over the cavity area. Test the breakband within 5 minutes of removal from the projectile.

FSC 1310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

(4) Mount the test band in the test fixture.
(5) Set the pins 3.25 to 3.50 inches apart at the start of the test.
(6) Use a crosshead rate for the test band of 10 inches per minute.
(7) Set the recorder at 200 pounds full scale and use a recorder time constant of no greater than 1 second full scale.
(8) Record the ultimate load (maximum tensile strength) to the nearest 0.5 pound."

PAGE 8

4.4.4.2(c). Delete last sentence and substitute "These test firings shall be conducted under nil wind conditions in an indoor range constructed to contain the projectile. All access to the range shall be controlled during firing."

PAGE 9

Delete paragraph 6.3(b) in its entirety.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1310-A422

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.