The documentation and process conversion measures necessary to comply with this revision shall be completed by January 22, 2002.

INCH-POUND

MIL-PRF-19500/395F
AMENDMENT 1
23 October 2001

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, SWITCHING
TYPES 2N3735, 2N3735L, 2N3737 AND 2N3737UB
JAN, JANTX, JANTXV, JANS AND JANHC, JANKC

This amendment forms a part of MIL-PRF-19500/395F, dated 26 February 2001, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

4.3, screen 11, JANTX and JANTXV levels column, delete: "I_{CBO1}" and substitute: "I_{CBO2}".

PAGE 11

4.5.2.a, delete and substitute: "Collector current magnitude during power application shall be 45 mA dc minumum for 2N3735 and 2N3735L and 31 mA dc minimum for 2N3737. "

PAGE 13

TABLE I, subgroup 2, after forward current transfer ratio, symbol h_{FE3}, add:

"

Subgroup 2 - Continued.						
Forward current transfer ratio	3076	V_{CE} = 1.5 V dc; I_C = 1.0 A dc pulsed (see 4.5.1)	h_{FE4}	20	80	
Collector to emitter voltage (saturated)	3071	I_C = 10 mA dc, I_B = 1.0 mA dc	$V_{CE(sat)1}$		0.2	V dc
Collector to emitter voltage (saturated)	3071	I_C = 150 mA dc, I_B = 15 mA dc, pulsed (see 4.5.1)	$V_{CE(sat)2}$		0.3	V dc

"

Custodians:
Army - CR
Navy - NW
Air Force - 11
NASA - NA
DLA – CC

Preparing activity:
DLA - CC

(Project 5961-2522)

Review activities:
Army - AR, AV, MI, SM
Navy - AS, MC
Air Force - 19

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:27Z
Check the source to verify that this is the current version before use.