The documentation and process conversion measures necessary to comply with this amendment shall be completed by 20 December 1997

INCH POUND

MIL-PRF-19500/398C
AMENDMENT 1
20 September 1997

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, HIGH-FREQUENCY
TYPES 2N3866, 2N3866A JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/398C, dated 14 June 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 7

4.4.3.1, delete and substitute as follows:

" 4.4.3.1 Group C inspection, appendix E, table VII of MIL-PRF-19500.

Subgroup	Method	Conditions
C6	1026	T_A = room ambient as defined in the general requirements of section 4.5 of MIL-STD-750, V_{CB} = 28 V dc; P_T = 1. W.
C7	3005	Prepulse condition V_{CE} = 0, I_C = 0; Pulse condition I_C = 400 mA dc, t_P = 60s, 1 cycle: $t_r \leq$ 6s, $t_f \leq$ 6s, Sample size, N = 22, C =0 (see 4.5.4)."

PAGE 9

Table I, subgroup 2, $V_{(BR)CEX}$; delete entire test.

Table I, subgroup 2, $V_{CE(sat)}$conditions column; delete " I_B = 10 A dc;" and substitute "I_B = 10 mA dc".

PAGE 10

Subgroup 7 add the following:

"

Collector-emitter breakdown voltage (clamped inductive)	3011	V_{BE} = -1.5 V dc; I_C = 40 mA dc (see figure 6)	$V_{(BR)CEX}$	55		V dc

"

PAGE 16

Figure 6, add the following note:

"$V_{(BR)CEX}$ clamped at 10 percent over rating."

Figure 6, title; delete " unclamped" and substitute "clamped."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force - 19, 85, 99

Preparing activity:
DLA - CC

(Project 5961-1935)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.