The documentation and process conversion measures necessary to comply with this revision shall be completed by 11 December 2000.

INCH-POUND

MIL-PRF-19500/398E
11 September 2000
SUPERSEDING
MIL-PRF-19500/398D
15 January 2000

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, HIGH-FREQUENCY
TYPES 2N3866, 2N3866A JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN silicon, VHF-UHF amplifier transistor. Four levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (TO-39).

1.3 Maximum ratings.

P_T T_C = (3),	P_T (1) T_A = (2)	V_{CBO}	V_{CEO}	V_{EBO}	I_C	T_J and T_{STG}	$R_{\theta JC}$
W	W	V dc	V dc	V dc	A dc	°C	°C/W
2.9	1.0	60	30	3.5	0.4	-65 to +200	60

(1) Derate linearly 5.71 mW/°C above $T_A \geq +25°C$.
(2) T_A = Room ambient as defined in the general requirements of MIL-PRF-19500.
(3) P_T = 2.9 W at T_C = +25°C, derate at 16.6 mW/°C above T_C > +25°C.

1.4 Primary electrical characteristics.

	h_{FE} (1) V_{CE} = 5.0 V dc, I_C = 50 mA dc		$\lvert h_{fe} \rvert$ V_{CE} = 15 V dc, I_C = 50 mA dc, f = 200 MHz		$V_{CE(SAT)}$ I_C = 100 mA dc, I_B = 10 mA dc	C_{obo} V_{CB} = 28 V dc, I_E = 0, 100 kHz ≤ f ≤ 1 MHz	P_{out1} V_{CC} = 28 V dc, P_{in} = 0.15 W, f = 400 MHz	P_{out2} V_{CC} = 28 V dc, Pin = 0.075 W, f = 400 MHz
	2N3866	2N3866A	2N3866	2N3866A	V dc	pF	W	W
Min	15	25	2.5	4.0			1.0	0.5
Max	200	200	8.0	7.5	1.0	3.5	2.0	

(1) Pulsed (see 4.5.1)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Supply Center Columbus, ATTN: DSCC-VAC, 3990 East Broad Street, Columbus, OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5961

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

2. DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

DEPARTMENT OF DEFENSE

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. Devices furnished under this specification shall be products that are authorized by the qualifying activity for listing on the applicable qualified products list before contract award (see 4.2 and 6.3).

3.2 Associated specification. The individual item requirements shall be in accordance with MIL-PRF-19500 and as specified herein.

3.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

η: (eta) Collector efficiency = $\frac{\text{rf power out}}{\text{dc power in}} \times 100$


Pin: Input power

Pout: Output power

3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 (similar to T0-39) herein.

3.4.1 Lead finish. Lead finish shall be solderable as defined in MIL-PRF-19500. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Beyond r (radius) maximum, TW shall be held for a minimum length of 0.011 inch (0.28 mm).
4. TL measured from HD maximum.
5. Outline in this zone is not controlled.
6. CD shall not vary more than 0.010 inch (0.25 mm) in zone P. This zone is controlled for automatic handling.
7. Leads at gauge plane 0.054 + 0.001, - 0.000 inch (1.37 + 0.03, - 0.00 mm) below seating plane shall be within 0.007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC.
8. LU applies between L_1 and L_2. LD applies between L_2 and LL minimum. Diameter is uncontrolled in L_1 and beyond LL minimum.
9. All three leads.
10. The collector shall be electrically and mechanically connected to the case.
11. r (radius) applies to both inside corners of tab.

FIGURE 1. Physical dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CH	0.240	0.260	6.10	6.60	
LC	0 .200 TP		5.08 TP		7
LD	0.016	0.021	0.41	0.53	8, 9
LU	0.016	0.019	0.41	0.48	8, 9
HD	0.335	0.370	8.51	9.40	
CD	0.305	0.335	7.75	8.51	6
TW	0.028	0.034	0.71	0.86	3
TL	0.029	0.045	0.74	1.14	4
LL	0.500	0.750	12.70	19.05	8, 9
L_1		0.050		1.27	8, 9
L_2	0.250		6.35		8, 9
P	0.100		2.54		6
Q					5
r		0.010		0.25	11, 3
α	45° TP		45° TP		7

FIGURE 1. Physical dimensions - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

3.4.2 Transistor construction. These devices shall be constructed in a manner and using materials which enable the transistors to meet the applicable requirements of MIL-PRF-19500 and this document.

3.4.3 Marking. Devices shall be marked in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in 4.4.2 and 4.4.3 herein.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.3 Screening (JANS, JANTXV, and JANTX levels only). Screening shall be in accordance with MIL-PRF-19500 (table IV) and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of appendix E, of MIL-PRF-19500)	Measurement	
	JANS level	JANTX and JANTXV levels
3	Thermal impedance See 4.3.2	Thermal impedance See 4.3.2
9	I_{CEO} and h_{FE1}	Not applicable
11	I_{CEO} and h_{FE1}; ΔI_{CEO} = 100 percent of initial value or 2 µA dc, whichever is greater. Δh_{FE1} = ±20 percent of initial value.	I_{CEO} and h_{FE1}
12	See 4.3.1	See 4.3.1
13	ΔI_{CEO} = 100 percent of initial value or 2 µA dc, whichever is greater; Δh_{FE1} = ± 20 percent of initial value; subgroups 2 and 3 of table I herein.	ΔI_{CEO} = 100 percent of initial value or 2 µA dc, whichever is greater; Δh_{FE1} = ± 20 percent of initial value; subgroup 2 of table I herein.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows:
T_A = room ambient as defined in the general requirements of MIL-STD-750; V_{CB} = 10 to 30 V dc. Power shall be applied to achieve a junction temperature T_J =135°C minimum and power dissipation of $P_T \geq 75$ percent of max rated P_T as defined in 1.3 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

4.3.2 Thermal impedance ($Z_{\theta JX}$ measurement). The $Z_{\theta JX}$ measurements shall be performed in accordance with MIL-STD-750, method 3131and as follows:

a. I_M measurement current .....5 mA.

b. I_H forward heating current.....200 mA (minimum).

c. t_H heating time .....25 – 30 ms.

d. t_{md} measurement delay time.....60 µs maximum.

e. V_{CE} collector emitter voltage.....10 V dc.

The maximum limit for $Z_{\theta JX}$ under these test conditions are: $Z_{\theta JX}$ (max) = 50°C/W.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in VIa (JANS) of 4.4.2.1. See 4.4.2.2 herein for JAN, JANTX, and JANTXV group B testing. Electrical measurements (end-points) requirements shall be in accordance with group A, subgroup 2 herein. Delta requirements apply to the subgroups specified in 4.4.2.1 and 4.4.2.2, and shall be those specified in 4.5.5.

4.4.2.1 Group B inspection, table VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Conditions
B4	1037	V_{CB} = 10 V dc; 2,000 cycles.
B5	1027	V_{CB} = 10 V dc; T_A = +125°C ± 25°C for 96 hours; P_T adjusted according to the chosen T_A to give an T_J = +275°C min. Optionally this test may be performed for a minimum of 216 hours with P_T adjusted to achieve a T_J = +225°C minimum, sample size = 45, cc = 0. In this case the ambient temperature shall be adjusted such that minimum of 75 percent of max rated P_D (see 1.3) is applied to the DUT. (Note: If a failure occurs, resubmission shall be at the test conditions of the original sample).

4.4.2.2 Group B inspection, table VIb (JAN, JANTX and JANTXV). Separate samples may be used for each step. In the event of a group B failure, the manufacturer may pull a new sample at double size from either the failed assembly lot or from another assembly lot from the same wafer lot. If the new “assembly lot” option is exercised, the failed assembly lot shall be scrapped.

Step	Method	Conditions
1	1027	Steady state life: test condition B, 340 hours, V_{CB} = 10 - 30 V dc; Power shall be applied to achieve T_J = 150°C minimum and a power dissipation of $P_D \geq 75$ percent of max rated P_T as defined in 1.3. n = 45 devices, c = 0. For small lots, n = 12 devices, c = 0

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

2	1027	The steady state life test of step 1 shall be extended to 1,000 hours for each die design. Samples shall be selected from a wafer lot every twelve months of wafer production. Group B step 2 shall not be required more than once for any single wafer lot. N = 45, c = 0.
3	1032	High temperature life (non operating), t = 340 hours, ; T_A = +200°C. n = 22, c = 0.

4.4.2.3 Group B sample selection. Samples selected from group B inspection shall meet all of the following requirements.

a. For JAN, JANTX and JANTXV samples shall be selected randomly from a minimum of three wafers (or from each wafer in the lot) from each wafer lot. For JANS samples shall be selected from each inspection lot. See MIL-PRF-19500.

b. Must be chosen from an inspection lot that has been submitted to and passed group A, subgroup 2 conformance inspection. When the final lead finish is solder or any plating prone to oxidation at high temperature, the samples for life test (subgroups B4 and B5 for JANS, and group B for JAN, JANTX and JANTXV) may be pulled prior to the application of final lead finish.

4.4.3 Group C inspection, Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500, and in 4.4.3.1 (JANS).and 4.4.3.2 (JAN, JANTX, and JANTXV) herein for group C testing. Electrical measurements (end points) requirements shall be in accordance with group A, subgroup 2 herein. Delta requirements apply to the subgroups C6 and C8, and shall be those specified in 4.5.5.

4.4.3.1 Group C inspection, table VII (JANS) of MIL-PRF-19500.

Subgroup	Method	Conditions
C2	2036	Test condition E.
C5	3131	See 4.5.2; n = 22, c =0
C6	1026	Steady state life: test condition B, 1,000 hours, V_{CB} = 10 V dc; Power shall be applied to achieve T_J = 150°C minimum and a power dissipation of $P_D \geq 75$ percent of max rated P_T as defined in 1.3. N = 45 devices, c = 0. For small lots, n = 12 devices, c = 0

4.4.3.2 Group C inspection, table VII (JAN, JANTX and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Conditions
C2	2036	Test condition E.
C6		Not applicable.
C8	3005	Prepulse condition V_{CE} = 0, I_C = 0; Pulse condition I_C = 400 mA dc, t_P = 60 s, 1 cycle; $t_r \leq 6s$, $t_f \leq 6s$. Sample size, n = 22, c = 0 (see 4.5.4).

4.4.3.3 Group C sample selection. Samples for subgroups in group C shall be chosen at random from any inspection lot containing the intended package type and lead finish procured to the same specification which is submitted to and passes group A tests for conformance inspection. Testing of a subgroup using a single device type enclosed in the intended package type shall be considered as complying with the requirements for that subgroup.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in MIL-STD-750.

4.5.2 Thermal resistance. Thermal resistance measurements shall be conducted in accordance with test method 3131 of MIL-STD-750. The following details shall apply:

a. Collector current magnitude during power application shall be 79 mA dc minimum.

b. Collector to emitter voltage magnitude shall be 20 V dc minimum.

c. Reference temperature measuring point shall be the case.

d. Reference point temperature shall be $+25°C \leq T_R \leq +75°C$ and recorded before the test is started.

e. Mounting arrangement shall be with heat sink to case.

f. Maximum limit of $R_{\theta JC}$ shall be 60°C/W.

4.5.3 Power-output and collector-efficiency measurements. The device shall be tested in the circuit of figure 2 using the procedure outlined on figure 3. The specified conditions shall be applied and the variable capacitors adjusted to obtain maximum power output. When the maximum power output is obtained, the collector current shall be measured and recorded. The collector efficiency shall be computed as follows:

$$\eta \text{ in percent} = \frac{P_O \text{ (watts)} \times 100}{28 \times I_C \text{ (amperes)}}$$

4.5.4 Burnout by pulsing. The devices shall be tested in the circuit of figure 4. The voltage source shall be increased from zero until the specified current is reached. The current shall be maintained for the specified time.

4.5.5 Delta requirements. Delta requirements shall be as specified below:

Step	Inspection	MIL-STD-750		Symbol	Limit		Unit
		Method	Conditions		Min	Max	
1.	Collector to emitter cutoff current	3036	Bias condition D; V_{CE} = 28 V dc	ΔI_{CEO} (1)	± 100 percent of initial value or 2 µA dc, whichever is grearer.		
2.	Forward current transfer ratio	3076	V_{CE} = 5 V dc, I_C = 50 mA dc (pulsed see 4.5.1)	Δh_{FE1} (1)	± 25 percent from initial reading.		
3.	Collector to emitter voltage (saturated)	3071	I_C = 100 mA dc, I_B = 10 mA dc, (pulsed see 4.5.1)	$\Delta V_{CE(sat)1}$ (1) (2)	± 50 mV dc change from previous measured value.		

(1) Devices which exceed group A limits shall be consider failures.

(2) JANS only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1 2/						
Visual and mechanical 3/ Examination	2071	n = 45 devices, c = 0				
Solderability 3/ 4/	2026	n = 15 leads, c = 0				
Resistance to 3/ 4/ 5/ Solvent	1022	n = 15 devices, c = 0				
Temp cycling 3/ 4/	1051	Test condition C, 25 cycles. n = 22 devices, c = 0				
Heremetic seal 4/	1071	n = 22 devices, c = 0				
Fine leak Gross leak						
Electrical measurements 4/		Group A, subgroup 2				
Bond strength 3/ 4/	2037	Precondition T_A = +250°C at t = 24 hrs or T_A = +300°C at t = 2 hrs, n = 11 wires, c = 0				
Subgroup 2						
Collector-emitter breakdown voltage	3011	Bias condition D; I_C = 5 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	30		V dc
Collector-base breakdown voltage	3001	Bias condition D; I_C = 100 µA dc; pulsed (see 4.5.1)	$V_{(BR)CBO}$	60		V dc
Emitter-base breakdown voltage	3026	Bias condition D; I_E= 100 µA dc; pulsed (see 4.5.1)	$V_{(BR)EBO}$	3.5		V dc
Collector-emitter cutoff current	3041	Bias condition D; V_{CE} = 28 V dc	I_{CEO}		20	µA dc
Collector-emitter cutoff current	3041	Bias condition C; V_{CE} = 55 V dc	I_{CES1}		100	µA dc
Forward-current transfer ratio 2N3866 2N3866A	3076	V_{CE} = 5.0 V dc; I_C = 50 mA dc; pulsed (see 4.5.1)	h_{FE1}	 15 25	 200 200	

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 2 continued						
Forward-current transfer ratio 2N3866 2N3866A	3076	V_{CE} = 5.0 V dc; I_C = 360 mA dc; pulsed (see 4.5.1)	h_{FE2}	 5.0 8.0		
Collector-emitter saturated voltage	3071	I_C = 100 mA dc; I_B = 10 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)}$		1.0	V dc
Subgroup 3 High temperature operation		T_A = +150°C				
Collector to emitter Cutoff current	3041	Bias condition C; V_{CE} = 55 V dc	I_{CES2}		2.0	mA dc
Subgroup 3 – Continued						
Low temperature operation		T_A = -55°C				
Forward-current transfer ratio 2N3866 2N3866A	3076	V_{CE} = 5.0 V dc; I_C = 50 mA dc; pulsed (see 4.5.1)	h_{FE3}	 7 12		
Subgroup 4						
Magnitude of small-signal short-circuit current transfer ratio 2N3866 2N3866A	3306	V_{CE} = 15 V dc; I_C = 50 mA dc; f = 200 MHz	$\lvert h_{fe} \rvert$	 2.5 4.0	 8.0 7.5	
Open circuit output capacitance	3236	V_{CB} = 28 V dc; I_E = 0	C_{obo}		3.5	pF
Power output		V_{CC} = 28 V dc; P_{in} = 0.15 W; f = 400 MHz (see figure 2 and 4.5.3)	P_{1out}	1.0	2.0	W
Power output		V_{CC} = 28 V dc; P_{in} = 0.075 W; f = 400 MHz (see figure 2 and 4.5.3)	P_{2out}	0.5		W
Collector-efficiency		V_{CC} = 28 V dc; P_{in} = 0.15 W; f = 400 MHz (see 4.5.3)	η_1	45		%
Collector-efficiency		V_{CC} = 28 V dc; P_{in} = 0.075 W; f = 400 MHz (see 4.5.3)	η_2	40		%

See footnote at end of table.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 6 Not applicable						
Subgroup 7						
Collector-emitter breakdown voltage (clamped inductive)	3011	V_{BE} = -1.5 V dc; I_C = 40 mA dc (see Figure 5)	$V_{(BR)CEX}$	55		V dc

1/ For sampling plan see MIL-PRF-19500.
2/ For resubmission of failed subgroup A1, double the sample size of the failed test or sequence of tests. A failure in group A, subgroup 1 shall not require retest of the entire subgroup. Only the failed test shall be rerun upon submission.
3/ Separate samples may be used.
4/ Not required for laser marked devices.
5/ Not required for JANS devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.




C_1, C_2, C_5 = 3 - 35 pF.
C_3 = 24 pF (see note).
C_4 = 0.4 - 7 pF.
L_1 = Straight piece number 16 bare tin wire, 0.625 inch long.
L_2 = 3 turns number 16 wire, 0.250 inch ID, 0.312 inch long.
L_3 = 1 turns number 18 wire, 0.250 inch ID, 0.022 inch long.
L_4 = Ferrite RF choke, Z = 450 Ω.

NOTE: For optimum performance, C_3 should be mounted as close as possible to base lead.

FIGURE 2. Power - output test circuit (400 MHz).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.



NOTES:

1. Test fixture is the circuit as described on figure 2.
2. RF power source may be any unit capable of generating desired power level at desired frequency with a harmonic and spurious content at least 20 dB below operating frequency level.
3. The RF isolator may be any device (pad, circulator, ect.) capable of establishing at least 20 dB of isolation (RL > 20 dB) between RF source and test fixture.
4. Variable attenuators (or fixed if calibrated): Attenuator on directional coupler number 2 shall be calculated against known working standard either by means of calibration chart or suitable adjustment if variable. Attenuator at position "A" of directional coupler number 1 shall be calibrated or adjusted so that actual power at test fixture is known. Attenuator at position "B" shall be adjusted to establish sensitivity needed to measure VSWR.
5. RF switch may be eliminated if additional power meters are used.

PROCEDURE:

a. Remove "test fixture" and install jumper between directional coupler number 1 and directional coupler number 2.
b. Set the RF switch to power output position "C".
c. Adjust frequency and power of RF source, as required by specification, and monitor frequency counter and RF power meter respectively (see note 4).
d. Set the RF switch to position "A" and adjust variable attenuator to obtain identical reading as power out in position "C" (see note 4).
e. Reconnect "test fixture" in test setup and insert device.
f. Adjust power supply to 28 V dc.
g. Adjust circuit output tuning for maximum power gain and circuit input tuning for maximum VSWR. (Switch between power in; VSWR, and power out while tuning and repeat as many times as necessary to obtain minimum VSWR and maximum power out. Check power in level before taking final reading. Minimum VSWR is defined as minimum reading obtained on power meter with switch in position "B" and maintaining power in.)

FIGURE 3. RF power output (P_{OUT}) test procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.





FIGURE 4. Burnout by pulsing test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.



R_{BB1} = 150 Ω.

V_{BB1} = 20 V dc.

K = s.p.s.t relay, 6 V ac coil (Clare Mercury Relay, model number HGP-1400, or equivalent).

R_{BB2} = 33 Ω.

V_{BB2} = 1.5 V dc.

R_S = 1 Ω ± 1 percent, .5 watt (noninductive).

V_{CC} = The voltage should be adjusted to approximately 17 volts.

L = 25 mH, 100 mA, 83 Ω resistive (Miller number 957, or equivalent).

Vclamp = 55 V (min).

$V_{(BR)CEX}$ clamped at 10 percent over rating.

FIGURE 5. $V_{BR(CEX)}$ (clamped inductive) test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. Packaging shall prevent mechanical damage of the devices during shipping and handling and shall not be detrimental to the device. When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points' packaging activity within the Military Department or Defense Agency, or within the Military Departments' System Command. Packaging data retrieval is available from the managing Military Departments' or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Issue of DODISS to be cited in the solicitation (see 2.2.1).

b. The lead finish as specified (see 3.4.1).

c. Type designation and quality assurance level.

d. Packaging requirements (see 5.1).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturer’s List QML No.19500 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center Columbus, DSCC-VQE, 3990 E. Broad Street, Columbus OH 43216-5000.

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA – NA
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force – 19, 99

Preparing activity:
DLA - CC

(Project 5961-2129)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-PRF-19500/398E	2. DOCUMENT DATE 000911

3. **DOCUMENT TITLE**
SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, HIGH-FREQUENCY TYPES 2N3866, 2N3866A JAN, JANTX, JANTXV, AND JANS

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) COMMERCIAL DSN FAX EMAIL	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. Point of Contact Alan Barone	b. TELEPHONE Commercial 614-692-0510 DSN 850-0510 FAX 614-692-6939 EMAIL alan_barone@dscc.dla.mil
c. ADDRESS Defense Supply Center Columbus, ATTN: DSCC-VAC, 3990 East Broad Street, Columbus, OH 43216-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman, Suite 2533, Fort Belvoir, VA 22060-6221 Telephone (703) 767-6888 DSN 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:32Z
Check the source to verify that this is the current version before use.