The documentation and process conversion measures necessary to comply with this revision shall be completed by 17 September 2004.

INCH-POUND

MIL-PRF-19500/402D
17 March 2004
SUPERSEDING
MIL-PRF-19500/402C
30 August 1999

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, POWER,
TYPE 2N3739,
JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

* The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, power transistors. Three levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (similar to TO-66).

1.3 Maximum ratings.


Types	P_T (1) T_C = +25°C	P_T (2) T_C = +100°C	$R_{\theta JC}$	V_{CBO}	V_{CEO}	V_{EBO}	I_B	I_C	T_{STG} and T_J
	W	W	°C/W	V dc	V dc	V dc	A dc	A dc	°C
2N3739	20	10	7.5	325	300	6.0	0.5	1.0	-55 to +200

* (1) Derate linearly, 0.133 W/°C for $T_C \geq +25°C$. For temperature-power derating curves, see figure 2.
* (2) Derate linearly, 0.100 W/°C for $T_C \geq +100°C$. For temperature-power derating curves, see figure 2.

* Comments, suggestions, or questions on this document should be addressed to Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43216-5000, or emailed to Semiconductor@dscc.dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://www.dodssp.daps.mil/.

AMSC N/A FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		.620		15.75	
CH	.250	.340	6.35	8.64	
HR		.350		8.89	
HR1	.115	.145	2.92	3.68	
HT	.050	.075	12.70	1.91	
LD	.028	.034	0.71	0.86	4, 6
LL	.360	.500	9.14	12.70	
L1		.050		1.27	6
MHD	.142	.152	3.61	3.86	4
MHS	.958	.962	24.33	24.23	
PS	.190	.210	4.83	5.33	3
PS1	.093	.107	2.36	2.72	3
S	.570	.590	14.48	14.99	
Term 1	Emitter				
Term 2	Base				
Term 3	Collector				

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. These dimensions should be measured at points .050 inch (1.27 mm) +.005 inch (0.13 mm) -.000 inch (0.00 mm) below seating plane. When gauge is not used, measurement will be made at the seating plane.
4. Two places.
5. The seating plane of the header shall be flat within .001 inch (0.03 mm) concave to .004 inch (0.10 mm) convex inside a .930 inch (23.62 mm) diameter circle on the center of the header and flat within .001 inch (0.03 mm) concave to .006 inch (0.15 mm) convex overall.
6. Lead diameter shall not exceed twice LD within L_1.
7. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

* FIGURE 1. Physical dimensions (similar to TO-66).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics at T_A = +25°C.

Limit	h_{FE1} (1)	h_{FE3} (1)	V_{BE}	$V_{CE(SAT)}$	C_{obo}	$\|h_{fe}\|$	Switching	
	V_{CE} = 10 V dc I_C = 10 mA dc	V_{CE} = 10 V dc I_C = 100 mA dc	V_{CE} = 10 V dc I_C = 100 mA dc	I_C = 250 mA dc I_B = 25 mA dc	V_{CB} = 100 V dc I_E = 0 mA dc 100 kHz≤f≤1 MHz	V_{CE} = 10 V dc I_C = 100 mA dc f = 10 MHz	t_{on}	t_{off}
			V dc	V dc	pF		µs	µs
Min	30	40				1		
Max		200	1	2.5	20	6	1.5	3.5

(1) Pulsed (see 4.5.1).

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

* 2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

* DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

* DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://www.dodssp.daps.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

* 3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

* 3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

* 3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1.

* 3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

* 3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical characteristics are as specified in 1.3, 1.4 and table I.

* 3.6 Electrical test requirements. The electrical test requirements shall be as specified in table I.

* 3.7 Marking. Marking shall be in accordance with MIL-PRF-19500.

* 3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

* c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

* 4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein shall be performed by the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

* 4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with table IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500	Measurement
	JANTX and JANTXV levels only
9	Not applicable
11	h_{FE2} and I_{CBO1}
12	See 4.3.1
13	Subgroup 2 of table I herein, ΔI_{CBO1} = 100 percent of initial value or 10 µA dc, whichever is greater Δh_{FE2} = ±20 percent of initial value

* 4.3.1 Power burn-in conditions. Power burn-in conditions are as follows:

2N3739 - - - - V_{CB} = 10 - 30 V dc, T_J = +162.5°C ±12.5°C

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein. Group A inspection shall be performed on each sublot.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VIb (JAN, JANTX, and JANTXV), of MIL-PRF-19500 and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 and delta requirements shall be in accordance with 4.5.2 herein.

	Subgroup	Method	Conditions
*	B3	1037	For solder die attach: $V_{CB} \geq 10$ V dc, 2,000 cycles. $T_A \leq +35°C$.
		1026	For eutectic die attach: V_{CB} = 10 V dc, $T_A \leq +35°C$ adjust P_T to achieve $T_J = +150°C$ min.
	B6		Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table VII of MIL-PRF-19500 and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 and delta requirements shall be in accordance with 4.5.2 herein.

Subgroup	Method	Conditions
C6	1037	For solder die attach: $V_{CB} \geq 10$ V dc, 6,000 cycles. $T_A \leq +35°C$.
	1026	For eutectic die attach: $V_{CB} = 10$ V dc, $T_A \leq +35°C$ adjust P_T to achieve $T_J = +150°C$ min.

* 4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table IX of MIL-PRF-19500 and as specified in table II herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta requirements shall be in accordance with 4.5.2 herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows:

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

* 4.5.2 Delta requirements. Delta requirements shall be as specified below:

Step	Inspection (1) (2) (3)	MIL-STD-750		Symbol	Limit	Unit
		Method	Conditions			
1	Collector to base cutoff current	3036	Bias condition D; $V_{CB} = 325$ V dc	ΔI_{CBO}	100 percent or 10 µA dc, whichever is greater	
2	Forward-current transfer ratio	3076	$V_{CE} = 10$ V dc; $I_C = 100$ mA dc pulsed (see 4.5.1)	Δh_{FE1}	±25 percent change from initial recorded value.	

(1) The electrical measurements for table VIb (JAN, JANTX and JANTXV) of MIL-PRF-19500 are: Subgroups 3 and 6, 4.5.2 herein, steps 1 and 2.
(2) The electrical measurements for table VII of MIL-PRF-19500 are: Subgroup 6, see 4.5.2 herein, steps 1 and 2.
(3) The electrical measurements for table IX of MIL-PRF-19500 are: Subgroups 1 and 2, see 4.5.2 herein, steps 1 and 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Breakdown voltage, collector to emitter	3011	Bias condition D, I_C = 5.0 mA dc	$V_{(BR)CEO}$	300		V dc
Collector to base cutoff current	3036	Bias condition D, V_{CB} = 325 V dc	I_{CBO1}		0.1	mA dc
Collector to emitter cutoff current	3041	Bias condition A, V_{CE} = 300 V dc, V_{BE} = 1.5 V dc	I_{CEX}		0.5	mA dc
Emitter to base cutoff current	3061	Bias condition D, V_{EB} = 6.0 V dc	I_{EBO}		0.1	mA dc
Base to emitter, non-saturated voltage	3066	Test condition B, V_{CE} = 10 V dc, I_C = 100 mA dc; pulsed (see 4.5.1)	V_{BE}		1	V dc
Collector to emitter voltage (saturated)	3071	I_C = 100 mA dc; I_B = 10 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$		0.75	V dc
Collector to emitter voltage (saturated)	3071	I_C = 250 mA dc; I_B = 25 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		2.5	V dc
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 10 mA dc; pulsed (see 4.5.1)	h_{FE1}	30		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 50 mA dc; pulsed (see 4.5.1)	h_{FE2}	30		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 100 mA dc; pulsed (see 4.5.1)	h_{FE3}	40	200	
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 250 mA dc; pulsed (see 4.5.1)	h_{FE4}	25		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 500 mA dc; pulsed (see 4.5.1)	h_{FE5}	10		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

	Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
	Subgroup 3						
	High-temperature operation:		T_A = +150°C				
*	Collector to base cutoff current	3036	Bias condition D, V_{CB} = 325 V dc	I_{CBO2}		150	µA dc
	Low-temperature operation:		T_A = -55°C				
	Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 100 mA dc; pulsed (see 4.5.1)	h_{FE6}	15		
	Subgroup 4						
	Pulse response:						
*	Turn-on time		V_{CC} = 150 V dc; I_C = 500 mA dc; I_B = 50 mA dc (see figure 3)	t_{on}		1.5	µs
*	Turn-off time		V_{CC} = 150 V dc; I_C = 500 mA dc; I_{B1} = I_{B2} = 50 mA dc (see figure 3)	t_{off}		3.5	µs
	Magnitude of common emitter, small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 100 mA dc; f = 10 MHz	$\|h_{FE}\|$	1.0	6	
*	Small-signal short-circuit forward-current transfer ratio	3206	V_{CE} = 20 V dc; I_C = 100 mA dc f = 1 kHz	h_{fe}	35	300	
	Open circuit output capacitance	3236	V_{CB} = 100 V dc; I_E = 0 mA dc; 100 kHz ≤ f ≤ 1 MHz	C_{obo}		20	pF
	Subgroup 5						
*	Safe operating area (continuous dc)	3051	T_C = +25°C; t = 1 s; 1 cycle; (see figure 4)				
	Test 1		V_{CE} = 80 V dc; I_C = 250 mA dc				
	Test 2		V_{CE} = 290 V dc; I_C = 6 mA dc				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

	Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
	Subgroup 5 - Continued						
*	Safe operating area (switching)	3053	Load condition C (unclamped inductive load) (see figure 5)				
			T_A = +25°C; duty cycle ≤ 10 percent; R_s = 1Ω; $t_r = t_f \leq 500$ ns				
	Test 1		t_p approx 8 ms (vary to obtain I_C); R_{BB1} = 100Ω; $V_{BB1} \geq 10$ V dc; $R_{BB2} = \infty$; V_{BB2} = 0 V dc; $V_{CC} \geq 100$ V dc; I_C = 500 mA dc; the coil used shall provide a minimum inductance of 3.5 mH at 500 mA with max. dc resistance of 0.5 ohm (for reference only: Acme T58220, or equivalent)				
	Test 2		t_p approx 8 ms (vary to obtain I_C); R_{BB1} = 100Ω; $V_{BB1} \geq 10$ V dc; $R_{BB2} = \infty$; V_{BB2} = 0 V dc; $V_{CC} \geq$ 100 V dc; I_C = 100 mA dc; the coil used shall provide a minimum inductance of 25 mH at 100 mA with max. dc resistance of 1.0 ohm (for reference only: Triad C-48u, centertapped, or equivalent.)				
*	Safe operating area (switching)		T_A = +25°C; duty cycle ≤ 10 percent; t_p approx 8 ms (vary to obtain I_C); $V_{CC} \geq 100$ V dc; I_C = 1 A dc; R_s = 1Ω; clamp voltage = 300 V dc (see figure 6)				
	Electrical measurements		See table I, subgroup 2				


1/ For sampling plan, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

* TABLE II. Group E inspection (all quality levels) - for qualification and re-qualification only.

Inspection	MIL-STD-750		Qualification
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling	1051	500 cycles	
Hermetic seal Fine leak Gross leak	1071	 Test conditions G or H Test conditions C or D	
Electrical measurements		See table I, subgroup 2 and 4.5.2, steps 1 and 2.	
Subgroup 2			45 devices c = 0
High temperature reverse bias	1039	Condition A; 1,000 hrs	
Electrical measurements		See table I, subgroup 2 and 4.5.2, steps 1 and 2.	
Subgroup 3			3 devices c = 0
DPA	2102		
Subgroup 4			Sample size N/A
Thermal impedance curves		Each supplier shall submit their (typical) design maximum thermal impedance curves. In addition, the optimal test conditions and $Z_{\theta JX}$ limit shall be provided to the qualifying activity in the qualification report	
Subgroup 5			15 devices c = 0
Barometric pressure	1001	See 1.3	
Subgroup 6			
Not applicable			
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition A for devices ≥ 400 V, condition B for devices < 400 V.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.



DC Operation
$R_{\theta JC}$ = 7.5°C/W


Note: Max finish alloy temp = +175°C

NOTES:

1. Maximum theoretical derate design curve. This is the true inverse of the worst case thermal resistance value. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ +200°C) and power rating specified. (See 1.3 herein)
3. Derate design curve chosen at T_J ≤ +150°C, where the maximum temperature of electrical test is performed.
4. Derate design curve chosen at T_J ≤ +125°C, and +110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 2. Temperature-power derating graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.




NOTES:

1. The rise time (t_r) and fall time (t_f) of the applied pulse shall be each ≤ 20 ns; duty cycle ≤ 1 percent; generator source impedance shall be 50 ohms.
2. Output sampling oscilloscope: $Z_{in} \geq 100$ kΩ; $C_{in} \leq 50$ pF; rise time ≤ 2.0 ns.


* FIGURE 3. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.




* FIGURE 4. Maximum safe operating area graph (continuous dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.



* FIGURE 5. Safe operating area for switching between saturation and cutoff (unclamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.



NOTES:
1. Either a clamping circuit or clamping diode may be used.
2. The coil used shall provide a minimum inductance of 25 mH at 1 A with a maximum dc resistance of 1 ohm. For reference only: Triad C-48u (center-tapped), or equivalent (see 4.4.5)
3. $R_S \leq 1$ ohm, 12 W, 1% tolerance max., (noninductive).

Procedure:
1. With switch S_I closed, set the specified test conditions.
2. Open S_1. Device fails if clamp voltage not reached and maintained until the current returns to zero.
3. Perform specified endpoint tests.

* FIGURE 6. Clamped inductive sweep test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

* 6.1 Intended use The notes specified in MIL-PRF-19500 are applicable to this specification.

* 6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Product assurance level and type designator.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML No. 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43216-5000 or e-mail vqe.chief@dla.mil.

* 6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2853)

Review activities:
Army - AV, MI, SM
Navy - AS, MC, SH
Air Force - 19

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://www.dodssp.daps.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.