The documentation and process conversion measures necessary to comply with this amendment shall be completed by 6 December 2000.

INCH-POUND

MIL-PRF-19500/404C
AMENDMENT 1
6 September 2000

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, RECTIFIER, MODULE
HIGH VOLTAGE, 1N5597, 1N5600, 1N5603,
JAN, JANTX AND JANTXV

This amendment forms a part of MIL-PRF-19500/404C, dated 30 July 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.3, delete "$V_{BR(CEO)}$" and substitute "V_{BR}"

PAGE 5

4.3, screen table, screen column, screen 9, add "& 10"; screen 11, measurement column, delete "V_{F1}" and substitute "V_{F2}"; screen 13, measurement column, delete "ΔV_{F1}" and substitute "ΔV_{F2}", end of paragraph, add "electrical endpoints, table II, all tests."

4.3.2, delete and substitute as follows:

"4.3.2 Surge screening. See MIL-STD-750, method 4066. V_{RWM} = 0, I_O = 0, I_{FSM} = 20 x I_O rated (see 1.3) at T_A = +25°C, t_p = 8.3 ms, 3 surges, duty factor = 1 percent maximum (half-sine or rectangular pulse of equivalent energy).

4.4.2, delete "table I" and substitute "table III".

page 6

4.4.2.1, subgroup 6, method column, delete "1031" and substitute "1032"; delete subgroup 2 test in its entirety and add the following:

"Subgroup	Method	Condition
1	2026	Not applicable."
2	4066	V_{RWM} = 0 V, I_{FSM} = (see 1.3) ten surges, 8.3 ms I_0 = I_0 rated at T_C = +75°C"

4.4.3, delete "table I" and substitute "table III"; delete subgroup 2 test in its entirety and add the following:

Subgroup	Method	Condition
2	2036	Test condition D2 (stud torque), t = 3 s; torque for 1N5597 & 1N5600 = 18 inch-pound; torque for 1N5603 = 36 inch-pound.

4.5.2, after Reverse recovery time (second occurrence), add "(MIL-STD-750, test method 4031)".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.

PAGE 7

4.5.4, delete "shall" and substitute "should" (three occurrences).

4.5.6, delete "Avalanche (bulk-breakdown) characteristic" and substitute "Avalanche (bulk-breakdown) characteristic (MIL-STD-750, test method 4023)".

PAGE 8

TABLE II, subgroup 3, conditions column, add "sample size : n = 45, c = 0", reverse recovery time, method column, add "4031".

PAGE 9

TABLE III, subgroup 4, after capacitance test, add the following new test:

"

Inspection	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Reverse recovery time	4031	(See 4.5.2) t_{rr} @ 0.5 A/1.0 A/ 0.25 A.			2	µs

"

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Air Force - 70
Navy - AS, CG, MC, OS

Preparing activity:
DLA - CC

(Project 5961-2397)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:34Z
Check the source to verify that this is the current version before use.