MILITARY STANDARD

RELIABILITY MODELING AND PREDICTION

TO ALL HOLDERS OF MIL-STD-756B:

1. THE FOLLOWING PAGES OF MIL-STD-756B HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

New Page	Date	Superseded Page	Date
v	31 August 1982	v	18 November 1981
vi	31 August 1982	vi	18 November 1981

2. MAKE THE FOLLOWING PEN AND INK CHANGES:

(a) Page 1001-4 add "(11)" to the right of $P_S = P_A P_B P_1 P_2$.

(b) Page 1001-6 add "(15)" to the right of $P_S = P_A P_B^2 P_C^2$.

(c) Page 1001-7 add "=" between P_A^2"="P_A^2, $P_B = P_B^2$, and $P_C^2 = P_C$.

(d) Page 1002-3 add "(2)" to the right of $P_S = B_1\overline{B}_2\overline{C}_1\overline{C}_2A + \ldots\ldots\ldots + B_1B_2C_1C_2A$.

(e) Page 1002-3 add "(3)" to the right of $P_S = B_1C_1 + \ldots\ldots\ldots + B_1\overline{B}_2\overline{C}_1C_2A$.

(f) Page 1003-4 add "(1)" to the right of $P_S = A[C_1 + C_1\overline{C}_2] + \ldots\ldots + B_1\overline{C}_1B_2C_2]$.

3. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

4. Holders of MIL-STD-756B will verify that page changes and additions indicated above have been entered. This notice page will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the military standard is completely revised or canceled.

Custodians:
Army - CR
Navy - AS
Air Force - 17

Preparing Activity:
NAVY - AS
(Project No. RELI-0038)

Review Activities:
Army - EA, AR
Navy - SH, OS

Users:
Army - AM
Navy - EC
National Security Agency - NS
Defense Mapping Agency - DMA

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:34Z
Check the source to verify that this is the current version before use.

Page

FIGURES

Figure 1.	Service use events in the logistic and operational cycles	8
102.1	Performance parameters, limits and failure criteria	102-3
2003.1	Failure-rate estimating chart for electronic analog function	2003-3
2003.2	Failure-rate estimation chart for digital electronics functions	2003-5
2003.3	Failure-rate estimation chart for mechanical devices	2003-7

TABLES

Table 1002-I	Truth table calculation for the mission reliability diagram	1002-2
1002-II	Reduction tabulation	1002-4
1003-I	Logic diagram examples	1003-2
1004-I	Success/Failure array for the mission reliability diagram	1004-3
1004-II	Success/Failure array for the mission reliability diagram	1004-5
200-I	Environmental symbol identification and description	200-5
2003-I	Weighting factors for different classes of electronic AEGs used in estimating analog complexity for Figure 2003.1	2003-2
2003-II	Weighting factors for estimating digital electronics AEG complexity for use with Figure 2003.2	2003-5
2003-III	Weighting factors for shipboard mechanical elements for use in conjunction with Figure 2003.3	2003-6

Source: https://assist.dla.mil -- Downloaded: 202610-23T22:34Z
Check the source to verify that this is the currentversion before use.

TASK SECTIONS

Task Section	100	Reliability modeling 100-1
	200	Reliability prediction 200-1

TASKS

Task	101	Basic reliability model. 101-1
	102	Mission reliability model. 102-1
	201	Basic reliability prediction 201-1
	202	Mission reliability prediction 202-1

METHODS

Method	1001	Conventional probability 1001-1
	1002	Boolean truth table. 1002-1
	1003	Logic diagram. 1003-1
	1004	Monte carlo simulation 1004-1
	2001	Similar item method. 2001-1
	2002	Similar circuit method 2002-1
	2003	Active element group method. 2003-1
	2004	Parts count method 2004-1
	2005	Parts stress analysis method 2005-1

APPENDIX A. APPLICATION AND TAILORING GUIDE

Paragraph		
10.		GENERAL. A-1
10.1		Scope. A-1
10.2		Tailoring requirements A-1
10.3		Duplication of effort. A-1
10.4		Limitations. A-1
20.		REFERENCED DOCUMENTS A-1
30.		DEFINITIONS. A-1
40.		GENERAL. A-2
40.1		Ordering data. A-2
40.2		Data item descriptions A-2
50.		APPLICATION CRITERIA A-2
50.1		General considerations A-2
50.1.1		Level of detail. A-2
50.1.2		Timing A-2
50.1.3		Intended use A-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:34Z
Check the source to verify that this is the current version before use.