INCH-POUND

MS19070C
w/AMENDMENT 1
07 August 2026
SUPERSEDING
MS19070C
01 December 2021

DETAIL SPECIFICATION SHEET

WASHER, KEY RETAINING, BALL AND ROLLER BEARING, REGULAR SERIES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-21338.




FIGURE 1. Washer.

Comments, suggestions, or questions on this document should be addressed to U.S. Army DEVCOM Ground Vehicle Systems Center, ATTN: Standardization, FCDD-GVS-SAT, MS #268, 6501 E. 11 Mile Road, Warren, MI 48397-5000 or emailed to usarmy.detroit.devcom-gvsc.mbx.standardization@army.mil. Since contact information can change, you may want to verify the currency of this address information using ASSIST at https://assist.dla.mil.

AMSC N/A FSC 5310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:20Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and dimensions.

DASH NO	Q THICKNESS		R BORE		∅E		∅B OVER TANGS MAX	KEY							TANGS		
								S WIDTH		X DEPTH		V PROJECTION		r	NO.	T WIDTH	
	Q	TOL ±	MAX	MIN	E	TOL+	MAX	MAX	MIN	MAX	MIN	V	TOL+	RAD		T	TOL±
00	.042	.004	.421	.406	.625	.015	.875	.120	.110	.030	.020	.062	.031	.016	9	.115	.005
01	.042	.004	.499	.484	.719	.015	1.016	.120	.110	.030	.020	.062	.031	.016	9	.115	.005
02	.042	.004	.616	.601	.812	.015	1.156	.120	.110	.030	.020	.062	.031	.016	11	.115	.005
03	.042	.004	.694	.679	.938	.015	1.328	.120	.110	.030	.020	.062	.031	.016	11	.115	.005
04	.042	.004	.816	.801	1.125	.015	1.531	.176	.156	.030	.020	.062	.031	.016	11	.156	.010
05	.050	.004	1.009	.989	1.281	.015	1.719	.176	.156	.030	.020	.094	.031	.016	13	.156	.010
06	.050	.004	1.213	1.193	1.500	.015	1.922	.176	.156	.050	.035	.094	.031	.031	13	.156	.010
065 *	.050	.004	1.353	1.333	1.812	.015	2.250	.176	.156	.050	.035	.094	.031	.031	15	.156	.010
07	.050	.004	1.416	1.396	1.812	.015	2.250	.176	.156	.050	.035	.094	.031	.031	15	.156	.010
08	.058	.005	1.603	1.583	2.000	.030	2.469	.290	.250	.050	.035	.094	.031	.031	15	.219	.015
09	.058	.005	1.817[1]	1.792	2.281	.030	2.734	.290	.250	.050	.035	.125	.031	.031	17	.219	.015
10	.058	.005	2.017	1.992	2.438	.030	2.922	.290	.250	.050	.035	.125	.031	.031	17	.219	.015
11	.063	.005	2.207	2.182	2.656	.030	3.109	.290	.250	.050	.035	.125	.031	.031	17	.219	.015
12	.063	.005	2.425	2.400	2.844	.030	3.344	.290	.250	.070	.055	.125	.031	.047	17	.219	.015
13	.063	.005	2.613	2.588	3.062	.030	3.578	.290	.250	.070	.055	.125	.031	.047	19	.219	.015
14	.063	.005	2.816	2.791	3.312	.030	3.828	.290	.250	.070	.055	.188	.062	.047	19	.219	.015
15	.072	.005	3.003	2.973	3.562	.030	4.109	.290	.250	.070	.055	.188	.062	.047	19	.313	.015
16	.072	.005	3.207	3.177	3.844	.030	4.375	.353	.313	.070	.055	.188	.062	.047	19	.313	.015
17	.072	.005	3.425	3.395	4.031	.030	4.625	.353	.313	.070	.055	.188	.062	.047	19	.313	.015
18	.094	.006	3.612	3.582	4.281	.045	4.938	.353	.313	.070	.055	.188	.062	.047	19	.313	.015
19	.094	.006	3.830	3.800	4.562	.045	5.219	.353	.313	.070	.055	.188	.062	.047	19	.313	.015
20	.094	.006	4.018	3.988	4.812	.045	5.500	.353	.313	.085	.065	.250	.062	.047	19	.313	.015
21	.094	.006	4.222	4.192	5.000	.045	5.703	.353	.313	.085	.065	.250	.062	.047	19	.375	.015
22	.125	.007	4.425	4.395	5.281	.045	6.062	.353	.313	.085	.065	.250	.062	.047	19	.375	.015
24	.125	.007	4.831	4.801	5.688	.045	6.469	.353	.313	.085	.065	.250	.062	.047	19	.375	.015
26	.125	.007	5.226	5.191	6.188	.045	7.031	.435	.375	.105	.085	.250	.062	.062	19	.500	.020
28	.125	.007	5.617	5.582	6.531	.045	7.438	.590	.500	.105	.085	.250	.062	.062	19	.500	.020
30	.156	.008	6.018	5.983	7.062	.060	8.062	.590	.500	.105	.085	.312	.062	.062	19	.500	.020
32	.156	.008	6.424	6.389	7.438	.060	8.438	.590	.500	.105	.085	.312	.062	.062	19	.500	.020
34	.156	.008	6.799	6.764	8.031	.060	9.062	.715	.625	.105	.085	.312	.062	.062	19	.500	.020
36	.156	.008	7.206	7.171	8.375	.060	9.438	.715	.625	.105	.085	.312	.062	.062	19	.625	.020
38	.156	.008	7.612	7.577	8.781	.060	9.875	.715	.625	.105	.085	.312	.062	.062	19	.625	.020
40	.156	.008	8.017	7.982	9.156	.060	10.312	.840	.750	.105	.085	.312	.062	.062	19	.625	.020

* Inactive for new design after 1987.

NOTES:

1. MATERIALS:

   (a) Carbon steel, AISI 1010 to 1035 (UNS G10100 to G10350), or 1116 to 1118 (UNS G11160 to G11180).

   (b) Corrosion resisting steel AISI 302, 303 or 304 (UNS S30200, S30300, or S30400).

2. TEMPER: Each washer shall be of such temper as to permit its being bent 180°, without fracture, either way of the grain, over a radius equal to one half the stock thickness.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:20Z
Check the source to verify that this is the current version before use.

3. PROTECTIVE COATING:

   (a) Carbon steel washers are available either zinc plated or unplated. Zinc plated washers shall be plated in accordance with ASTM B633, Class Fe/Zn 5, Type II. Cadmium plating in accordance with SAE AMS-QQ-P-416, Type II, Class 3 shall no longer be furnished.

   As a hexavalent chrome-free option, carbon steel washers shall be zinc plated in accordance with ASTM B633, Class Fe/Zn 5, Type V or VI, or zinc-nickel plated per MIL-PRF-32647, Type K20 or SAE AMS2461, Type II, Grade B, Class 3.

   (b) Corrosion resisting steel washers shall be passivated in accordance with SAE AMS2700, Method 1, Type 2.


   As a hexavalent chrome-free option, corrosion resistant steel washers shall be passivated in accordance with SAE AMS2700, Method 1, Type 6, Type 7 or Type 8, or Method 2.

4. DIMENSIONS: All dimensions are in inches. Tolerances: decimals ± 0.010, angles ±2° unless otherwise specified.

5. PART NUMBER: The MS19070 part number consists of the MS number (specification number), plus the dash number and the material number. The material numbers are:

   1 - unplated carbon steel
   2 - zinc plated carbon steel
   3 - passivated corrosion resisting steel
   4 - zinc-nickel plated carbon steel
   5 - zinc plated carbon steel (hex chrome-free)
   6 - passivated corrosion resisting steel (hex chrome-free)

   Example: MS19070 – 00 2 = Washer, Key Retaining, ØE = .625, zinc plated carbon steel.



5. NUTS: See MS19068 for applicable plain, round, retaining nuts. Applicable nuts should have size numbers corresponding to washer dash numbers: Example: washer size 00 shall be used with nut size number 00.

6. In the event of a conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.

7. Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:20Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AT
Navy - OS
Air Force – 11
DLA – GS

Preparing activity:
Army – AT

(Project 5310-2026-010)

Review activities:
Navy - AS, SA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:20Z
Check the source to verify that this is the current version before use.