MIL-B-43930B
30 June 1987
SUPERSEDING
MIL-B-43930A
29 March 1984

MILITARY SPECIFICATION

BEANS, GREEN, DEHYDRATED, COMPRESSED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers dehydrated, compressed green beans for use by the Department of Defense as an item of general use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-495	- Coatings, Exterior, for Tinned Food Cans
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-C-29	- Canned Subsistence Items, Packaging Of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8915

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497	- Labeling of Metal Cans for Subsistence Items
MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Regulations Governing Inspection and Certification of Processed Fruits and Vegetables, Processed Products Thereof, and Certain Other Processed Food Products

U.S. Standards for Snap Beans for Processing

U.S. Standards for Grades of Frozen Green Beans and Frozen Wax Beans

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the currentversion before use.

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Enzyme Inactivation Tests (Frozen Vegetables), Technical Inspection Procedures, Code 135-A-12

(Application for copies should be addressed to the U.S. Department of Agriculture, Agricultural Marketing Service, Washington, DC 20250.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:03Z
Check the source to verify that this is the current version before use.

NATIONAL ACADEMY OF SCIENCE

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

AMERICAN DAIRY PRODUCTS INSTITUTE

Standards for Grades of Dry Milks, Including Methods of Analysis, Bulletin 916

(Application for copies should be addressed to the American Dairy Products Institute, 130 North Franklin Street, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Traffic Department, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, 222 South Riverside Plaza, Suite 1120, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Bid sample approval. Unless otherwise specified (see 6.1), bid samples representative of the product the contractor proposes to furnish, must be submitted to the contracting officer prior to the bid opening. The bid sample shall consist of 12 hermetically sealed cans of at least 8 ounces of product preserved under nitrogen gas (less than 2.0 percent oxygen) or a vacuum of not less than 27 inches of mercury. The contracting officer will have the samples

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:03Z
Check the source to verify that this is the current version before use.

tested to determine whether the product has the desired subjective quality characteristics specified in 3.4. If the bid is accepted, the remaining samples shall be held at a temperature of 40°F or lower and shall be used as a reference standard for determining compliance of deliveries with subjective quality requirements. Additional samples may be withdrawn from accepted lots of materials for use as reference standards as deemed necessary by the inspection agency. The contracting officer's approval of the bid samples does not relieve the contractor from complying with all other requirements of the document not stipulated above.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Green beans. Green beans shall be either fresh or frozen.

3.2.1.1 Beans, green, fresh. The green beans shall be young bright, round type, U.S. No. 1, size 3 or 4 of the U.S. Standards for Snap Beans for Processing.

3.2.1.2 Beans, green, frozen. Frozen green beans shall be round type, cut style, U.S. Grade A of the U.S. Standards for Grades of Frozen Green Beans and Frozen Wax Beans. The frozen green beans shall be of the latest season's pack. Frozen beans may be used provided they have been blanched to peroxidase inactivation in accordance with 3.3.3.

3.2.2 Sodium sulfite or sodium acid sulfite. The sulfite(s) used shall comply with the Food Chemicals Codex.

3.2.3 Water. Water used for formulation, rehydration, blanching, and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation and processing.

3.3.1 Size grading. The beans shall be size graded so that not more than 3 percent are less than 18.5/64 inch thick and not more than 3 percent are more than 27/64 inch thick when measured at the shorter diameter of the bean transverse to the long axis at the thickest portion of the pod.

3.3.2 Cutting. The beans shall be cut transversely into 1 ± 1/8 inch segments.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:03Z
Check the source to verify that this is the currentversion before use.

3.3.3 Blanching. The beans shall be blanched in live steam or in hot water (usually 4 minutes in steam at atmospheric pressure or in hot water at not less than 200°F) until inactivation of the peroxidase enzyme, as determined in accordance with 4.3.2.2.

3.3.4 Sulfiting. The beans, prior to final dehydration, shall receive a sulfite treatment by such method as will ensure distribution of the sulfite throughout the product and a residual sulfur dioxide content in the dehydrated product within the limitations specified in 3.4.1. When frozen green beans are being sulfited, care should be exercised to ensure that they are completely thawed prior to the sulfite treatment. Contact of the wet beans with iron subsequent to the sulfiting operation shall be strictly avoided.

3.3.5 Freezing. The beans shall be individually quick frozen as expeditiously as possible and held in the frozen state until dehydrated.

3.3.6 Dehydration. Dehydration shall be by such method that the finished product complies with 3.4. The dehydration conditions shall be such that the product will not be scorched or otherwise damaged by heat or drying. (Note: A satisfactory product has been prepared by freeze-drying green beans to a moisture level of approximately 3 percent.)

3.3.7 Conditioning. The dehydrated green beans shall be conditioned by adding moisture sufficient to make them pliable so that they will not be crushed or ground under high pressure. (Note: Satisfactory conditioned green beans have been produced by adding moisture, either by applying wet live steam for approximately 5 minutes or spraying with water, to increase the weight by 8 to 14 percent and placing the sprayed green beans in a closed container and then heating, approximately 10 minutes at 150°F, in order to equilibrate the moisture in the green beans.)

3.3.8 Compression. The conditioned green beans shall be placed in a 3-12/16 inches ± 1/8 inch diameter mold and compressed into disks by applying 1000 to 2500 pounds per square inch pressure for a dwell time of 10 to 30 seconds depending upon the variety and maturity of the green beans. (Note: It has been found that a disk of approximately 1/2 inch in thickness gives good results. Disks thicker than 1/2 inch tend to relax too much and make it difficult to fill 15.5 ounces of product into the can.)

3.3.9 Redrying. The compressed green beans shall be redried within a minimum of time so that the finished product complies with 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:03Z
Check the source to verify that this is the current version before use.

3.4 Finished product requirements.

3.4.1 Compressed, dehydrated product. The compressed dehydrated product shall be in the form of disks 3-12/16 inches ± 1/8 inch in diameter, and 1/2 inch in thickness, ± 1/16 inch. Disk thickness may vary slightly depending on type of green beans, pressure, and dwell time used. The compressed product shall also comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. Product shall possess a bright uniform color typical of dehydrated green beans of similar variety.

e. The dehydrated product shall contain a sulfite level (calculated as sulfur dioxide) of 750 ± 250 parts per million (ppm), by weight.

f. The average net weight shall be not less than 15.5 ounces of product.

g. No individual can shall contain less than 15.2 ounces of product.

h. The moisture content of the compressed beans shall not exceed 3.0 percent.

3.4.2 Rehydrated product. The compressed green beans shall rehydrate to approximately their original physical form (1 inch transverse cuts) when 1.0 part of compressed green beans is added to 12.5 parts of 70° to 90°F water, by weight, stirred to break apart, brought to a boil, then turning off heat, covered, and allowed to stand for 10 minutes. The rehydrated product shall also comply with the following requirements:

a. The rehydrated product shall possess the color, odor, flavor, and appearance typical of cooked fresh green beans.

b. Bean texture shall be tender not mushy.

c. The product shall contain no harmful, extraneous vegetable matter.

d. Rehydrated green beans shall not have more than 5 percent, by weight, of unsnipped or loose bean stem ends; heat damaged units; units possessing tough inedible strings; or spotted, blemished, or otherwise damaged units.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the current version before use.

e. The rehydrated bean product shall not have more than 1 percent, by weight, of damage caused by pathological or insect injury.

f. Rehydrated green beans shall consist of not more than 10 percent, by weight, of the units less than 0.5 inch in length.

3.4.3 Palatability. The finished product shall be equal to or better than the approved bid sample in palatability and overall appearance.

3.5 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110: "Current Good Manufacturing Practice in Manufacturing, Processing or Holding of Human Foods," and the plant sanitation requirements of the appropriate Government inspection agency.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this document.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:03Z
Check the source to verify that this is the current version before use.

methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.3.1.2 Size. Fresh beans, after trimming and sorting, and frozen beans (as an incoming component) shall be examined to determine conformance to size requirements of 3.3.1. The sample for examination shall be a representative 200 beans. A "go-no-go" device shall be utilized to ascertain bean size. Any nonconformance shall be cause for rejection of the involved finished product.

4.3.1.3 Unfilled can inspection. Conformance of unfilled cans to the requirements specified in 5.1.1 shall be determined by examination of certificates of conformance or of other valid documents. Any nonconformance shall be cause for rejection of the can lot or of any involved product.

4.3.2 In-process inspection.

4.3.2.1 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, formulation, or of other valid documents shall be cause for rejection of the involved product.

4.3.2.2 In-process testing. As each production run is initiated, a 1-pound sample of the blanched green beans, prior to dehydration, shall be tested for peroxidase enzyme in accordance with 4.4.3. If the test result for peroxidase enzyme is negative, further testing for peroxidase activity need be accomplished only as often as there is a change in the amount or quality of the green beans or until procedures and controls applicable to the blanching process are changed. A test indicating active peroxidase enzymes shall be cause for rejection of that portion of the production from the time of previous negative result until such time as a negative test result is again attained.

4.3.3 Net weight examination. The cans of product shall be examined for net weight. The net weight of the filled and sealed cans shall be determined by weighing each sample unit on a suitable scale tared with a representative empty can and lid. The lot size shall be expressed in units of cans. The sample unit shall be one can of product. The inspection level shall be S-3. The results shall be reported to the nearest 0.1 ounce. If the average net weight is less than 15.5 ounces, or if the net weight of any individual can is less than 15.2 ounces, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the current version before use.

4.3.4 Product examination. The finished product shall be examined for the defects listed in table I. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for minor defects.

TABLE I. Product defects 1/ 2/

Category		Defect
Major	Minor	
		Compressed product
101		Product does not possess a bright uniform color typical of dehydrated green beans
	201	Diameter of product disk not as specified
		Rehydrated product 3/
102		Beans do not rehydrate to a form similar to their original cut physical form
	202	More than 10 percent of units, by weight, are under 0.5 inch in length
103		Presence of harmful, extraneous vegetative matter
104		More than 5 percent, by weight, of unsnipped or loose bean stem ends; heat damaged units; units possessing inedible tough strings; or spotted, blemished or otherwise damaged units
105		More than 1 percent, by weight, of units damaged by insect or pathological injury
106		The rehydrated product does not possess the color, odor, flavor, and appearance typical of cooked fresh green beans.
107		Texture is mushy or tough

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:03Z
Check the source to verify that this is the current version before use.

1/ The presence of foreign material (e.g., dirt, insect parts, hair, wood, paper, paint, glass, metal), foreign odor or flavor (e.g. burnt, scorched, moldy, musty, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved bid sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

3/ Rehydration of product shall be in accordance with 3.4.2.

4.3.5 Product testing.

4.3.5.1 Moisture and sulfur dioxide content testing. The finished product shall be tested as specified in 4.4.1 and 4.4.2 for conformance to the moisture and sulfur dioxide requirements in 3.4.1. The sample for testing shall be a 1-pound composite, derived from the number of cans indicated by inspection level S-2. The lot size shall be expressed in cans. Results for moisture shall be reported to the nearest 0.1 percent, and for sulfur dioxide to the nearest 10 ppm. A test failure for either moisture or sulfur dioxide content shall be cause for rejection of the lot.

4.3.5.2 Oxygen in headspace testing (when applicable). The filled and sealed cans shall be tested as specified in 4.4.4 for conformance to the oxygen in headspace requirement in 5.1.1. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.3.6 Can condition examination. Examination of filled and sealed cans shall be in accordance with U.S. Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.3.7 Leakage and vacuum (when applicable) examination. Examination for leakage and vacuum shall be in accordance with PPP-C-29 (see 5.1.1).

4.3.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the current version before use.

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Interior packing with fiberboard pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.
Container not snug-fitting.

Level C shipping containers shall be examined only for the marking, arrangement, and number of can defects specified above and for the closure method specified in 5.2.3.

4.3.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

4.4 Methods of inspection.

4.4.1 Moisture content test. Grind approximately 100 grams of a well mixed sample in a clean, dry Waring blender or similar mill for 1 minute. Weigh two samples, approximately 3.0 grams each of the sieved material, into tared, dry, aluminum weighing dishes (approximately 2 or 2 1/2 inches in diameter and 3/4 inch in depth) with tight-fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 6 hours at 70°C under a pressure of not more than 100 mm mercury. During drying, admit to the oven a slow current of air (approximately two bubbles per second) dried by passing through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the percent of moisture in the original samples.

4.4.2 Sulfur dioxide content test. Sulfur dioxide of the ground sample shall be determined in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Food Additives: Direct, Section: Chemical Preservatives, Method: Total Sulfurous Acid, Modified Monier-Williams.

4.4.3 Peroxidase activity test. The test to show adequate blanching shall be performed in accordance with the Peroxidase Test procedure described in "Enzyme Inactivation Tests (Frozen Vegetables) - Technical Inspection Procedures 135-A-12" of the USDA. Alternatively, a procedure using a mortar rather than a blender may be used as follows:

Procedure, using mortar:

1. Weigh representative 10 gram sample.
2. Place 30 mL of distilled water in graduated cylinder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:03Z
Check the source to verify that this is the current version before use.

3. Place sample in mortar with a little clean sand, add minimum amount of water from graduated cylinder to give best consistency for thorough maceration, and grind for 3 minutes. Add remainder of water from cylinder and mix.
4. Proceed as under "3" e through j inclusive, of the USDA Technical Inspection Procedures above.

NOTE: Because of the limits of mortar grinding when using mortar with 10 gram samples, special attention should be given to assuring a representative sample. Sample size can be increased to 20 or 30 grams with additional time given to grinding.

4.4.4 Oxygen content test. Oxygen content of headspace gas shall be determined in accordance with American Dairy Products Institute publication, Bulletin 916, Standards for Grades of Dry Milk; Including Methods of Analysis: Determination of Oxygen. The result of each determination shall be reported to the nearest 0.1 percent for each can. Alternatively, the headspace oxygen content may be determined by an Instrumentation Laboratories Oxygen Analyzer or equivalent instrument. Test results shall be reported to the nearest 0.1 percent for each can. The lot shall be rejected if any of the cans exceeds 2.0 percent oxygen. When referee testing is necessary, the American Dairy Products Institute method shall be followed.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (se 6.1).

5.1.1 Level A. A net weight of 15.5 ounces of product shall be unit packed into an open-top style, round metal can, size 401 by 411 with a soldered or welded side seam and compound-lined, double-seamed ends. The can shall be made throughout from not less than 0.25 pound per base box electrolytic tin plate. The base plate of the can shall be of sufficient temper to protect the product during shipment and storage. The entire inside area of the can shall be coated. The interior can coating shall not peel or blister when in contact with the product. The can shall be coated on the outside with a coating conforming to type I or when specified (see 6.1) type III of TT-C-495. The can shall be sealed under an atmosphere of nitrogen so that the oxygen content of the gases in the filled and sealed container shall not exceed 2.0 percent when tested in accordance with 4.3.5.2. The nitrogen packed cans shall be hermetically sealed and shall not show leakage when examined in accordance with 4.3.7. Alternatively, the cans may be hermetically sealed under a vacuum of not less than 27 inches of mercury when examined in accordance with procedures in PPP-C-29. When cans are closed under vacuum, the oxygen requirement is not applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with or without exterior commercial coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tin plate provided the cans have an exterior commercial coating.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Twenty-four cans of product, preserved as specified in 5.1, shall be packed in a fiberboard box, constructed and closed in accordance with style RSC, grade V2s of PPP-B-636. The cans shall be packed on end four in length, three in width, and two in depth within a snug-fitting shipping container. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each shipping container shall be reinforced with nonmetallic strapping or pressure-sensitive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of unit load specified (see 6.1). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Twenty-four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1 except the box shall be constructed of grade V3c, V3s,or V4s fiberboard.

5.2.3 Level C packing. Twenty-four cans of product, preserved as specified in 5.1, shall be packed in a fiberboard box on end four in length, three in width, and two in depth within a snug-fitting container in accordance with the National Motor Freight Classification or Uniform Freight Classification, as applicable, except the closure of the fiberboard boxes shall be in accordance with Method II as specified in the appendix of PPP-B-636.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the current version before use.

5.4 Labeling and marking.

5.4.1 Cans. Cans shall be labeled in accordance with MIL-L-1497 and shall include the following information:

Beans, Green, Dehydrated, Compressed
Net Weight 15.5 oz.
Name and address of contractor
Date packaged
Preserved with Sulfur Dioxide
GAS PACKAGED (if applicable)

Directions for Use

Beans, green, dehydrated, compressed	15.5 oz (1 No. 2-1/2 can)
Water (70° to 90°F)	1-1/2 gal
Salt	1-1/2 tbsp
Butter or margarine, melted (optional)	8 oz (1 cup)
Pepper	1 tsp

1. Add contents of can to salted, boiling water.
2. Return water to a boil. Boil moderately until beans separate, stirring occasionally.
3. Remove from heat. Let stand uncovered 10 minutes.
4. Drain. Combine 2 cups drained liquid with butter or margarine and pepper. Pour over beans.

Yield: 50 - 1/2 cup servings.

5.4.2 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When bid sample is not required (see 3.1).
c. Level of preservation and packing required (see 5.1 and 5.2).
d. When type III exterior coating of cans is required (see 5.1.1).
e. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the current version before use.

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 Subject term (key word) listing.

Beans, green
Compressed
Dehydrated foods
Disk form
Vegetables

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8915-0811

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-B-43930B	Beans, Green, Dehydrated, Compressed

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b Recommended Wording

c Reason/Rationale for Recommendation

6 REMARKS

7a NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:03Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Natick Research, Development, and
Engineering Center
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research, Development,
and Engineering Center
ATTN: STRNC-ES
Box 14A
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:03Z
Check the source to verify that this is the current version before use.