MILITARY SPECIFICATION

CLOTH, LAMINATED, AND CLOTH, COATED (CHLOROPRENE COATED)

This amendment forms a part of Military Specification MIL-C-43944, dated 30 March 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Add the following:

"2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein:

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 1424 - Tear Resistance of Woven Fabrics by Falling-Pendulum (Elmendorf) Apparatus

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)"

3.1, line 10, after the word "requirement.": Delete the period and add the following: ", except that all tests involving chemical warfare agents shall be conducted by the US Army Armament Research and Development Command (see 6.4)."

PAGE 5

Table I, Under characteristic for "Hydrostatic resistance p.s.i. minimum): 3/": Add the following new requirements in their respective columns:

"After cold cracking	300 2/	300 2/	300 2/	300 2/	____"

Table I, Characteristic for "Blocking at 200°F (both sides) Scale rating (maximum)": Delete requirement "No. 2" in all columns, and substitute "(2)".

Table I: Delete characteristic for "Cold crack at - 40°F" - Hydrostatic and Visual and all requirements.

FSC 8305

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:06Z
Check the source to verify that this is the current version before use.

PAGE 7

3.9.1, line 3, Delete "7500° Kelvin" and substitute: "7000 ± 500 kelvin".
line 4, Delete "2800° Kelvin" and substitute: "2850 ± 100 kelvin".

PAGE 11

Table IV, "Test method" column opposite "Tearing strength: Initial, After accelerated weathering and After oven aging",: Delete "5132 4/" and substitute "ASTM D 1424 5/".

Table IV, Under "Hydrostatic resistance": Add the following condition and test in respective columns:

"After cold cracking	3.6	5874 2/ and 4.3.2.1	-	1.0 p.s.i."

PAGE 12

Table IV, Characteristic for "After cold crack" under "Resistance to chemical warfare agents", in test method column: after "5874 2/, 4/": Add footnote "6/".

Footnote "2/" under Table IV: Delete 2nd sentence.

Add new footnote "5/" as follows:

"5/ See 2.2."

Add new footnote "6/" as follows:

"6/ The specimen shall be visibly examined under 5X magnification for crack or delamination of the polyvinyl flouride, and then forwarded to the US Army Armament Research and Development Command (see 6.4) for H and GB resistance."

PAGE 15

4.3.7.1, line 2, after "Method 204": Add "or T209".

4.3.7.2, line 2, after "Method 206": Add "or T208".

PAGE 16

5.2.1, line 1: Delete "packaged" and substitute "packed".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:06Z
Check the source to verify that this is the current version before use.

PAGE 17

6.4, line 4: Delete "Edgewood Arsenal." and substitute "US Army Armament Research and Development Command, Edgewood Area, ATTN: Chemical Test Branch, Building E5100, Aberdeen Proving Ground, MD 21010."

Custodians:

Army - GL
Navy - NU
Air Force - 20

Preparing activity:

Army - GL

Project No. 8305-0610

Review activities:

Army - EA, MD
Air Force - 99
DLA - CT

☆ U.S. GOVERNMENT PRINTING OFFICE: 1992—605-034/48018

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:06Z
Check the source to verify that this is the current version before use.