MIL-C-43949A(GL)
3 February 1978
SUPERSEDING
MIL-C-43949(GL)
29 June 1976

MILITARY SPECIFICATION

CLEANING AND SANITIZING MACHINES, SPRAYING HIGH PRESSURE, ELECTRIC

This specification is approved for use by the Natick Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers commercial types of cleaning and sanitizing machines.

1.2 Classification. The cleaning and sanitizing machines shall be of the following types, as specified (see 6.2):

Type I - Portable
Type II - Wall mounted

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall
PPP-T-60	-	Tape: Packaging, Waterproof

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:08Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, with Appropriate Test Methods

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip

* (Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

* (Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:08Z
Check the source to verify that this is the current version before use.

UNDERWRITERS LABORATORIES INC.

UL 73 - Motor Operated Appliances

(Application for copies should be addressed to Underwriters Laboratories Inc., 207 East Ohio St., Chicago, IL 60611: 333 Pfingsten Rd., Northbrook, IL 60062; 1285 Walt Whitman Road, Melville, Long Island, NY 11746; 1655 Scott Boulevard, Santa Clara, CA 95050; or 2602 Tampa East Blvd., Tampa, FL 33619.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical and using Federal agencies.)

3. REQUIREMENTS

* 3.1 Standard product. The cleaning and sanitizing machines furnished under this specification shall be the manufacturers current standard product except for changes necessary to comply with the requirements of this specification.

3.2 Codes and standards. The cleaning and sanitizing machines shall comply with the applicable requirements of UL 73.

3.2.1 Compliance. Prior to commencing production, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the machines furnished under this specification meet the applicable requirements of UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the machine has been tested and conforms to UL 73.

* 3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all provisions of this specification. When stainless steel is used, it shall conform to the chemical composition of type 301, 302, and 304 as specified in ASTM A 167 (see 6.4).

3.4 Design and construction.

* 3.4.1 Pump, water. The water pump shall be driven by a minimum of 1 horsepower, HP (746 W) motor. The motor shall be provided with a drip proof housing, sealed bearings and overload protection. The pump shall be constructed of materials that are resistant under operating conditions to the chemical supplies utilized in the cleaning and sanitizing process. The pump shall be provided with a pressure by pass valve or unloader to relieve pressure and recirculate

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:08Z
Check the source to verify that this is the current version before use.

the water when the pressure hose is turned off and the pump is still running. The type I, pump shall operate dry for 1 minute and the type II, pump shall operate dry for 5 minutes without seizing, and in addition, subsequent operation of both types of pumps with water at 140°F (60°C) shall show no evidence of leakage or loss of pressure (see 4.4.1).

* 3.4.2 Machine, cleaning and sanitizing. The dimensions and weights for the cleaning and sanitizing machines shall be as specified in Table I. The machines shall be a mounted unit and they shall consist of a water pump, motor, detergent tank or tanks, pressure hoses, spray gun, and nozzles. All operating controls shall be at the front or top of the unit for easy accessibility. The machines shall be equipped with one or two 5 gallon (19 l) tanks resistant to the type of detergent or detergents normally dispensed in cleaning dining facilities. The type I, machine shall be portable and mounted on a cart with two or more rubber mounted wheels. The type I, machine weighing more than 150 pounds (68 kg) shall be provided with ball bearing wheels to assure ease in mobility. The type II machine shall have provisions for wall mounting and for connection to one or more remote control stations when specified (see 6.2) and shall provide a means to precisely regulate the addition of chemical at a preset or adjustable rate. The machines shall conform to the following requirements during operation (see 4.4.2).

(a) Operate at not less than the capacities shown in Table II.
(b) No leakage, at the tanks, hoses, quick disconnect fittings, and couplings.
(c) The spray control gun shall completely shut off without leakage.
(d) The machine shall dispense chemicals at a rate prescribed by the manufacturers standard commercial practice.

TABLE I. Dimensions, and weights

	Type I (less handles)	Type II (less mounting brackets)
Width (maximum), overall	28 inches (711 mm)	20 inches (508 mm)
Depth (maximum), overall	25 inches (635 mm)	20 inches (508 mm)
Height (maximum), overall	38 inches (965 mm)	37 inches (940 mm)
Weight (maximum)	200 pounds (91 kg)	130 pounds (59 kg)

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:08Z
Check the source to verify that this is the current version before use.

TABLE II. Capacity requirements

Type	Pressure capacity psi (kPa)	Flow capacity gpm (ml/sec)
I	500 + 50 (3450 + 345)	3 + .15 (190 + 10)
II	800 + 60 (5520 + 410)	4 + .2 (250 + 13)

* 3.4.3 Hose, pressure high. The high pressure hose shall be reinforced, neoprene coated, and shall withstand a pressure of 2500 psi (17237 kPa) without leakage or bursting of the hose when tested as specified in 4.4.3. Unless otherwise specified (see 6.2), the high pressure hose shall be provided with quick disconnect fittings for the pressure outlet from the machine and means provided to attach extra lengths of hose as specified (see 6.2). Types I and II machines shall be furnished with a minimum of 25 feet (7.6 m) of high pressure discharge hose. The type II machine shall be provided with a reel type hanger.

* 3.4.4 Hose, water. The type I machine shall be provided with a minimum of 25 feet (7.6 m) of hose to connect the water source to the machine. The type II machine shall be provided with a minimum of 6 feet (1.8 m) of hose.

* 3.4.5 Gun, spray assembly. The spray gun assembly shall be provided with a stainless steel wand and an adjustable nozzle allowing the operator to change spray patterns from 0° to 65° without the use of tools. In the absence of an adjustable nozzle, four single nozzles covering the range of 0° to 65° may be provided. Spray gun assemblies for type II machines shall have means for changing from high to low pressure. Means shall be provided to turn machines on and off and change from soap or detergent to rinse at the machine. A finger tip controlled spray gun or wand with a squeeze trigger shall be furnished for the control of spray.

* 3.4.6 Electrical. Unless otherwise specified (see 6.2), the type I machine shall operate on, 60 hertz (hz) single phase power source and the type II machine shall operate on 115/220-volt, 60 (hz) single phase power source and with one or more remote control stations to operate on 24 volts. The type I machine shall be provided with no less than a 20 foot (6 m) electrical grounded cord with plug and cord hanger. The type II machine shall be provided with an 8 foot (2.4 m) electrical grounded cord with plug.

* 3.4.7 Contract data requirements. Contract data requirements shall be furnished as specified in 6.2 and 6.3.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:08Z
Check the source to verify that this is the current version before use.

conveyors shall be designed and equipped for electromag-

3.5 Marking. The cleaning and sanitizing machines shall be marked for identification in accordance with the manufacturers commercial practice and shall include manufacturers name, date of manufacturer, model number, and electrical characteristics.

3.6 Workmanship. The cleaning and sanitizing machines shall be free from defects such as fractures, splits, punctures, tears, dents, creases, deteriorations, or malfunctions. There shall be no sharp edges, slivers, burrs, projections, or other defects. The finish applied to the machines shall be continuous, smooth, adherent, without discoloration or foreign material imbedded, and contain no sags, runs, drips, creeps, laps, bubbles or streaks. No rust or tool marks shall show through the coatings. The surface of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall be sound, smooth, and free from porosity, cracks, incomplete fusion, and deformation of material. All scale and flux deposits shall be removed from the finished welds. Soldering shall be complete and adherent with all flux and residue removed and shall contain no pin holes. Threaded fasteners shall not be broken, stripped, fractured or loose. Rivets shall completely fill the holes, with full size heads neatly finished and in full contact with the surface of the riveted members and shall not be loose. Wiring shall not be cut, abraded, or have insulation stripped, and shall be joined at the terminals. Wiring shall have adequate slack to provide strain relief.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:08Z
Check the source to verify that this is the currentversion before use.

4.2.1.1 In-process inspection of material. The high pressure hose shall be tested in accordance with 4.4.3. The sample unit shall be extracted from a coil of hose used in fabricating hose assemblies for cleaning and sanitizing machines and shall be of sufficient length to suit pressure testing apparatus.

4.2.2 End item inspection. The inspection lot shall be all machines of one type offered for inspection at one time. The sample unit for this inspection shall be one completely fabricated machine.

4.2.2.1 Visual examination. The machine shall be examined for the defects in table III. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE III. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Type of finish not as specified or not in accordance with the manufacturer's standard commercial practice		X
	Area of no film	X	
	Not continuous, smooth and adherent	X	
	Discoloration or foreign material, embedded in finish		X
	Sags, runs, drips, creeps, laps, bubbles or streaks		X
	Rust or toolmarks showing through the coating	X	
Design and construction and workmanship (applicable to all components and assemblies)	Any component or part missing or not specified type or size	X	
	Part fractured, split, punctured, torn, dented, creased, deteriorated or malformed	X	
	Sharp burr or edge of sliver	X	
Nozzles	Not adjustable to four spray patterns or not provided with four spray nozzles	X	
Welding and brazing (where applicable)	Missing, incomplete, burn holes, fractured, or not fused	X	
	Slag inclusion, undercut, not smooth and uniform, or deposit of scale and flux not removed	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:08Z
Check the source to verify that this is the current version before use.

* TABLE III. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Soldering (where applicable)	Missing, incomplete or not adherent	X	
	Not clean (flux or residue not removed) or contains pinholes	X	
Bolts, nuts, screws, studs and other types of threaded fasteners	Broken, stripped, fractured or loose	X	
Rivets (when required)	Broken, not peened or insufficiently peened or loose	X	
Electrical wiring	Wiring cut, abraded, insulation stripped, not properly joined or loose at the terminals	X	
	Adequate slack not provided for wiring to relieve strain	X	
Marking	Missing, incomplete, not legible		X

4.2.2.2 Dimensional and weight examination. The machines shall be examined for compliance with dimensions and weight specified. Any dimensions and weight not within the specified requirements of 3.4.7 and 3.4.8 shall be a defect. The inspection level shall be S-4 with an AQL of 6.5 expressed in defects per hundred units.

4.2.3 End item testing. Each sample machine shall be tested as specified in 4.4.1 and 4.4.2, failure of this test shall be recorded as a defect. The inspection level shall be S-4 with an AQL of 4.0 per hundred units.

4.2.4 Packaging inspection. An examination shall be made to determine that the preservation-packaging, packing and marking comply with the section 5 requirements. Defects shall be as indicated in table III. The sample unit shall be one shipping container fully prepared for delivery except that it need not be closed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 20260-21T23:08Z
Check the source to verify that this is the current version before use.

TABLE IV. Packaging inspection

Examine	Defect
Marking (exterior and interior)	Omitted: incorrect: illegible: of improper size, location, sequence, or method of application.
Materials	Components missing, damaged, or not as specified.
Workmanship	Components not disassembled or drained and dried, as applicable. Openings not sealed as specified. Contents of interior packages or shipping containers not immobilized, cushioned, blocked, braced or waterproofed, when applicable. Bulged or distorted container.

4.2.4.1 Inspection of shipping containers. When shipping containers are required to be in accordance with PPP-B-601, PPP-B-621, PPP-B-636 or PPP-B-640, inspection for defects in the closure and strapping shall be in accordance with the appendix in the applicable container specification.

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.4 Tests.

* 4.4.1 Pump, water test. At an ambient temperature of 70 to 80°F (21 to 27°C), the water pump for types I and II machines shall be operated for conformance with the requirements in 3.4.1. Nonconformance shall constitute failure of the test.

* 4.4.2 Operational test. At an ambient of 70 to 80°F (21 to 27°C), the machine shall be connected to the applicable power source and 140°F (60°C) inlet water supply. The machine shall be operated for a period of 60 minutes to determine conformance with the capacity requirements in table II. In addition, the machine shall be operated to determine compliance with the leakage, spray gun shut off and dispensing chemical rate requirements in 3.4.2. Nonconformance shall constitute failure of the test.

* 4.4.3 Hose pressure high, test. At an ambient temperature of 70 to 80°F (21 to 27°C), the high pressure hose shall be statically tested at 2500 psi (17237 kPa) for 3 minutes, for conformance with the requirements in 3.4.3. Nonconformance shall constitute failure of the test.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:08Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. All detachable parts and components such as tanks, pressure hoses, spray gun, wand and nozzles, shall be removed from the machine and packaged as specified in 5.1.1.5. All connector hardware removed during the disassembly shall be placed in a cotton cloth draw-string bag and tied to the machine or disassembled part.

5.1.1.2 Draining. All pumps, tanks and hoses shall be drained and dried or flushed with 50/50 solution of ethylene glycol type commercial anti-freeze.

5.1.1.3 Sealing. All openings into the machine and electric components shall be sealed with tape conforming to type III or IV, class 1 of PPP-T-60, or shall be sealed with preformed plugs.

5.1.1.4 Line cord. The line cord shall be looped and securely tied in place.

5.1.1.5 Parts and components. Disassembled parts or components shall be packaged in a snug-fitting fiberboard box conforming to style optional, class weather-resistant of PPP-B-636. The contents of each box shall be cushioned, blocked or braced within the box to prevent movement while in-transit. Each box shall be securely closed in accordance with method IV as specified in the appendix of PPP-B-636.

5.1.2 Commercial. Each complete machine shall be preserved-packaged to afford adequate protection against physical damage during shipment from the contractor to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. One complete machine, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type, style A or B, grade A or B, type 2 load of PPP-B-601 or class 2, style 2 or 4, grade A or B, type 2 load of PPP-B-621. The contents of each shipping container shall be cushioned, blocked and braced, and waterproofed in accordance with the applicable requirements of MIL-STD-1186. When applicable, each machine with non-detached wheels shall be blocked to provide a minimum 1-inch (25.4 mm) clearance from the inside face of the container and the wheels. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:08Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. One complete machine, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style optional, type CF (variety DW), class domestic, grade 500 of PPP-B-636; class 1, style optional of PPP-B-640; domestic type, style A or B, grade B, type 2 load of PPP-B-601; or class 1, style 2 or 4, grade B, type 2 load of PPP-B-621. The contents of each shipping container shall be cushioned, blocked and braced in accordance with the applicable requirements of MIL-STD-1186. When applicable, each machine, with non-detached wheels, shall be blocked to provide a minimum 1-inch (25.4 mm) clearance from the inside face of the container and the wheels. Each shipping container shall be closed in accordance with the appendix of the applicable container specification.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the fiberboard shipping container specified in 5.2.2 shall be a grade VIIc or class 2 fiberboard box fabricated in accordance with PPP-B-636 or PPP-B-640, respectively, and closed in accordance with the appendix of the applicable container specifiation.

5.2.3 Commercial. Each complete machine, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall comply with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The cleaning and sanitizing machines are intended to be used to remove dirt and other foreign matter from baskets, carts, shelving, racks, and food service equipment used in Army Kitchen facilities and Commissary Stores.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type machine required (see 1.2).
(c) When one or more remote control stations are required (see 3.4.2).
(d) When high pressure hose quick disconnects are not required (see 3.4.3).
(e) Specify additional lengths of high pressure hose when required (see 3.4.3).
(f) Electrical characteristics if other than specified (see 3.4.8).
(g) Contract data requirements (see 3.4.10 and 6.3).
(h) Selection of the applicable levels of preservation-packaging and packing (see 5.1 and 5.2).
(i) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:08Z
Check the source to verify that this is the current version before use.

* 6.3 Contract data requirements. Any contract data items to be delivered under any contract covered by this specification shall be specifically called for in the contract in accordance with the applicable regulation of the procurement agency (see 3.4.10 and 6.2).

* 6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification (see 3.3).

* 6.5 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling.

* 6.6 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Review activity:

DLA - GS

Preparing activity:

Army - GL

Project No. 7320-A653

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-C-43949A - CLEANING & SANITIZING MACHINES, SPRAYING HIGH PRESSURE, ELECTRIC

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:08Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T23:08Z
Check the source to verify that this is the currentversion before use.