MIL-D-43953
AMENDMENT-1
9 June 1977

MILITARY SPECIFICATION

DISPENSER, BUTTER, SELF-CONTAINED, EUTECTIC

This amendment forms a part of Military Specification MIL-D-43953, dated 9 September 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.4, line 5, after "chips". Add "a maximum of 2 inches (50.8 mm)".

3.4.2 Delete and substitute:

"3.4.2 Eutectic cooling units. Each eutectic cooling unit shall be capable of maintaining butter temperature between 48°F (8.8°C) to 60°F (15.5°C) in a 70°F (21°C) to 80°F (26.6°C) ambient temperature when tested as specified in 4.4.1. Each butter dispenser shall be furnished with two eutectic cooling units."

PAGE 7

4.4.1 Delete and substitute:

"4.4.1 Performance. The test shall be performed in an ambient temperature range of 70°F (21°C) to 80°F (26.6°C). The eutectic cooling unit shall be refrigerated at 0°F (-18°C) + 2°F (1°C) for 8 hours. The prepackaged butter trays shall be refrigerated at 38°F (3°C) + 2°F (1°C). Load the dispenser with refrigerated butter trays and eutectic cooling unit. At the end of 4 hours the internal temperature of the butter pat located at the approximate center of the butter tray length of each butter tray shall be recorded to determine compliance with 3.4.2. The failure of any butter temperature to meet specified requirements shall constitute failure of this test.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Army - GL

Project No. 7320-0661

Review activity:

Army - MD

User activity:

Navy - MC, SA

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 202640-21T23:09Z
Check the source to verify that this is the current version before use.