MIL-P-43940A
31 December 1985
SUPERSEDING
MIL-P-43940
23 February 1976

MILITARY SPECIFICATION

*PANS, STEAM TABLE, RECTANGULAR AND INSETS, STEAM TABLE, ROUND

This specification is approved for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers rectangular pans and round insets to be used mainly with steam tables.

* 1.2 Classification. The pans and insets shall be of the following styles and sizes as specified (see 6.2).

Style I	-	Pans, rectangular, 12 inch by 20 inch series
Size 1	-	Soup tureen - 32 quarts capacity
Size 2	-	Full size - 7-1/2 quarts
Size 3		
Model A	-	Full size - 15 quarts (without perforations)
Size 4		
Model B	-	Full size - 19-3/4 quarts (with perforations)
Size 5	-	Half size - 4-1/8 quarts
Size 6	-	Half size - 6-3/4 quarts
Size 7	-	Half size - 10-3/4 quarts
Size 8	-	Half size, - long - 4 quarts
Size 9	-	Half size, long - 6-1/2 quarts

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:05Z
Check the source to verify that this is the current version before use.

Style I - Pans, rectangular, 12 inch by 20 inch series -continued

Size 10	-	Half size, long - 9-1/2 quarts
Size 11	-	One-third size - 2-3/4 quarts
Size 12	-	One-third size - 4-1/4 quarts
Size 13	-	One-third size - 6-1/2 quarts
Size 14	-	One-quarter size - 2 quarts
Size 15	-	One-quarter size - 3-1/4 quarts
Size 16	-	One-quarter size - 4-3/4 quarts
Size 17	-	One-sixth size - 1-1/4 quarts
Size 18	-	One-sixth size - 2 quarts
Size 19	-	One-sixth size - 2-5/8 quarts
Size 20	-	One-ninth size - 3/4 quarts
Size 21	-	One-ninth size - 1-1/4 quarts

Style II - Inset, round

Size 22 - 6-1/2 inch diameter - 4-1/8 quarts capacity

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing
UU-P-268	-	Paper, Kraft, Wrapping

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:05Z
Check the source to verify that this is the current version before use.

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIAL (ASTM)

A 167 - Corrosion-Resisting Chromium-Nickel Steel, Plate, Sheet and Strip

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

No. C-2 - Basic Criteria for Equipment in Handling of Food

(Application for copies should be addressed to the National Sanitation Foundation, P.O. Box 1468, Ann Arbor, MI 48106.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Standard product. The pans and insets delivered shall be the manufacturer's commercial standard product, except for any changes necessary to comply with the requirements of this document.

* 3.2 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer for his standard commercial steam tables, provided the completed item complies with all provisions of this document. Recycled materials may be used (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 20261O-21T23:05Z
Check the source to verify that this is the current version before use.

3.2.1 Stainless steel sheets and strips. Stainless steel sheets and strips shall conform to type 300 series of ASTM A 167.

3.3 Design and construction.

* 3.3.1 Pans. The food pans shall be fabricated of stainless steel specified in 3.2.1. The length and width of the food pans shall be such that one full size pan, two 1/2 size pans, three 1/3 size pans, four 1/4 size pans, six 1/6 size pans, nine 1/9 size pans, or other various combinations of pans will completely fill an opening that is 11-7/8 inches (plus 1/8 inch minus 0 inch) wide by 19-7/8 inches (plus 1/8 inch minus 0 inch) long. The pans shall be seamless drawn and shall conform to table I. The top of the pans shall be provided with a horizontal flange or semirolled edge. The flange widths shall be such that the pan or combinations of various size pans shall completely cover the openings. The edge of the flange shall be turned down, and the four corners shall be square or finished with a maximum 3/8-inch radius. The sides of the pans shall be tapered to permit nesting of same size pans. The perforated pans shall have bottom, sides, and ends perforated.

TABLE I. Food pans and tureen sizes, capacities, and metal thickness

Pan size or inset size	Outside, depth (+0, -1/8 in.)	Capacity (± 10 percent) quarts	Starting metal thickness (nominal)	Minimum metal thickness after forming
Tureen	8	32	0.050	0.025
Full size	2-1/2	7-1/2	0.035	0.020
Full size	4-1/8	15	0.035	0.020
Full size	6	19-3/4	0.035	0.020
Half size	2-1/2	4-1/8	0.035	0.020
Half size	4	6-3/4	0.035	0.020
Half size	6	10-3/4	0.035	0.020
Half size, long	2-1/2	4	0.035	0.020
Half size, long	4	6-1/2	0.035	0.020
Half size, long	6	9-1/2	0.035	0.018
One-third size	2-1/2	2-3/4	0.032	0.020
One-third size	4	4-1/4	0.032	0.020
One-third size	6	6-1/2	0.032	0.016
One-quarter size	2-1/2	2	0.035	0.020
One-quarter size	4	3-1/4	0.032	0.016

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:05Z
Check the source to verify that this is the current version before use.

TABLE I. Food pans and tureen sizes, capacities, and metal thickness - Continued

Pan size or inset size	Outside, depth (+0, -1/8 in.)	Capacity (± 10 percent) quarts	Starting metal thickness (nominal)	Minimum metal thickness after forming
One-quarter size	6	4 3/4	0.032	0.014
One-sixth size	2 1/2	1 1/4	0.032	0.020
One-sixth size	4	2	0.032	0.016
One-sixth size	6	2 5/8	0.032	0.014
One-ninth size	2 1/2	3/4	0.035	0.020
One-ninth size	4	1 1/4	0.0375	0.016
6 1/2" dia. inset	-	4 1/8	0.032	0.020

3.3.1.1 Pan covers. When specified (see 6.2), the food pans shall be provided with a flat, one piece overlapping cover of stainless steel specified in 3.2.1 of the same thickness as the pan. The cover shall be provided with a flush, flat strap type handle located at the top center of the cover. The cover shall have a lip to fit the flange on the pan. When specified (see 6.2), the covers shall come slotted for utensil handle.

3.3.2 Soup tureens. Soup tureens shall fit the same size rectangular opening as specified in 3.3.1 for the full size food pans. The sides shall be formed with a shoulder to support the tureen on the table top. The shoulder shall be located so as to limit the depth of the tureen below the shoulder to maximum 6 inches.

3.3.2.1 Tureen cover. Each soup tureen shall be provided with a one piece, slotted, flat cover identical to pan covers specified in 3.3.1.1.

3.3.3 Round inset. The inset shall be fabricated of stainless steel specified in 3.2.1, be seamless drawn, and conform to table I. The sides shall be formed with a shoulder to support the inset on the table top. The diameter of inset below the shoulder shall be such as to fit into a 6 1/2-inch diameter opening.

Source: https://assist.dla.mil -- Downloaded: 20261O-21T23:05Z
Check the source to verify that this is the currentversion before use.

3.3.3.1 Cover, round. Each inset shall be provided with a slotted, flat cover with flush, flat strap type handle, all of stainless steel specified in 3.2.1. The slot shall be for a utensil handle.

3.3.4 Adapter bars. To support fourth, sixth, or ninth size pans, when specified (see 6.2), the bars shall be made from 18 gage, minimum, steel specified in 3.2.1 and shall be of length to fit across 12-inch openings.

* 3.4 Marking for identification. Marking of pans shall include pan capacity, manufacturer's name or trade name, contract number, and National Stock Number.

3.5 Finish. Pans and covers shall be free from scratches, rough die or grind marks, pits, scale, sharp burrs, slivers, and splinters. Food contact surfaces shall be smooth and easily cleanable conforming to sanitary requirements of NSF Standard C-2 for Basic Criteria for Equipment in Handling of Food.

3.6 Workmanship. The finished pans and covers shall be clean, well made, and free from defects affecting appearance, durability, and serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents, unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall consist of all pans of one style and size offered for inspection at one time. The sample unit shall be one complete pan.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:05Z
Check the source to verify that this is the current version before use.

* 4.2.2.1 Visual examination. The pans shall be examined for defects in table II. The inspection level shall be level II, and the acceptable quality level (AQL) shall be 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of visual defects

Examine	Defect	Classification	
		Major	Minor
Standard product	Item not in accordance with manufacturer's standard product	101	
Finish	Corrosion-resisting steel finish not as specified		201
	Sharp burr, sliver or splinter	102	
	Any scratch or grind mark which impedes the progress of a finger-nail when drawn across the mark	103	
Construction and workmanship general	Fractured, dented, missing perforations (Model B)	104	
Rectangular pan	Sides not tapered	105	
	Lip flange uneven (more than 1/16 inch)	106	
	Not seamless	107	
	Edge not properly flanged		202
	Bulge at sides or bottom more than 1/8 inch		203
	Corners not rounded		204
Pan cover	Not flat		205
	Lip does not overlap pan flange	108	
	Flat handle not in center or not flush		206
	Not slotted for utensil handle when specified	109	

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:05Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Tureen	Top edge of body not properly flanged		207
	Bulge at side		208
	Cover does not fit flush (flange uneven more than 1/16 inch)	110	
Round inset	Not seamless	111	
	Does not have support shoulder	112	
Inset cover	Not flat	113	
	Lip does not overlap flange	114	
	Flat handle not in center or not flush		209
	Not slotted for utensil handle	115	
Marking	Missing, illegible		210

4.2.2.2 Dimensional examination. The pans shall be examined for specified dimensions and capacities. Any dimensions or pan capacity not within the specified tolerance shall be a defect. The inspection level shall be S-2, and the AQL shall be 4.0, expressed in terms of defects per hundred units.

4.2.3 Packaging inspection. An inspection shall be made to determine that preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with table III. The lot size shall be the number of shipping containers in the inspection lot. The sample unit shall be one shipping container fully packaged. Inspection level shall be S-2, and the AQL shall be 2.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:05Z
Check the source to verify that this is the current version before use.

TABLE III. Packaging inspection

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, or of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete closure of interior packages. Bulged or distorted containers

* 4.2.4 Palletization inspection. An inspection shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with table IV. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1, and the AQL shall be 6.5, expressed in terms of defects per hundred units.

TABLE IV. Palletization inspection

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted, incorrect, illegible, or of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:05Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Pans with covers. Each pan, with cover in place, shall be unit packed in a snug-fitting fiberboard box conforming to style RSC, type CF (variety SW) class domestic, grade 200 of PPP-B-636. The contents of each box shall be cushioned to prevent movement while in transit. Each box shall be securely closed with 2-inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45.

5.1.1.2 Pans without covers. Each pan shall be completely form wrapped in 30-pound basis weight kraft paper conforming to type I, grade B of UU-P-268. Alternately, each pan shall be completely enclosed in a polyethylene bag with a minimum thickness of 0.001 inch. A quantity, as determined by the contractor, of the wrapped pans of one description only shall be compactly nested and then unit packed as specified in 5.1.1.1.

5.1.1.3 Tureens and insets. Each tureen or inset shall be unit packed as specified in 5.1.1.1.

* 5.1.1.4 Adapter bars. Each adapter bar shall be completely wrapped with the kraft paper specified in 5.1.1.2. The wrap shall be secured with the tape specified in 5.1.1.1. Two wrapped adapter bars shall be unit packed as specified in 5.1.1.1.

* 5.1.2 Commercial . Pans with or without covers, tureens, insets, and adapter bars shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Pans with or without covers, tureens, insets, and adapter bars of one description only, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, grade V2s of PPP-B-636. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636. The weight of contents of each fiberboard container shall not exceed 65 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:05Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Pans with or without covers, tureens, insets, and adapter bars of one description only, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636. The weight of contents of each fiberboard container shall not exceed 65 pounds.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the fiberboard shipping container shall be grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

* 5.2.3 Commercial packing. Pans with or without covers, tureens, insets, and adapter bars, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), pans, packed as specified in 5.2, shall be palletized in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size that does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. These pans are intended for use in food storage and serving in connection with steam tables (S-S-710).

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Style, size, and model of pan required (see 1.2).
c. When covers are required (see 3.3.1.1).
d. When covers with slots are required (see 3.3.1.1).
e. When adapter bars are required (see 3.3.4).
f. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:05Z
Check the source to verify that this is the current version before use.

g. When weather-resistant grade fiberboard shipping containers are required for level B shipment (see 5.2.2.1).
h. When palletization is required (see 5.3).

* 6.3 Recycled material. The contractor is encouraged to use recycled material when practical, provided that it meets the requirements of this document (see 3.2).

6.4 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD
Air Force - 84
DLA - GS

User activities:

Navy - SH, MC

Preparing activity:

Army - GL

Project No. 7330-0565

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:05Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 202610-21T23:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-43940A	Pans, Steam Table, Rectangular and Insets, Steam Table, Round

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-10-21T23:05Z
Check the source to verify that this is the current version before use.