MIL-U-43937A(GL)
28 December 1979
SUPERSEDING
MIL-U-43937(GL)
24 December 1975

MILITARY SPECIFICATION

UNIFORM WOMAN'S: JUNIOR R.O.T.C.

This specification is approved for use by Natick Research and Development Command, Department of the Army, and is available for use by Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a plaid, polyester and rayon uniform consisting of skirt, vest and tie.

1.2 Classification. The uniform shall be of one type in the following sizes (see 6.2):

Schedule of sizes

Vest	6	8	10	12	14	16	18	20							
Skirt															
Waist	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
Length															
	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15
	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
	17	17	17	17	17	17	17	17	17	17	17	17	17	17	17
	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18
	19	19	19	19	19	19	19	19	19	19	19	19	19	19	19
	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
	21	21	21	21	21	21	21	21	21	21	21	21	21	21	21
	22	22	22	22	22	22	22	22	22	22	22	22	22	22	22
	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
Tie	One size														

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8410

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

V-T-280	-	Thread, Cotton Gimp, Buttonhole
V-B-871	-	Button, Sewing Hole, and Button, Staple (Plastic)
V-F-106	-	Fasteners, Slide, Interlocking
DDD-B-1199	-	Binding, Textile, Cotton, Bias-Cut
DDD-L-20	-	Label; for Clothing, Equipage and Tentage, (General Use)

MILITARY

MIL-B-3461	-	Buttons, Insignia, Metal, Uniform and Cap
MIL-F-10884	-	Fasteners, Snap
MIL-C-41820	-	Cloth, Gabardine, Polyester and Rayon
MIL-C-43718	-	Cloth, Twill, Polyester; Polyester and Cotton; Polyester and Rayon
MIL-T-43548	-	Thread, Polyester, Cotton-Covered
MIL-C-43935	-	Cloth, Plain Weave, Polyester/Rayon, Plaid

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

TECHNICAL MANUAL OF THE AMERICAN ASSOCIATION OF TEXTILE CHEMISTS AND COLORISTS

(Application for copies of the AATCC Manual should be addressed to the American Association of Textile Chemists and Colorists, Research Triangle Park, P.O. Box 12215, Durham, NC 27709.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed to technical groups and using Federal Agencies.)

3. REQUIREMENTS

3.1 Guide sample. A sample, when furnished, is solely for guidance and information to the contractor (see 6.3). Variation from this specification may appear in the sample, in which case this specification shall govern.

3.2 Materials.

3.2.1 Basic material. The basic material for the uniform shall be a plain weave polyester/rayon plaid cloth conforming to MIL-C-43935.

3.2.2 Interlining. The interlining material for the vest pockets and tie shall be polyester, polyester and cotton or polyester and rayon cloth conforming to class 1 of MIL-C-43718. The colors shall be Black Shade No. 3212 or Navy Blue to match the basic material.

3.2.3 Shoulder loops. The material for shoulder loops shall be polyester and rayon, gabardine cloth conforming to type III of MIL-C-41820 and shall be Black Shade No. 3212.

3.2.4 Thread. The thread shall be polyester core, cotton-covered ticket numbers 50, 2 or 3 ply and 70, 2 ply conforming to MIL-T-43548. The color shall be Navy Blue AT, C.A. 66060 for all stitches, except Black AA, C.A. 66043 for shoulder loop stitching.

3.2.4.1 Colorfastness. The dyed thread shall show colorfastness to laundering, equal to or better than the standard sample. When no standard sample is available, the dyed thread shall show "good" colorfastness to laundering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

3.2.4.2 Gimp. The gimp for reinforcing the buttonholes shall be cotton, type I, or II, size 8 conforming to V-T-280.

3.2.5 Binding. The material for the bias-cut cotton binding shall conform to type I, class 2 of DDD-B-1199. The color of the binding shall be Navy Blue or black to match the basic material. (As an alternate, the bias-cut binding may be cut from the interlining, if it is Navy Blue or Black Shade No. 3212 in color.)

3.2.6 Rubberized waistband tape. The rubberized waistband tape shall be a woven cotton or polyester tape construction with an exposed rubber track woven thereon. The tape shall be one inch wide and shall be a natural shade. There shall be three rows of exposed (uncovered) rubber woven or raised above the surface of the cotton or polyester tape. Each row shall contain four strands of rubber woven adjacent to each other. The rubber shall be compounded to resist dry cleaning and pressing (see 6.4).

3.2.7 Slide fastener. The slide fastener shall conform to either 3.2.7.1 or 3.2.7.2.

3.2.7.1 Slide fastener, plastic monofilament (coil type). The slide fastener shall be manufactured of polyester or nylon with an automatic lock and shall be equal to commercial size No. 2. The tape shall have a minimum width (one side) of 7/16 to 1/2 inch. The complete slide fastener shall not shrink more than 2 percent when tested as specified in 4.2.1. The length of the slide fastener shall be 7 inches long for all sizes (see 4.2.1).

3.2.7.2 Slide fastener, metal. The slide fastener shall be type I, style 3, brass, short tab pull, size LS, enamelled Navy Blue, conforming to V-F-106. The length of the slide fastener shall be 7 inches for all sizes.

3.2.7.3 Slide fastener, tape. The tape for the slide fasteners shall be a blend of nylon and cotton or polyester and cotton. The tape shall be dyed Navy Blue, Shade 2, Cable No. 66526.

* 3.2.8 Snap fastener, tie. The snap fastener for the tie shall be style 3 pronged-ring-head type, size 17 or 18 line, finish 3 conforming to MIL-F-10884, but with a white pearlized insert within the pronged ring (see 6.6).

3.2.9 Buttons.

3.2.9.1 Buttons, vest. The buttons shall be insignia metal, uniform, 30-line, hopper back conforming to type I, style 2, class D of MIL-B-3461.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

3.2.9.2 Button, skirt. The button for the skirt shall be type II, class D, 30-line, style 20 or 21 without studs of V-B-871. The button shall be Blue Shade BU, Cable No. 62002.

3.2.10 Chain, (for vest buttons). The chain for the vest shall be curb chain, steel links, 10 links per inch, 0.035 inch diameter wire, 0.062 inch I.D., 24 K gold plated, with brass ring, 0.040 inch diameter wire, 3/16 inch I.D., 6-5/8 inches overall length of chain (see 6.5).

3.2.11 Buckle. The buckle for the tie shall be steel, nickel finish, belt, slide, 3/4 inch (see 6.7).

3.2.12 Loop. The loop for the tie shall be steel wire, nickel finish, 7/8 inch (see 6.7.1).

3.2.13 Labels. All labels shall conform to type I of DDD-L-20. The skirt and vest shall have an identification, a size and an instruction label. The tie shall have an identification label only. The fastness to laundering requirements of DDD-L-20 shall apply.

3.2.13.1 Identification label. The identification label for the skirt and vest shall be class 1. The identification label for the tie shall be class 4, except that the requirements for size shall not apply.

3.2.13.2 Size label. The size label shall be class 2.

3.2.13.3 Instruction label. The instruction label shall be class 3 and shall contain the following information:

MACHINE WASH
Use warm water and detergent
(DO NOT USE chlorine bleach or starch)
Drip dry or tumble dry at medium heat
Remove immediately
Steam press, if required, at synthetic (Medium heat)

3.2.13.4 Combination label. A combination identification (class 1) and instruction (class 3) label may be used. The combination label shall conform to the requirements of the type I, class 3 label.

3.3 Design. The vest is sleeveless with a v-neck front, gold buttons with chain closure, front patch pockets, shoulder loops and front and back darts for shaping. The skirt has four topstitched inverted box-pleats (2 in front and 2 in back), a sewn-on and topstitched waistband lined with a rubberized tape for holding blouse tails secure, and a left side slide fastener closure. The tie is two piece, adjustable for size with a snap front closure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

3.4 Patterns. Standard patterns will be supplied by the Government. They provide a seam allowance of 1/4 inch for tie and vest pocket construction and for application of bias tape to vest armhole, 3/4 inch for skirt seam and slide fastener application, 1/4 inch for safety-stitch for right skirt side seam (as worn) and vest shoulder seam, 1/2 inch for waistband application and vest side seams, and 3/8 inch for waistband ends and facing to vest application. The standard patterns shall not be altered in any way and are to be used only as a guide for cutting the contractor's working patterns. The working patterns shall be identical to the standard patterns.

* 3.4.1 List of pattern parts. The uniform shall be cut from the materials specified in accordance with the number of parts indicated in table I.

TABLE I. List of pattern parts.

Material		Pattern nomenclature	Cut parts
Polyester/rayon plaid	Vest	Front	2
		Back	1
		Pocket	2
		Front facing	2
		Back facing	1
	Skirt	Front	1
		Back	1
		Placket	1
		Waistband	1
	Tie	Right half	1
		Left half	1
Polyester/rayon gabardine (black)	Vest	Shoulder loop	2
Polyester/rayon	Vest	Pocket interfacing	2 1/
Polyester/cotton, or polyester	Tie	Right interfacing	1
		Left interfacing	1

1/ The pocket interfacing may be cut from the polyester/rayon plaid cloth.

3.5 Construction.

3.5.1 Stitches, seams and stitching. Stitch, seam and stitching types, as specified in table II, shall conform to FED-STD-751. Where two or more seam or stitch types are given for the same part of an operation, any one of them may be used. When stitch type 401 is used, the looper (under thread) shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

be on the inside of the uniform. Seam allowances shall be maintained with seams sewn so that raw edges, run offs, twists, pleats or puckers will not result. All seams shall start and finish evenly. Thread tension shall be maintained so that no tight or loose tension will result. In the safety-stitch construction the width of the overedge stitch shall be 3/16 to 1/4 inch.

3.5.2 Stitches per inch. The minimum and maximum number of stitches per inch shall be as specified in table II.

3.5.3 Thread breaks and ends of seams. Ends of all seams and stitchings (except darts) shall be backtacked not less than 1/4 inch unless otherwise specified. The ends of a continuous line of stitching shall be overlapped not less than 1/2 inch except on labels where the overlap shall be not less than 3 stitches. Thread breaks shall be secured by stitching back of the break not less than 1/2 inch. Skipped stitches or thread breaks on 401 stitch type may be repaired using 301 stitch type. The thread ends of darts shall be trimmed to a length 1/2 to 3/4 inch.

3.5.4 Buttonhole. The buttonhole shall be cut first or cut after, eyelet end taper bar or straight cut, barred at both ends, with a finished cut length of 3/4 to 7/8 inch. The buttonhole shall be clean cut and correctly positioned with the stitching securely caught in the fabric. When a purl-type stitch is used, the purling shall be on the outside of the waistband.

3.5.5 Bartacks. Bartacks shall measure 1/2 to 5/8 inch in length.

3.6 Pressing. All pressing specified in table II shall be done with a heated pressing iron or machine.

3.7 Manufacturing operations requirements. The uniform shall be manufactured in accordance with the operations requirements specified in table II. The contractor is not required to follow the exact sequence of operations. Any additional basting or holding stitching used to facilitate manufacture is permissible provided the thread is removed or does not show on the finished uniform.

3.7.1 Marking. The cut parts shall be marked, ticketed or bundled to insure a uniform shade and size throughout the uniform. Any method of marking may be used except:

(a) Corrosive metal devices
(b) Sew-on type tickets
(c) Adhesive type tickets, which leave traces of paper or adhesive on the material upon removal of the tickets

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

TABLE II

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
1.	Cut uniform. a. Cut uniform in strict accordance with patterns furnished which show directional lines, size, placement of pockets, darts and notches for proper assembly of all parts. The red stripe runs in the warp direction. The horizontal stripes shall match at front vest closure and side seams of skirt. Fronts may be arranged on lay so that left and right fronts are abutted. b. Cut basic material parts of the uniform out of one piece of material except facings, skirt placket and pocket interfacing (if of basic material) which may be cut from ends. The facings, skirt placket and pocket interfacing shall approximate the shade of the finished uniform. c. Cut tie and pocket interlinings from the material indicated in table I. d. Cut bias binding of sufficient length to comply with operation 12.a. If bias binding is not used, the stripping shall be bias cut from the basic material or interlining and shall finish 1/2 inch wide. e. Cut shoulder loops from the material indicated in table I, and in the warp direction.						
2.	Replacement of damaged parts. Care shall be exercised during the spreading, cutting and manufacturing operations to assure that material defects and damages, as classified in 4.2.1.1 are						

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

NO.	TABLE II MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
2.	Replacement of damaged parts. (cont'd)						
	excluded and replaced with non-defective and properly matched material.						
3.	Marking.						
	Mark, ticket or bundle all component parts to insure a correct size and shade throughout the uniform.						
4.	Make tie.						
*	a. Position identification label, 3-1/4 ± 1/4 inches from straight end of right tie (as worn) and centered on bottom folded half of tie. Stitch around label edges through single layer of tie. The stitching shall not be through the printing.	301	LSbj-1	8-14	50	50	
	b. Fold tie sections, position corresponding interlining pieces even with edges and stitch along side and across pointed end, catching interlining in the stitching.	301	SSa-1	10-14	50	50	
	c. Trim and turn tie sections, forcing out points.						
	d. Position snap fastener as indicated by marks on pattern. The pearlized top of the snap fastener shall finish on the outside left tie.						
	e. Overedge stitch raw edge of left tie.	502 or 503	SSa-1 SSa-1	6-8 6-8	70 70	70 70	
	f. Slide buckle onto left tie. Thread overedge stitched edge through metal loop and back through underside of buckle. The tie shall finish 13-1/4 ± 1/4 inches in length.						

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

TABLE II

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
4.	Make tie. (cont'd)						
	g. Slide metal loop onto the end of right tie. Fold end of tie into a point, form a 5/8 inch loop and bartack. The tie shall finish 9-1/2 ± 1/4 inches in length.	Bartack		28 per bartack	50	50	
	VEST						
5.	Make pockets.						
	a. Stitch interlining to pocket along sides and bottom. Turn and force out corners.	301	SSe-2(a)	10-14	50	50	
	b. Overedge top of pocket.	502 or 503	EFd-1 EFd-1	6-8 6-8	70 70	70 70	
	c. Turn under top of pocket 3/8 inch and top stitch 1/4 inch from edge.	301	SSn-1	10-14	50	50	
6.	Make shoulder loops.						
	a. Fold shoulder loop in half lengthwise and with raw edges even, stitch 3/8 inch from raw edges the length of the loop.	301 or 401	SSa-1	10-14	50 50	50 70	
	b. With seam centered, press seam allowance open.						
	c. Stitch 1/4 inch from raw edges at neck edge of loop.	301 or 401	SSa-1	10-14	50 50	50 70	
	d. Turn shoulder loop to finished position, force out points and press. The shoulder loops shall finish 2 ± 1/8 inches in width.						

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

NO.	TABLE II MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
7.	Join facings.						
	a. Join front facings to back facing.	301 or 401	SSa-1 SSa-1	10-14 10-14	50 50	50 50	
*	b. Overedge back edge of facings with shoulder seams of facing turned toward front and catching the bottom edge of the size label in the back facing stitching. The label shall not be off center by more than 1/2 inch.	502 or 503	EFd-1 EFd-1	6-8 6-8	70 70	70 70	
	c. Position the instruction label on the left front facing (as worn) with bottom edge of label 1 to 1-1/4 inches from finished bottom, and stitch through facing only on all four sides. Stitching shall not be through printing.	301	LSbj-1	8-14	50	50	
	d. Position identification label on left facing with the bottom edge of label no more than 1/4 inch above instruction label. Stitch through facing only on all four sides. Stitching shall not be through printing. Bottom of identification label may be caught in row of stitching across top of instruction label.	301	LSbj-1	8-14	50	50	
	e. Combination label (when used) shall be positioned as specified for the instruction label (see 7.c) and stitched through facing only on all four sides. Stitching shall not be through printing.	301	LSbj-1	8-14	50	50	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

NO.	TABLE II MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
8.	Make darts.						
	a. Stitch bust and waist darts on fronts, tapering to nothing 3/4 ± 1/8 inch beyond drill hole and inclosing drill hole within the dart. Turn the inside fold of bust dart toward the bottom and the inside fold of waist darts toward center front.	301	OSf-1	10-14	50	50	
*	b. Stitch neck and waist darts on backs, tapering to nothing 3/4 ± 1/8 inch beyond drill hole and inclosing drill hole within the dart. Turn the inside fold of neck and waist darts toward side seams.	301	OSf-1	10-14	50	50	
9.	Set pockets.						
	a. Position the pockets on right and left front as indicated by marks on patterns. Topstitch to fronts 1/4 inch from edge securely backtacking the ends of stitching. The front edges of the pockets shall be parallel to the front edges of the vest.	301	SSe-2(b)	10-14	50	50	
10.	Join shoulders.						
	Join shoulders with a safety stitch seam	515 or 516 or 519	SSa-2	10-14	50 (chain 70-2 over-edge)	70 70	
11.	Attach facings.						
	Stitch facings to vest with shoulder seams of vest turned toward back.	301	SSe-2(a)	10-14	50	50	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

NO.	TABLE II MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
*12.	Attach shoulder loops and binding to armholes and join side seams.						
	a. Position shoulder loop on shoulder seam, so that center seam of loop is 1/2 inch in front of shoulder seam, and the finished edge of loop is even with neck edge of vest. Position bias binding to outside of vest armhole with shoulder loop sandwiched between the binding and vest and with raw edges of binding and armholes even, stitch 1/4 inch from raw edges.	301	SSa-1	10-14	50	50	
	b. Overedge stitch the side seams.	502 or 503	EFd-1 EFd-1	6-8 6-8	70 70	70 70	
	c. Join side seams from armhole to notch for side vent opening, catching ends of binding.	301	SSa-1	10-14	50	50	
	d. Turn binding to inside of vest with remaining raw edge of binding turned under, stitch to vest 1/16 to 3/32 inch from turned edge. The shoulder loop shall be held out of the way so that it is not caught in the stitching. The binding shall finish 1/2 inch wide and shall lay smooth and flat.	301	LSct-2(b)	10-14	50	50	
	e. Turn shoulder loop back to finished position, and using black thread specified in 3.2.4, stitch to the vest at the neck with the stitching 1/8 inch from edge.	301	SSa-1	10-14	50	50	
13.	Hem bottom of vest.						
	a. Overedge bottom of vest.	502 or 503	EFd-1 EFd-1	6-8 6-8	70 70	70 70	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

TABLE II

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
13.	Hem bottom of vest. (cont'd)						
	b. With facing folded to outside of vest, stitch bottom of vest from front opening to back edge of facing 1 ± 1/8 inch from bottom. Turn facing and evenly force out corners.	301	SSa-1	10-14	50	50	
	c. Turn up bottom of vest and blind stitch. The hem shall finish 1 ± 1/8 inch in width.	103 or 106	EF1-1	6-8	70		
14.	Topstitch.						
	a. Topstitch the vest front opening 1/4 inch from edge securely backtacking the ends of stitching.	301	SSe-2(b)	10-14	50	50	
	b. Turn back side vent edges and topstitch 1/4 inch from folded edge.	301	EFa-1	10-14	50	50	
15.	Attach buttons.						
	Sew the button and chain assembly to the vest fronts as indicated by marks on pattern with the shield in an upright position. (1/8 inch off marks indicated shall be acceptable).	Hand or		6 per button double thread	50		
		101 or 301		14-16 per button	50		
				14-16 per button	50	50	
	SKIRT						
16.	Make darts.						
	Fold darts as indicated by marks on pattern and stitch tapering to nothing 3/4 ± 1/8 inch below drill hole.	301	OSf-1	10-14	50	50	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

TABLE II

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
17.	Make pleats.						
	a. Fold pleats as indicated by marks on pattern and stitch across top to hold in place.	101 or 301 or 401		6-14	50	50	
*	b. On the outside of the skirt, topstitch the folded edges of each pleat to the skirt from the top raw edge of the skirt and down 6-1/2 ± 1/8 inches The edge stitching shall be 1/16 ± 1/32 inch.	301	OSe-1	10-14	50	50	
	c. Top stitch inverted "V" across pleat 6-1/2 ± 1/8 inches down from top of skirt backtacking ends at edge of pleat through all plies according to marks on pattern.	301		10-14	50	50	
*	d. For the remaining length of the pleat, topstitch the folded edge of the pleat only. The edge stitching shall be 1/16 ± 1/32 inch.	301	OSf-1	10-14	50	50	
18.	Join front to back.						
	a. Overedge the raw edges of the left side of front and back (as worn).	502 or 503	EFd-1	6-8 6-8	70 70	70 70	
	b. Starting at top, stitch left side of front to back leaving opening for placket.	301	SSa-1	10-14	50	50	
	c. Stitch right side of front to back with a safety-stitch seam.	515 or 516 or 519	SSa-2	10-14	50 (Chain) 70 (over-edge)	70 70	
	d. Press left seam open and right seam toward the front.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

NO.	TABLE II MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
19.	Make placket.						
	Finished appearance. The placket shall be smooth and flat. The stops at top of fastener shall not be more than 1/4 inch below waistband on the finished skirt. The welt on front skirt shall completely cover the slide fastener when slide fastener is closed and the front skirt shall overlap the back skirt slightly at the bottom of placket (without an outside pleat). The stitching shall not interfere with the operation of the slider and the welt shall be uniform in width.						
	a. Fold the placket piece in half and overedge the side and bottom raw edges.	502 or 503	SSa-1 SSa-1	6-8 6-8	70 70	70 70	
	b. Place slide fastener on placket piece with the center of the closed chain 3/4 to 7/8 inch from overedging and stitch together 1/8 inch from edge of chain nearest the overedging.	301	SSa-1	10-14	50	50	
	c. Place back folded edge of skirt along slide fastener chain and stitch 1/16 inch from folded edge of skirt through slide fastener tape and placket piece.	301	LSah-1	10-14	50	50	
	d. Fold front opening in line with side seam and stitch to fastener tape, forming a welt 1/2 to 5/8 inch wide, stitch across the bottom of welt to the side seam, catching the placket and ends of fastener tapes in the stitching. The stitching shall be 1/8 to 1/4 inch from the chain and the welt shall cover the slide fastener and the stitching along back edge when fastener is closed.	301		10-14	50	50	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTE

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

NO.	TABLE II MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
20.	Attach waistband and labels.						
	Finished appearance. The waistband shall finish 1-1/4 ± 1/16 inches wide and shall be uniform in width. The labels shall be positioned side by side on center of back with the size label on the left side (when skirt is worn). When a combination label is used, it shall be centered (1/2 inch off center tolerance) on the center back. The stitching shall not be through the label printing.						
	a. Position rubberized waistband tape on waistband and stitch on all four sides. (When worn it will be on the inside facing wearer).	301	LSbj-1	10-14	50	50	
	b. Stitch waistband to inside top of skirt catching labels in the stitching.	301	BSg-2(a)	10-14	50	50	
	c. Fold the waistband in half lengthwise; seam the ends. Trim, turn to outside and work out corners.	301	SSe-2(a)	10-14	50	50	
	or						
	d. As an alternate method, the ends of waistband may be seamed, trimmed, and turned, prior to setting waistband to skirt.	301	SSe-2(a)	10-14	50	50	
	e. Turn under free edge of waistband and edge stitch to skirt on outside; continue edge stitching around ends and along top of waistband. The edge stitching shall be 1/16 inch gage.	301	BSg-2(b) and	10-14	50	50	
		301	SSe-2(b)	10-14	50	50	
		301	OSf-1	10-14	50	50	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

TABLE II
MANUFACTURING OPERATIONS REQUIREMENTS

NO.		STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
21.	Hem bottom of skirt.						
	a. Overedge bottom of skirt.	502 or 503	EFd-1 EFd-1	6-8 6-8	70 70	70 70	
	b. Turn up bottom of skirt and blind stitch. The hem shall finish 3 ± 1/4 inches in width.	103 or 106	EF1-1	6-8	70		
22.	Make buttonhole.						
	Finished appearance. The inside edge of buttonhole shall be 1/2 to 3/4 inch from end of waistband. The buttonhole shall be centered (1/4 inch off center tolerance) on waistband.						
	a. Make a 3/4 to 7/8 inch finished cut length buttonhole at end of waistband.	Button-hole		50-60 not including tack	(eyelet end taper bar) 50 (straight cut) 50	 70 50	
*	b. When a straight cut type buttonhole is used it is bartacked in the same operation.	Bartack		21 per tack	50	50	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

NO.	TABLE II MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
23.	Attach button. Mark or gauge position for the button on the waistband to correspond with buttonhole. Sew the button on the mark. When the button is sewn by hand, the sewing shall be tacked off with two stitches and the ends of the threads shall be hidden.	101 or 301 or Hand		14-16 per button 14-16 per button 8 per button double thread	50 50 50	 50 	
24.	Clean uniform. Trim thread ends and remove all loose threads, spots, stains and shade tickets.						
25.	Press. a. Press entire skirt, close slide fastener and button waistband. b. Press entire vest. c. Press tie.						
26.	Prepare for packaging. Prepare uniform for packaging.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

3.8 Finished measurements. The uniform shall conform to the finished measurements shown in table III. The skirt shall be measured with the slide fastener closed.

* TABLE III. Table of measurements (in inches)

Vest	6	8	10	12	14	16	18	20	Tolerance
Front Bust 1/									
- Right	9 7/8	10 1/4	10 5/8	11	11 3/8	11 3/4	12 1/8	12 1/2	± 1/4
- Left	9 7/8	10 1/4	10 5/8	11	11 3/8	11 3/4	12 1/8	12 1/2	± 1/4
Back width 2/	16 3/8	17 1/8	17 7/8	18 5/8	19 3/8	20 1/8	20 7/8	21 5/8	± 1/2
Back length 3/	25 1/2	25 5/8	25 3/4	25 7/8	26	26 1/8	26 1/4	26 3/8	± 1/4
Front sweep 4/									
- Right	10 5/8	11	11 3/8	11 3/4	12 1/8	12 1/2	12 7/8	13 1/4	± 1/4
- Left	10 5/8	11	11 3/8	11 3/4	12 1/8	12 1/2	12 7/8	13 1/4	± 1/4
Back sweep 5/	17 3/4	18 1/2	19 1/4	20	20 3/4	21 1/2	22 1/4	23	± 1/4
Side vent 6/	5 5/8	5 5/8	5 5/8	5 5/8	5 5/8	5 5/8	5 5/8	5 5/8	± 1/4

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

TABLE III. Table of measurements (in inches) (cont'd)

Skirt	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	Tolerance
1/2 Waist 7/	10 3/4	11 1/4	11 3/4	12 1/4	12 3/4	13 1/4	13 3/4	14 1/4	14 3/4	15 1/4	15 3/4	16 1/4	16 3/4	17 1/4	17 3/4	± 1/4
1/2 Hip 8/	16	16 1/2	17	17 1/2	18	18 1/2	19	19 1/2	20	20 1/2	21	21 1/2	22	22 1/2	23	± 1/4
Length 9/	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	± 1/2
	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	± 1/2
	17	17	17	17	17	17	17	17	17	17	17	17	17	17	17	± 1/2
	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18	± 1/2
	19	19	19	19	19	19	19	19	19	19	19	19	19	19	19	± 1/2
	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	± 1/2
	21	21	21	21	21	21	21	21	21	21	21	21	21	21	21	± 1/2
	22	22	22	22	22	22	22	22	22	22	22	22	22	22	22	± 1/2
	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	± 1/2
	24	24	24	24	24	24	24	24	24	24	24	24	24	24	24	± 1/2

1/ Measure from side seam to front edge along dart.

2/ Measure across back from side seam to side seam at dart.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

3/ Measure from neck edge down center back to bottom edge of vest.

4/ Measure from front edge to side vent at hem.

5/ Measure across back from side vent to side vent at hem.

6/ Measure from top of vent opening to bottom of hem.

7/ Measure from folded edge to folded edge along center of waistband.

8/ Measure from folded edge to folded edge at bottom of slide fastener opening.

9/ Measure from waistband joining seam to bottom of hem.

3.9 Workmanship. The finished uniform shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except when otherwise indicated herein.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable specification. A certificate of compliance shall be furnished to indicate that the plastic monofilament slide fastener complies with the requirements of 3.2.7.1. In addition, testing shall be performed on the components listed in table IV for the characteristics shown therein. All test reports shall contain the individual values utilized in expressing the final results. The sample size shall be as specified below and the sample unit shall be one slide fastener (see 3.2.7.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

Lot size (lot unit)	Sample size (sample unit)
800 or less	2
801 to 22,000 inclusive	3
22,001 and over	5

TABLE IV. Component tests

Component	Characteristic	Requirement paragraph	Test method
Slide fastener	Shrinkage	3.2.7.1	4.2.1.1

4.2.1.1 Test procedure for testing shrinkage of slide fastener. The completed slide fastener shall be tested for shrinkage as follows:

4.2.1.1.1 Preparation of specimens. Each slide fastener shall be exposed to Standard Conditions for Testing Textiles until equilibrium is reached. The chain shall be closed and the specimen marked as follows:

(a) The closed slide fastener shall be laid flat without tension on a smooth surface.

(b) Two lines shall be marked 18 inches apart crosswise (from selvage edge to back of chain) on both tapes with laundry proof ink.

4.2.1.1.2 Procedure. Test specimens shall be subjected to one laundering cycle using the apparatus specified in 4.2.1.2 and the following procedures for laundering and drying. The closed slide fastener test specimens shall be placed in the washer with dummy pieces (4.2.1.2.1d.) bringing the washing load to 4 pounds. Fill the full water level of the washer with water, of a hardness not to exceed 50 parts per million and at a temperature of 140 ± 5 degrees F. Add 140 grams of detergent. Set the washer for a 12 minute cycle on the Normal setting. Allow the washing to proceed automatically through the final spin cycle. Remove the load immediately at the completion of the final spin and separate the specimens and dummy pieces when required, if tangled. Place the complete washed load in the dryer and dry at the Normal cycle and at a setting which generated 140 to 160 degrees F. Operate the dryer until the load is dry and continue tumbling 5 minutes with the heat turned off (cool-down cycle). Remove the load immediately after the machine stops. The laundered and dried slide fasteners shall be exposed again to Standard Conditions for Testing Textile until equilibrium is reached.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

4.2.1.1.3 Evaulation. The shrinkage shall be evaluated as follows:

(a) The closed slide fastener shall be laid on a flat, smooth surface with no tension.

(b) The distance between the ink marks on both tapes shall be measured and recorded to the nearest 1/32 of an inch.

(c) The percent shrinkage shall be calculated for both tapes and recorded separately as the percent of the original measurement. Both tapes shall meet the requirement specified (see 3 2.7.1).

4.2.1.2 Apparatus and materials.

4.2.1.2.1 The following apparatus and material is required for laundering:

(a) Automatic washing machine (see 6.8).

(b) Automatic dryer (see 6.8).

(c) AATCC Standard Detergent 124 or equivalent.

(d) Dummy pieces for ballast - 3 by 3 feet hemmed pieces of type 128 cotton sheeting which, when added to test zippers, will make a four pound load.

4.2.2 Examination of the end item. The end item shall be examined for the defects listed in 4.2.2.1 through 4.2.3. The sample unit shall be one uniform (i.e., one skirt, one vest, one tie). Defects shall be classified in accordance with the list below.

4.2.2.1 General defects.

Defects	Classification Major	Minor
Pressing		
a. Omitted		X
b. Burned or scorched	X	
Material defects and damages		
a. Any weakening defect such as a smash, multiple float, or loose slub	X	
b. Any hole, (including drill hole), cut, tear, mend, needle chew or friction burn	X	
c. Shade bar	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

Defects	Classification Major	Minor
Shaded part		
Any outside part shaded	X	
Cleanness		
a. Any spot or stain clearly noticeable on outside	X	
b. Thread ends not trimmed, or loose threads not removed		X
c. Visible basting or holding stitches		X
Components and assembly		
a. Any component part or required operation omitted (unless otherwise classified herein)	X	
b. Any operation not performed as specified (unless otherwise classified herein)		X
c. Any component part not as specified	X	
Cutting		
a. Any part not cut in conformance with dimensional lines	X	
b. Plaid not matching at vest fronts and skirt side seams		
- by 1/8 to 1/4 inch		X
- by more than 1/4 inch	X	
Seams and stitching		
a. Accuracy of seaming:		
1. Any part of uniform caught in unrelated operation or stitching	X	
2. Seam twisted or pleated (unless otherwise classified herein)		X
3. End of seam or stitching when not caught in other seams or stitching backtacked less than 1/4 inch		X
4. Thread breaks stitched back of the break less than 1/2 inch		X
5. Ends of a continuous line of stitching overlapped less than 1/2 inch, or less than 3 stitches on labels		X
6. Seam puckered (see 6.3.1)		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor
Seams and stitching (cont'd)		
b. Gage of stitching and seam allowance:		
1. Irregular unevenly gaged or corresponding stitchings not uniformly gaged (to be scored only when condition exists along major portion of seam)		X
2. Width not as specified or not within range of gage specified or varies more than 1/16 inch when no range is specified		X
c. Any raw edge:		
- More than 1/4 inch to 1 inch, inclusive		X
- More than 1 inch	X	
d. Stitch, broken or missing:		
1. All stitching except buttonholes, slide fastener and overedging		
- More than 1/4 inch but not more than 1/2 inch		X
- More than 1/2 inch	X	
2. Slide fastener stitching:		
- Any	X	
3. Overedging:		
- More than 1 inch		X
e. Skipped stitches or runoffs: (except on buttonholes)		
- Over 1/4 inch in length		X
f. Seam and stitch type		
1. Not specified seam or stitch type		X
2. Looper thread on 401 stitch type on outside	X	
g. Stitch tension		
1. Loose tension resulting in a loose seam	X	
2. Tight tension (on 301 stitch type, stitches break when tension is applied in direction of seam)	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor
Seams and stitching (cont'd)		
h. Stitches per inch: (Score only when condition exists on major portion of seam) - Less than the minimum or more than the maximum specified		X
i. Bartack (except buttonhole bartack) missing, insecure, misplaced, not serving intended purpose or not specified length		X
Buttonhole		
a. Omitted, added, or not specified type	X	
b. Ragged edges or stitching not caught in fabric		X
c. One or more broken or continuous skipped stitches		X
d. Tacking omitted on ends		X
e. Purling not on outside		X
Button		
a. Missing, broken, defective, unsecurely sewn	X	
b. Stitching not locked at end of cycle (tug at loose end of thread, when accessible, to determine if it will ravel)	X	
Labels		
a. Not attached as specified, misplaced, or stitched through printing		X
b. Missing, incorrect or illegible	X	
1. Size label, instruction or combination label	X	
2. Identification		X
Snap fastener		
Broken, loose, missing or mismated		X
Slide fastener		
Broken or defective	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

Defects	Classification Major	Minor
Tie		
a. Twisted, full or puckered	X	
b. Pointed ends not worked out (have a depth between folds of 1/16 inch)		X
c. Underside of tie exposed on outside more than 1/16 inch or for a distance of more than one inch		X
d. Irregular in width by more than 1/8 inch		X
Vest		
a. Front		
1. Button placed beyond specified location		X
2. Buttons out of horizontal alignment by more than 1/8 inch		X
3. Facing not worked out at hem, having fold of 1/16 inch or more		X
4. Topstitching uneven by more than 1/16 inch	X	
5. Horizontal stripes of plaid not matched on front closure by more than 1/4 inch	X	
b. Darts		
1. Dart tapered less than 5/8 or more than 7/8 inch beyond drill hole		X
2. Inside thread on dart less than 1/2 inch or more than 3/4 inch long		X
c. Armholes		
1. Binding tight at armhole causing puckers or pleats on front or back		X
2. Top stitching not evenly gaged around arm hole		X
d. Pockets		
1. Position not as indicated by marks on pattern	X	
2. Not uniform in size or shape	X	
3. Pocket edge not parallel to front edge of vest by		
- More than 3/8 inch	X	
- 1/4 inch to 3/8 inch inclusive		X
4. Edge of pocket pleated or twisted		X
5. Pocket corners not secured as specified		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

Defects	Classification Major	Minor
Vest (cont'd)		
e. Direction of seams		
1. Shoulder seam allowance not turned toward back at facing joining seam		X
2. Bust darts not turned toward bottom hem		X
3. Folds of back darts and back neck darts not turned toward center back		X
4. Fold of front darts not turned toward center front		X
f. Facing		
1. Twisted, puckered or pulled at shoulder or hem		X
2. Back edge of facing not overedged		X
g. Bottom hem		
1. Side vents less than 5-3/8 inch or more than 5-7/8 inches in length		X
2. Hem twisted, puckered or pleated		X
3. Width less than 7/8 inch or more than 1-1/8 inches		X
h. Shoulder loops		
1. Less than 1-7/8 inches or more than 2-1/8 inches wide		X
2. Not positioned as specified		X
Skirt		
a. Waistband		
1. Twisted	X	
2. Not uniform in width by more than 1/8 inch		X
3. Less than 1-3/16 or more than 1-5/15 inches wide		X
4. Ends poorly shaped or corners not completely forced out		X
5. Fullness on outside of waistband		X
b. Skirt closure		
1. Button misplaced		X
2. Inside edge of buttonhole less than 1/2 or more than 3/4 inch from end of waistband		X
3. Buttonhole misplaced on waistband causing bulge or twist	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

Defects	Classification Major	Minor
Skirt (continued)		
b. Skirt closure (cont'd)		
4. Placket piece or welt twisted, tight or pleated	X	
5. Placket piece not completely caught in waistband joining seam		X
6. Welt edge stretched or twisted		X
7. Welt stitching irregular		X
8. Slide fastener stitching on back edge of placket exposed beyond edge of welt		X
9. Back or front of placket stitched too close to slide fastener preventing free passage of slider or slide fastener defective affecting function	X	
10. Slide fastener tapes stitched too loose or too tight, causing placket to bulge when closed		X
11. Stops at top of slide fastener more than 1/4 inch from waistband		X
12. Top of slide fastener tapes not securely caught in waistband		X
13. Bottom stop on slide fastener extended more than 1/4 inch above or below the top end of side seam		X
c. Darts		
1. Twisted or puckered		X
2. Ends of darts less than 5/8 or more than 7/8 inch below drill hole		X
3. Inside folded edge of darts not turned toward center of skirt		X
d. Pleats		
1. Depth of pleat less than 3-7/8 inches or more than 4-1/8 inches		X
2. Total pleat not uniform in width by more than 1/4 inch		X
3. Topstitching to hold pleats down less than 5-7/8 inches or more than 6-1/8 inches		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor
Skirt (cont'd)		
d. Pleats (cont'd)		
4. Pleats not positioned as indicated by marks on pattern		X
5. Pleats not uniform in size		X
6. End topstitching on pleats out of horizontal alignment by 1/4 inch or more	X	
e. Hem		
1. Hem twisted, puckered or pleated		X
2. Width less than 2-3/4 or more than 3-1/4 inches		X
f. Side seams		
1. Horizontal stripes of plaid not matched on side seams by more than 1/8 inch		X

4.2.2.3 Size measurements. Any measurement deviating from the dimensions and tolerances specified in table III shall be classified as a size measurement defect.

4.2.3 Acceptable quality and inspection levels. The inspection levels and acceptable quality levels expressed in defects per hundred units (DHU) shall be as follows:

	AQLs	Inspection level
For 4.2.2.1 and 4.2.2.2		
Major	2.5	II
Minor	15.0	II
For 4.2.2.3		
One class	4.0	S-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

4.2.4 Packaging inspection. An examination shall be made to determine that packaging, packing and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully packaged. The lot size shall be the number of containers in the end item inspection. The inspection levels shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, inadequate stapling Open and noncontinuous heat sealed seams and closure of polyethylene bag. Omission of vent hole in polyethylene bag. Alternative to heat sealed closure polyethylene bag not provided with tuck or reverse flap Bulged or distorted container
Content	Number of unit packs per shipping container more or less than required

5. PACKAGING

5.1 Preservation. Preservation shall be level Commercial.

5.1.1 Commercial. Uniforms shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level Commercial.

5.2.1 Commercial packing. Uniforms preserved as specified in 5.1 shall be packed in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract, unit packs and shipping containers shall be marked in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

5.3.2 Labels, mixed sizes. Each shipping container, packed with mixed sizes, shall have securely attached to the end and side, directly under the printing or stenciling a white paper label 5 by 4 inches, with the words "MIXED SIZES" plainly stamped or printed thereon, and under these words shall be legibly stamped or printed the correct quantity and sizes contained therein.

6. NOTES

6.1 Intended use. The uniform covered by this specification is intended for wear by girls in the Junior R.O.T.C. Program.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Sizes required (see 1.2).

6.3 Samples. For access to samples of the end item and shade samples, address the procuring officer issuing the invitation for bids.

6.4 United Elastic Company Style N3-5564 - "ANCHORTEX" has been found suitable for use as the rubberized waistband tape (see 3.2.6).

6.5 The following commercial style numbers will meet the requirements listed in 3.2.10; Anchor Chain Corporation, Catalog No. 3310-XC or Armbrust Chain Company, Catalog No. 802X.

6.6 Rau Fastener Company components

Male component	- Stud # 1531 - Eyelet # 1541
Female component	- Front # 10-1525 - Socket # 1521

will meet the requirements listed in 3.2.8.

6.7 Waterbury Buckle Company, style No. 9045 will meet the requirements of 3.2.11.

6.7.1 Waterbury Buckle Company, style No. 6277 will meet the requirements of 3.2.12.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

6.8 The recommended apparatus for test procedure in 4.2.1.2.1 subparagraphs a and b are:

(a) Kenmore Automatic Washing Machine Model 600, or similar washing machine. In case of dispute, the Kenmore Model 600 shall be used.

(b) Kenmore Automatic Dryer Model 600, or equivalent.

6.9 Shrinkage of slide fasteners. Experience has shown that slide fasteners containing a durable press finish will meet the shrinkage requirements of 3.2.7.1.

6.10 Changes from previous issue. The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Review activities:

Army - MD
DLA - CT

Preparing activity:

Army - GL

Project No. 8410-A380

☆ U.S. GOVERNMENT PRINTING OFFICE: 1980—603-121/501

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

DRDNA-ES

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S. MAIL

Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

NATICK OP 1 AUG 78
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document a enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users the document are invited to submit comments to the government. Fold on lines on reverse side, staple in co and send to preparing activity. Attach any pertinent data which may be of use in improving this document there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating th the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specificatio requirements on current contracts. Comments submitted on this form do not constitute or imply authorizat to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-U-43937A(GL)
UNIFORM, WOMAN'S: JUNIOR R. O. T. C.

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUR USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T23:04Z
Check the source to verify that this is the current version before use.