INCH - POUND

MIL-DTL-11484/344A
15 June 2017
SUPERSEDING
MIL-DTL-11484/344
7 August 2012

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, EARLY CAREER ACHIEVEMENT MEDAL, NASA

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: 24K Gold Plated, Matte Finish, Polished Highlights, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

DIMENSIONS:
HEIGHT: 5/8 inch
WIDTH: 19/32 inch
THICKNESS (along top hoop): 0.086 inch ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prong with pick and wing type clutch.

2. The prong shall be centered on the reverse side and either fused or soldered to the lapel button.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:00Z
Check the source to verify that this is the current version before use.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The manufacturer may deviate from MIL-DTL-11484 by using nickel underplating prior to plating with 24K gold.

3. This item is not authorized for commercial sale, and may be produced only under Government contract and at the request of the National Aeronautics and Space Administration.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review Activity:
DLA - CT

(Project No. 8455-2017-245)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:00Z
Check the source to verify that this is the current version before use.