INCH-POUND
MIL-S-15743C(SH)
SUPPLEMENT 1
22 November 1993

MILITARY SPECIFICATION

SWITCHES, ROTARY, ENCLOSED

This supplement forms a part of Military Specification MIL-S-15743C(SH) dated 22 November 1993.

MIL-S-15743/1 - Switch, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 125 Volts Alternating Current, 10 Ampere, Symbol 801.1 (DPST).

MIL-S-15743/2 - Switch, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 125 Volts Alternating Current, 10 Ampere, Symbol 858 (DPTT).

MIL-S-15743/3 - Switches, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 125 Volts Alternating Current, 10 Ampere, Symbols 801.2 (DPST), 804.1 (TPST), 829.1 (DPDT), and 879.1 (DPTT).

MIL-S-15743/4 - Switches, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 125 Volts Alternating Current, 10 Ampere, Symbols 805.1 (4PST), and 857 (TPDT).

MIL-S-15743/5 - Switches, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 125 Volts Alternating Current, 10 Ampere, Symbols 827.1 (SPECIAL), 850.1 (TPDT), and 863 (4PDT).

MIL-S-15743/6 - Switch, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 125 Volts Alternating Current, 10 Ampere, Symbol 862 (TPTT).

MIL-S-15743/7 - Switch, Rotary, Enclosed, Splashproof, Snap Action, 125 Volts Alternating Current, 10 Ampere, Symbol 814 (DPST).

MIL-S-15743/8 - Switches, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 500 Volts Alternating Current/250 Volts Direct Current, 30 Ampere, Symbols 838.1 (DPDT), 840.1 (DPDT), and 851 (TPST).

MIL-S-15743/9 - Switches, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 500 Volts Alternating Current/250 Volts Direct Current, 30 Ampere, Symbols 839.1 (4PDT), 848.1 (TPDT), and 2752.1 (SPECIAL).

MIL-S-15743/10 - Switch, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 500 Volts Alternating Current/250 Volts Direct Current, 30 Ampere, Symbol 852 (4PDT).

AMSC N/A FSC 5930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.

MIL-S-15743/11 - Switch, Rotary, Enclosed, Submersible (15 Feet), Snap Action, 500 Volts Alternating Current/250 Volts Direct Current, 30 Ampere, Symbol 2753 (DPST).

MIL-S-15743/12 - Switch, Rotary, Enclosed, Submersible (15 Feet), Snap Action, Transfer, with Indication, 125 Volts Alternating Current, 30 Ampere, Symbol 2763 (4PDT).

MIL-S-15743/13 - Switch, Rotary, Enclosed, Watertight Snap Action, Transfer, with Indication, 125 Volts Alternating Current, 30 Ampere, Symbol 849 (TPDT).

MIL-S-15743/14 - Switches, Rotary, Enclosed, Watertight Snap Action, Transfer, with Indication, Symbol 853 (TPDT), 500 Volts Alternating Current, 60 Ampere, Symbol 854 (TPDT), 125 Volts Alternating Current, 60 Ampere.

MIL-S-15743/15 - Switch, Rotary, Enclosed, Watertight, Snap Action, Portable, 500 Volts Alternating Current, 30 Ampere, Symbol 817.1 (TPST).

MIL-S-15743/16 - Switch, Rotary, Enclosed, Submersible (15 Feet), Contact Maker, Six-Pole, Two-Position, Spring-Return, 125 Volts Alternating Current, 10 Ampere, Symbol 2637.1.

MIL-S-15743/17 - Switch, Rotary, Enclosed, Submersible (15 Feet), Contact Maker, Six-Pole, Two-Position, Spring-Return, 125 Volts Alternating Current, 10 Ampere, Symbol 2638.1.

MIL-S-15743/18 - Switch, Rotary, Enclosed, Submersible (15 Feet), Snap Action, Six-Pole, Two-Position, Positive Detent, 125 Volts Alternating Current, 10 Ampere, Symbol 2639.1.

MIL-S-15743/19 - Switch, Rotary, Enclosed, Submersible (15 Feet), Snap Action, Six-Pole, Three-Position, Positive Detent, 125 Volts Alternating Current, 10 Ampere, Symbol 2640.1.

MIL-S-15743/20 - Switch, Rotary, Enclosed, Submersible (15 Feet), Contact Maker, Six-Pole, Three-Position, Spring- Return, 125 Volts Alternating Current, 10 Ampere, Symbol 2641.1.

MIL-S-15743/21 - Switches, Rotary, Enclosed, Watertight, Contact Maker, Multipole, Eight Position, 125 Volts Alternating Current, 5 Ampere, Symbols 867.1 through 872.1.

MIL-S-15743/22 - Switches, Rotary, Enclosed, Watertight, 6-Section, 16-Position, 125 Volts Alternating Current, 5 Ampere, Symbols 2785 (Deck Mounted) and 2786 (Bulkhead Mounted).

Preparing activity:
Navy - SH

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.