
MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, ENCLOSED, SUBMERSIBLE (15 FEET),
SNAP ACTION, 125 VOLTS ALTERNATING CURRENT, 10 AMPERE,
SYMBOL 801.1 (DPST)

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-S-15743(SH).




SH 131123

FIGURE 1. Switch, enclosed. (01)

NOTES:
1. All dimensions in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.
   Angular dimensions - plus or minus 30 minutes.

FSC 5930


Source: https://assist.dla.mil -- Downloaded: 202610-18T07:55Z
Check the source to verify that this is the current version before use.



SH 131124

FIGURE 2. Box assembly, (modified).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.



SH 131125


FIGURE 3. Cover assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.



SH 131126


FIGURE 4. Cushion gasket. (04)



SH 131127


FIGURE 5. Handle. (05)

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:55Z
Check the source to verify that this is the current version before use.




SH 131128

FIGURE 6. Shaft assembly. (06)



SH 131129


FIGURE 7. Shaft. (07)



SH 131130


FIGURE 8. Coupler. (08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.



SH 131131


FIGURE 9. Coupler plate. (09)



SH 131132


FIGURE 10. Mounting dimensions, ref.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.



SH 131134

FIGURE 12. Identification plate. (11)



SH 131133

FIGURE 11. Wiring diagram. (10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

SYMBOL NUMBER: See table I.

DESIGN:

Electrical rating: 125 Va.c., 0-10 ampere, 60 Hz.
Dimensions and configuration: See figures 1 through 9.
Wiring diagram: See figure 11.
Mounting dimensions: See figure 10.
Degree of enclosure: Submersible (15 feet).
Weight: 2 pounds maximum.
Designation and marking: See figure 12.
Identification data shall be as shown on figure 12. Unless otherwise specified in the ordering data, switch action marking shall be as shown on figure 12.
Parts: The parts shown in table II shall be used in the construction of the switch specified herein.

GENERAL INFORMATION:

Military part number and general information are as shown in table I.

TABLE I. Military part number and general information.

Military part no.	Symbol no.	No. of poles and switching characteristics	Supersedes 1/				
			Type	Unit	Sheet	Revision	Date
M15743/1-001	801.1	DPST	1SR2A4-4	1	1	D	10/28/57

1/ NAVSEA Drawing 9000-S6202-74207, in part.

ORDERING DATA:

Acquisition documents should specify the following:
Switch action marking, if required (see requirements).

TABLE II. Parts list.

Item no. 1/	Description	Quantity M15743/1-001	Material/specification	Remarks
01	Switch, enclosed	-		See figure 1
02	Enclosure	1	Brass, MIL-E-24142/5	M24142/5-001 Mod 2/
03	O-ring	1	MS28775-010	----
04	Cushion gasket	1	MIL-R-900	See figure 4
05	Handle	1	Copper alloy 854 of QQ-C-390	See figure 5
06	Shaft assembly	1	-----	See figure 6
07	Shaft	1	Ni-Cu alloy of QQ-N-281	See figure 7
08	Coupler	1	Brass, alloy 260 of QQ-B-613	See figure 8

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 202640-18T07:55Z
Check the source to verify that this is the current version before use.

TABLE II. Parts list. - Continued

Item no. 1/	Description	Quantity M15743/1-001	Material/specification	Remarks
09	Coupler plate	1	CRES, class 304 or 316 of QQ-S-766	See figure 9
10	Wiring diagram	1	MIL-E-2036	See figure 11
11	Switch (type 1SR2A4)	1	MIL-S-15291/3	M15291/3-002
12	Identification plate	1	Brass, QQ-B-613	See figure 12

1/ Numbers in circles shown on the figures are the same as the item numbers shown in this table.
2/ Modified depth and deleted mounting brackets (see figure 2).

Preparing activity:
Navy - SH
(Project 5930-N584-1)

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:55Z
Check the source to verify that this is the current version before use.