MIL-P-15736D(SHIPS)
AMENDMENT 3
28 February 1985
SUPERSEDING
AMENDMENT 2
27 October 1965

MILITARY SPECIFICATION

POWER SUPPLIES, METALLIC RECTIFIER,
NAVAL SHIPBOARD

This amendment forms a part of Military Specification MIL-P-15736D(SHIPS), dated 9 August 1965, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2: Delete and substitute:

"1.2 Classification. Power supplies shall be of the following classes as specified on the individual detail specification (see 6.1.1) or as specified in the contract or order (see 6.1.2).

Class R - Regulated.
Class NR - Nonregulated."

PAGE 2

* 2.1, under "SPECIFICATIONS, MILITARY": Delete reference to "MIL-O-16485".

3.1, line 3: Delete "(see 6.1)".

PAGE 6

3.6.4.1, line 1: Delete "Cohen" and substitute "When".

PAGE 11

3.9.1(c)(12), line 3: Delete "similar applications" and substitute "application stresses".

PAGE 14

3.10, line 4: Delete "II" and substitute "I".

PAGE 17

Table II, inspection column, opposite inclined operation: Delete "---" and substitute "4.5.15".

FSC 6130

Source: https://assist.dla.mil -- Downloaded: 202640-18T07:33Z
Check the source to verify that this is the current version before use.

PAGE 21

* 4.5.2, fourth sentence: Delete and substitute: "Insulation resistance shall be measured with a hand-driven generator type insulation resistance indicating ohmmeter which contains a 500 volt constant voltage source and has a 0 to 100 megohm range. The ohmmeter is required to be accurate to the extent that the pointer indicates within 2 percent of scale length."

PAGE 27

Add as new paragraph 4.5.15:

"4.5.15 Inclined operation. The equipment shall be tested for inclined operation by operating at full output load current with rated input voltage and frequency. Inclination of the equipment in the following positions shall not cause interruption of the output current from the equipment while operating, and while not operating shall not cause any change from the nonoperating condition:

(a) Inclined 45 degrees forward.
(b) Inclined 45 degrees backward.
(c) Inclined 45 degrees to the right side.
(d) Inclined 45 degrees to the left side.

This test applies only to equipment containing relays or contactors."

PAGE 28

6.1: Delete and substitute:

"6.1 Ordering data. Acquisition documents should specify data of 6.1.1 or 6.1.2, as applicable.

"6.1.1 Power supplies covered by detail specifications:

(a) Title, number and date of this specification.
(b) Title, number and date of detail specification.
(c) Classification under detail specification (where applicable).

"6.1.2 Power supplies not covered by detail specifications:

(a) Title, number and date of this specification.
(b) Class required (see 1.2).

NOTE: Equipment classification shall normally be based on the requirements of the application. Use of class NR power supplies is desirable, where practical, because of their generally lower cost and greater simplicity. The factors which determine whether a class NR power supply can be used in a specific application are given in 6.2.

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:33Z
Check the source to verify that this is the current version before use.

(c) Electrical rating and performance (see 3.5.2):
  (1) Ac input voltage (see 3.5.2.1).
  (2) Input frequency (see 3.5.2.2).
  (3) Phases and balances (see 3.5.2.3).
  (4) Dc output (see 3.5.2.4).
    a. Output voltage adjustment range and resolution.
    b. Output voltage regulation required.
      1. With input voltage changes.
        a. Steady state.
        b. Transient.
      2. With output load current changes.
        a. Steady state.
        b. Transient.
          1. Maximum permitted initial excursion of output voltage on load application and rejection.
          2. Time to recover steady value.
          3. Maximum permitted overshoot during recovery.
        c. Remote regulation (d.c. line drop compensation.)
          1. Whether remote sensing is required (see 3.5.2.4.1).
          2. Maximum voltage drop (at rated output current) between power supply and remote point at which voltage is to be regulated.
(d) Permissible ripple content (see 3.5.2.5).
(e) Whether remote control of output voltage is required.
(f) Rating (normally given in output current) (see 3.5.2.5).
  (1) Continuous
  (2) Intermittent, if applicable.
    a. Current.
    b. Time.
  (3) Degree and type of protection (for example, fuses) (see 3.5.2.8).
(g) Current limiting characteristics (if any) required.
(h) Duty, if other than continuous (see 3.5.2.5).
(i) Switching required (if any).
  (1) Input.
  (2) Output.
  (3) Remote control, if required.
(j) Meter and meter accessories required (see 3.8.3):
  (1) Type and size.
  (2) Range.
  (3) Special marking, if applicable.
(k) Structureborne noise limits required (see 3.5.4.2, and note 2, table II).
(l) Radio frequency (see 3.5.5).
(m) Ventilation (see 3.6.5).
(n) Mounting (see 3.6.2).
(o) Ambient temperature, if different from 3.5.3.2.
(p) Enclosure type, if other than dripproof protected (45 degrees) (see 3.6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:33Z
Check the source to verify that this is the current version before use.

(q) Maximum size and weight (see 3.6.4):
    (1) For submarine equipment, whether equipment must pass submarine hatch, watertight door, or both (see 3.6.4.1).
(r) Type of load (see 3.5.2.6). Note: For battery charging, specify type of battery, if other than lead acid.
(s) Whether manuals are required (see 3.10).
(t) Repair parts (see 3.11.1).
(u) Preservation, packaging, packing and marking required, if other than specified in 5.1 (see 5.2).
(v) Exceptions, if any."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 6130-N251)

☆U.S. GOVERNMENT PRINTING OFFICE: 1985 — 505-038/21331

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:33Z
Check the source to verify that this is the current version before use.