INCH-POUND
MIL-S-15743/2A(SH)
22 November 1993
SUPERSEDING
MIL-S-15743/2(SH)
27 August 1984

MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, ENCLOSED, SUBMERSIBLE (15 FEET), SNAP ACTION, 125 VOLTS ALTERNATING CURRENT, 10 AMPERE, SYMBOL 858 (DPTT)

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-S-15743.




FIGURE 1. Switch, enclosed. (01)

NOTES:
1. All dimensions in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.
   Angular dimensions - plus or minus 30 minutes.

AMSC N/A FSC 5930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-18T07:55Z
Check the source to verify that this is the current version before use.




FIGURE 2. Box assmebly, (modified).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.




FIGURE 3. Cover assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.




FIGURE 4. Cushion gasket. (04)




FIGURE 5. Handle. (05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.




FIGURE 6. Shaft assembly. (06)




FIGURE 7. Shaft. (07)




FIGURE 8. Coupler. (08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.




FIGURE 9. Coupler plate. (09)




FIGURE 10. Mounting dimensions, ref.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.




FIGURE 12. Identification plate. (12)




FIGURE 11. Wiring diagram. (10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

SYMBOL NUMBER: See table I.

DESIGN:

Electrical rating: 125 Va.c., 0-10 ampere, 60 Hz.
Dimensions and configuration: See figures 1 through 9.
Wiring diagram: See figure 11.
Mounting dimensions: See figure 10.
Degree of enclosure: Submersible (15 feet).
Weight: 2 pounds maximum.
Designation and marking: See figure 12.
Identification data shall be as shown on figure 12. Unless otherwise specified in the ordering data, switch action marking shall be as shown on figure 12.
Parts: The parts shown in table II and as specified in MIL-S-15743 shall be used in the construction of the switch specified herein.

GENERAL INFORMATION:

Military part number and general information are as shown in table I.

TABLE I. Military part number and general information.

Military part no.	Symbol no.	No. of poles and switching characteristics	Supersedes 1/		
			Type	Unit	Sheet
M15743/2-001	858	DPTT	1SR2F4-2a	10	11

1/ NAVSEA Drawing 9000-S6202-74207, in part.

ORDERING DATA:

Acquisition documents should specify the following:
Switch action marking, if required (see requirements).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:55Z
Check the source to verify that this is the current version before use.

TABLE II. Parts list.

Item no. 1/	Description	Quantity M15743/2-001	Material/specification	Remarks
01	Switch, enclosed	-		See figure 1
02	Enclosure	1	Brass, MIL-E-24142/5 (modified)	M24142/5-001 See figures 2 & 3
03	O-ring	1	MS28775-010	----
04	Cushion gasket	1	MIL-R-900	See figure 4
05	Handle	1	Copper alloy ASTM B 584	See figure 5
06	Shaft assembly	1	-----	See figure 6
07	Shaft	1	Ni-Cu alloy of QQ-N-281	See figure 7
08	Coupler	1	Brass, ASTM B 36 ASTM B 121	See figure 8
09	Coupler plate	1	CRES, class 306 or 316 of QQ-S-766	See figure 9
10	Wiring diagram	1	MIL-E-2036	See figure 11
11	Switch (type 1SR2F4)	1	MIL-S-15291/3	M15291/3-021
12	Identification plate	1	ASTM B 36, ASTM B 121	See figure 12

1/ Numbers in circles shown on the figures are the same as the item numbers shown in this table.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 5930-N746-2)

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:55Z
Check the source to verify that this is the current version before use.