
MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, ENCLOSED, SUBMERSIBLE (15 FEET), SNAP ACTION, 125 VOLTS ALTERNATING CURRENT, 10 AMPERE, SYMBOL 862 (TPTT)

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-S-15743(SH).




SH 131180

FIGURE 1. Switch, enclosed. (01)

NOTES:
1. All dimensions in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.
   Angular dimensions - plus or minus 30 minutes.

FSC 5930


Source: https://assist.dla.mil -- Downloaded: 202610-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131181

FIGURE 2. Box assembly.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131182

FIGURE 3. Cover assembly, (modified).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131183


FIGURE 4. Handle. (04)

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:57Z
Check the source to verify that this is the current version before use.




SH 131184

FIGURE 5. Shaft assembly. 05



SH 131185


FIGURE 6. Shaft. 06



SH 131186


FIGURE 7. Coupler. 07

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131187


FIGURE 8. Coupler plate. (08)



SH 131188

FIGURE 9. Mounting dimensions, ref.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131189

FIGURE 10. Wiring diagram. (09)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131190

FIGURE 11. Identification plate. (11)

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:57Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

SYMBOL NUMBER: See table I.

DESIGN:

Electrical rating: 125 Va.c., 0-10 ampere, 60 Hz.
Dimensions and configuration: See figures 1 through 9.
Wiring diagram: See figure 10.
Mounting dimensions: See figure 9.
Degree of enclosure: Submersible (15 feet).
Weight: 3 pounds maximum.
Designation and marking: See figure 11.
Identification data shall be as shown on figure 11. Unless otherwise specified in the ordering data, switch action marking shall be as shown on figure 10.
Parts: The parts shown in table II and as specified in MIL-S-15743 shall be used in the construction of the switch specified herein.

GENERAL INFORMATION:

Military part number and general information are as shown in table I.

TABLE I. Military part number and general information.

Military part no.	Symbol no.	No. of poles and switching characteristics	Supersedes 1/				
			Type	Unit	Sheet	Revision	Date
M15743/6-001	862	TPTT	1SR3F4-2	11	12	E	10/4/58

1/ NAVSEA Drawing 9000-S6202-74207, in part.

ORDERING DATA:

Acquisition documents should specify the following:
Switch action marking, if required, (see requirements).

TABLE II. Parts list.

Item no. 1/	Description	Quantity M15743/6-001	Material/specification	Remarks
01	Switch, enclosed	-		See figure 1
02	Enclosure	1	MIL-E-24142/5 2/	M24142/5-002 See figure 2
03	O-ring	1	MS28775-010	---
04	Handle	1	Copper alloy 854 of QQ-C-390	See figure 4
05	Shaft assembly	1	-----	See figure 5
06	Shaft	1	Ni-Cu alloy of QQ-N-281	See figure 6
07	Coupler	1	Brass, alloy 260 of QQ-B-613	See figure 7
08	Coupler plate	1	CRES, class 304 or 316 of QQ-S-766	See figure 8

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:57Z
Check the source to verify that this is the current version before use.

TABLE II. Parts list. - Continued

Item no. 1/	Description	Quantity M15743/6-001	Material/specification	Remarks
09	Wiring diagram	1	MIL-E-2036	See figure 10
10	Switch (type 1SR3F4)	1	MIL-S-15291/3	M15291/3-002
11	Identification plate	1	Brass, QQ-B-613	See figure 11

1/ Numbers in circles shown on the figures are the same as the item numbers shown in this table.
2/ Modified enclosure cover, (see figure 3).

Preparing activity:
Navy - SH
(Project 5930-N584-6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.