MIL-B-41809 / 17D
12 April 1985
SUPERSEDING
MIL-B-41809 / 17C(IH)
13 May 1980

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION; US ARMY NATIONAL GUARD, RECRUITER

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-41809.

DASH NO.	DEGREE
-1:	BASIC
-2:	SENIOR

MATERIAL: RED BRASS
DIMENSIONS (INCHES)
DIAMETER: 2 (REF)
THICKNESS (EDGE): .065 ± .005

FINISH:
-1: NICKEL PLATED, SILVER PLATED, OXIDIZED RELIEVED SATIN FINISH
-2: GOLD PLATED SATIN FINISH WITH POLISHED LETTERS AND HIGHLIGHTS

NOTES:
1. ATTACHING DEVICE SHALL BE THREE PRONGS AND CLUTCHES. THE PRONGS SHALL BE LOCATED ON A 1-3/4 INCH CIRCLE, 120 DEGREES APART WITH THE TOP PRONG LOCATED ON THE VERTICAL CENTER LINE OF THE BADGE.

2. A MOCK FORCER MAY BE USED TO BRING UP THE DESIGN OF THE MINUTEMAN.

3. THE FACE AND SIDE (EDGES VISIBLE FROM THE FRONT) OF -1 AND -2 BADGES SHALL BE COATED WITH LACQUER.

CUSTODIANS:	REVIEW ACTIVITIES:	USER ACTIVITIES:
ARMY	IH	
AIR FORCE		
NAVY		
OTHER	CT	

PREPARING ACTIVITY:
THE INSTITUTE OF HERALDRY, UNITED STATES ARMY

Project No. 8455 - A154

/FSC 8455/

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:35Z
Check the source to verify that this is the current version before use.