NOT MEASUREMENT SENSITIVE

MIL-B-41809/17F
30 April 1992
SUPERSEDING
MIL-B-41809/17E
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, U.S. ARMY NATIONAL GUARD RECRUITER

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red Brass

DASH NO:
-1: Basic
-2: Senior

DIMENSIONS:

DIAMETER: 2 inches (5.08 cm) (REF)

THICKNESS (Edge): 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm)

FINISH:
-1: Nickel plated, silver plated, oxidized, relieved, matte finish
-2: Gold plated, matte finish, polished letters and highlights

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:35Z
Check the source to verify that this is the current version before use.

NOTES:

1. Attaching device shall be prong and clutch type. Three prongs shall be located on a 1-3/4 inch (4.45 cm) diameter circle. Each prong shall be 120 degrees apart with one prong located on the vertical center line at the top of the badge.

2. A mock forcer may be used to bring up the design of the minuteman.

3. The term (REF) refers to the measurements taken from the Government furnished hub or die.

4. As an alternate method of manufacturing, 22 karat gold plate with nickel underplating may be used.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0666)

Source: https://assist.dla.mil - Downloaded: 2026-10-21T19:35Z
Check the source to verify that this is the current version before use.