NOT MEASUREMENT SENSITIVE

MIL-B-41809/19C
21 September 1994
SUPERSEDING
MIL-B-41809/19B
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, CAREER COUNSELOR, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass Only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Overall): 1-7/8 inches (4.76 cm) (REF)
WIDTH (Overall): 2-9/16 inches (6.51 cm) (REF)
THICKNESS (Edge of Scroll): 0.100 inch ± 0.005 (0.254 cm ± 0.012 cm)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnis hub or die.

2. Piercing shall be as indicated.

3. A full forcer shall be used to bring up the design.

4. The attaching device shall be prong and clutch type. One prong shall be located on the vertical center line, 5/16 inch (0.79 cm) below the top of the wreath. Two prongs shall be located on a horizontal line 1/2 inch (1.27 cm) above the base, equidistant from each end and 1-7/8 inch (4.76 cm) apart.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.