MIL-B-41809 /20C
31 DECEMBER 1978
SUPERSEDING
MIL-B-41809/ 20B
20 February 74

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION; JUNIOR ROTC INSTRUCTOR, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-41809.

MATERIAL: 1/20 SILVER FILLED (FRONT ONLY) OVER A COMMERCIAL COPPER BASE ALLOY

DIMENSIONS (INCHES):
- HEIGHT (OVERALL): 1-7/8 (REF)
- WIDTH (OVERALL): 1-5/8 (REF)
- THICKNESS (EDGE OF OUTER SCROLLS): .060 (REF)

FINISH: SILVER PLATED, OXIDIZED, RELIEVED SATIN FINISH

NOTES:

1. THE ATTACHING DEVICE SHALL CONSIST OF THREE PRONGS AND CLUTCHES LOCATED AS FOLLOWS:

   ONE PRONG LOCATED AT THE INTERSECTION OF THE VERTICAL CENTER LINE OF THE BADGE AND THE CENTER OF THE TOP SCROLL.

   TWO PRONGS LOCATED ON A HORIZONTAL LINE 5/8 ± 1/16 INCH ABOVE THE BOTTOM OF THE BADGE

   PRONGS SHALL BE EQUIDISTANT FROM THE EDGES AND 1-1/4 ± 1/16 INCH ON CENTERS.

2. THE BADGE SHALL BE DAPPED TO A RADIUS OF 3 INCHES ± 1/2 INCH ALONG THE HORIZONTAL PLANE. WIDTH DIMENSION GIVEN WAS TAKEN AFTER DAPPING.

CUSTODIANS:	REVIEW ACTIVITIES:	USER ACTIVITIES:
ARMY		
NAVY		
AIR FORCE	11	99
DLA		CT

PREPARING ACTIVITY:

THE INSTITUTE OF HERALDRY,
UNITED STATES ARMY

Project No. 8455-0248

/FSC 8455/

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.