NOT MEASUREMENT SENSITIVE

MIL-B-41809/20E
14 September 1990
SUPERSEDING
MIL-B-41809/20D
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, JUNIOR ROTC INSTRUCTOR, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809



MATERIAL: Red brass or nickel silver

DIMENSIONS:
HEIGHT (Overall): 1-7/8 inch (4.76 cm) (REF)
WIDTH (Overall): 1-5/8 inch (4.13 cm) (REF)
THICKNESS (Edge of outer scrolls): .060 inch ± .005 inch (0.152 cm ± 0.012 cm)

FINISH: Nickel plated (red brass only), silver plated, oxidized, relieved, matte finish.

1. Attaching device shall be prong and clutch type. One prong shall be located at the intersection of the vertical centerline of the badge and the center of the top scroll. Two prongs shall be located on a horizontal line, 5/8 inch ± 1/16 inch (1.59 cm ± 0.16 cm) above the bottom of the badge, equidistance from each end and 1-1/4 inch ± 1/16 inch (3.18 cm ± 0.16 cm) apart.
2. The badge shall be dapped to a radius of 3 inches ± 1/2 inch (7.62 cm ± 1.17 cm) along the horizontal plane.
3. The badge may be nickel or rhodium plated with a mirror-like polished finish when specified in the procurement document except the silver plating requirement shall not apply.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Air Force - 11

Review activities:
Air Force - 99
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0539)

Source: https://assist.dla.mil - Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.