NOT MEASUREMENT SENSITIVE

MIL-B-41809/21E
21 September 1994
SUPERSEDING
MIL-B-41809/21D
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, MILITARY POLICE, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:

HEIGHT (Overall): 2-3/4 inches (6.99 cm) (REF)
WIDTH (Overall): 1-15/16 inches (4.92 cm) (REF)
THICKNESS (At Thickest Point): 0.060 inch ± 0.005 inch (0.152 cm ± 0.012 cm)

WEIGHT (Assembled): 1.25 ounces ± 0.05 ounces

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be a heavy duty pin with side opening catch. The pin stem shall be 1-3/4 inch ± 1/32 inch (4.45 cm ± 0.08 cm) long. The joint and catch shall be attached on the vertical center line and equidistant from each end. The joint and catch shall be positioned on the same level plane to each other (platform areas on the reverse side may be used for leveling the joint and catch.

3. The badge shall be spherically dapped 1/8 inch ± 1/32 inch (0.32 cm ± 0.08 cm) in depth when measured on the reverse.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:36Z
Check the source to verify that this is the current version before use.