NOT MEASUREMENT SENSITIVE

MIL-B-41809/22C
14 September 1990
SUPERSEDING
MIL-B-41809/22B
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, FOREST SERVICE VOLUNTEER

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.

MATERIAL: Gilding metal

DIMENSIONS:
HEIGHT (Overall): 1-5/16 inch (3.33 cm) (REF)
WIDTH (Overall): 7/8 inch (2.22 cm) (REF)
THICKNESS (Edge): .085 inch ± .005 inch (0.215 cm ± 0.215 cm)

FINISH: Hard enameled, nickel plated, mirror-like polished.

NOTES:
1. Attaching device shall be a pin and top opening catch type. The stem shall be 1 inch ± 1/16 inch (2.54 cm ± 0.16 cm) long. The joint and catch shall be centered on the vertical centerline with the catch located at the bottom.
2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Green	12
Yellow	31

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be a stoning epoxy, have a shore D hardness of 85, and incorporate an ultraviolet inhibitor.
4. The badge may be rhodium plated with a mirror-like polished finish at the option of manufacturer.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-0539)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.