NOT MEASUREMENT SENSITIVE

MIL-B-41809/22D
21 September 1994
SUPERSEDING
MIL-B-41809/22C
14 September 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, FOREST SERVICE VOLUNTEER

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Gilding Metal

FINISH: Hard Enameled, Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Number 16.

DIMENSIONS:
HEIGHT (Overall): 1-5/16 inches (3.33 cm) (REF)
WIDTH (Overall): 7/8 inch (2.22 cm) (REF)
THICKNESS (Edge): 0.085 inch ± 0.005 inch (0.215 cm ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Green	12
Yellow	31

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. Attaching device shall be a pin and top opening catch type. The pin stem shall be 1 inch ± 1/16 inch (2.54 cm ± 0.16 cm) long. The joint and catch shall be centered on the vertical center line with the catch located at the bottom.

5. At the option of the manufacturer, the badge may be rhodium plated with a mirror-like polished finish.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:36Z
Check the source to verify that this is the current version before use.