NOT MEASUREMENT SENSITIVE

MIL-B-41809/25C
14 May 1990
SUPERSEDING
MIL-B-41809/25B
31 December 1978

# MILITARY SPECIFICATION SHEET

## BADGE, IDENTIFICATION, CUTTERMAN, US COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL:
-1, -3: Red brass
-2, -4: Red brass or nickel silver

DASH NO:
-1: Officer (Regular size)
-2: Enlisted Personnel (Regular Size
-3: Officer (Miniature size)
-4: Enlisted Personnel (Miniature size)

DIMENSIONS:
HEIGHT (Overall):
-1, -2: 3/4 inch (1.91 cm) (REF)
-3, -4: 7/16 inch (1.11 cm) (REF)
WIDTH (Overall):
-1, -2: 2-1/2 inch (6.35 cm) (REF)
-3, -4: 1-3/8 inch (3.49 cm) (REF)
THICKNESS (Over shield):
-1, -2: .125 inch ± .005 inch (0.317 cm) ± (0.012 cm)
-3, -4: .090 inch ± .005 inch (0.228 cm) ± (0.012 cm)

FINISH:
-1, -3: Gold plated, matte finish, polished highlights
-2, -4: Nickel plated (red brass only), silver plated, oxidized, relieved, matte finish

NOTES:
1. Attaching device shall be prong and clutch type. The prongs shall be located on the horizontal centerline, equidistant from each end and 2 inch ± 1/64 inch (5.08 cm) ± (0.04 cm) apart for Dash No. 1 and 2 and 1-9/32 inch ± 1/64 inch (3.25 cm) ± (0.04 cm) apart for Dash No. 3 and 4.
2. A mock forcer may be used to bring up the center (shield) of the design on Dash No. 1 and 2.

Custodian:
Army - IH
Navy - SA

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-0500)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:37Z
Check the source to verify that this is the current version before use.