NOT MEASUREMENT SENSITIVE


MIL-B-41809/25D
21 September 1994
SUPERSEDING
MIL-B-41809/25C
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, CUTTERMAN, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL:
-1, -3: Red Brass
-2, -4: Red Brass or Nickel Silver

DASH NO.
-1: Officer, Regular Size
-2: Enlisted Personnel, Regular Size
-3: Officer, Miniature Size
-4: Enlisted Personnel, Miniature Size

FINISH:
-1, -3: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
-2, -4: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Overall):
-1, -2: 3/4 inch (1.91 cm) (REF)
-3, -4: 7/16 inch (1.11 cm) (REF)
WIDTH (Overall):
-1, -2: 2-1/2 inches (6.35 cm) (REF)
-3, -4: 1-3/8 inches (3.49 cm) (REF)
THICKNESS (Over Shield):
-1, -2: 0.125 inch ± 0.005 inch (0.317 cm ± 0.012 cm)
-3, -4: 0.090 inch ± 0.005 inch (0.228 cm ± 0.012 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:37Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. A mock forcer may be used to bring up the center (shield) of the design on Dash No. -1 and -2.

3. Attaching device shall be prong and clutch type. For Dash No. -1 and -2, two prongs shall be located on the horizontal center line, equidistant from each end and 2 inches ± 1/64 inch (5.08 cm ± 0.04 cm) apart. For Dash No. -3 and -4, two prongs shall be located on the horizontal center line, equidistant from each end and 1-9/32 inches ± 1/64 inch (3.25 cm ± 0.04 cm) apart.

Custodian:
Army - IH
Coast Guard - CG

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:37Z
Check the source to verify that this is the current version before use.